Date: 03-02-2025

## BOQ FOR THE PROPOSED INTERIOR WORKS FOR HOLEHONNURU

|          | BOQ FOR THE PROPOSED INTERIO  | DR WORK | S FOR HOL | EHONNURU |        |
|----------|---|---------|-----------|----------|--------|
| Sl.No    | Description   | Qty     | Rate      | Unit     | Amount |
| <u> </u> | NEEDIOD WORKS   |         |           |          |        |
| I        | INTERIOR WORKS:   |         |           |          |        |
| A        | FIXED FURNITURE:  |         |           |          |        |
|          | PARTITIONS  |         |           |          |        |
|          | FULL HEIGHT PARTITIONS - PARTLY   |         |           |          |        |
|          | GLAZED  |         |           |          |        |
| 1.00     | Providing and fixing metal stud dry wall partition  |         |           |          |        |
|          | with following specifications:  |         |           |          |        |
|          | Supporting system comprising of 51mm / 50mm x   |         |           |          |        |
|          | 35mm / 34mm x 0.5mm <u>metal studs</u> <u>at 600mm c/c</u>  |         |           |          |        |
|          | and 51mm / 50mm x 32mm x 0.5mm metal tracks at  |         |           |          |        |
|          | floor, middle, door and ceiling level with joints   |         |           |          |        |
|          | staggered to avoid through joints. The vertical   |         |           |          |        |
|          | members should touch the ceiling with horizontal  |         |           |          |        |
|          | ceiling channel at slab / beam bottom. The rate<br>should also include necessary strengthening with |         |           |          |        |
|          | studs / tracks or channels at doors and other   |         |           |          |        |
|          | openings.   |         |           |          |        |
|          | 12mm Exterior Grade MDF ( EG-MDF) Board   |         |           |          |        |
|          | fixed on both sides with 25mm dry wall screws for   |         |           |          |        |
|          | the entire height of the partition.   |         |           |          |        |
|          | Partition fixed with 1.0mm laminate sheet on both   |         |           |          |        |
|          | sides as per the following:   |         |           |          |        |
|          | Skirting level upto 100 mm from FFL to have   |         |           |          |        |
|          | 1.0mm laminate of dark blue colour From 100mm to 300mm level to have 1mm                            |         |           |          |        |
|          | Laminate (agua blue color)  |         |           |          |        |
|          | From 300 mm level to 1070 mm level to have 1mm  |         |           |          |        |
|          | Laminate (white color)  |         |           |          |        |
|          | From 1070 mm level to 2135 mm level to have   |         |           |          |        |
|          | 8mm clear float glass fixed with with 85mm x  |         |           |          |        |
|          | 15mm alround jamb and 12mm x 12mm button  |         |           |          |        |
|          | beading on both sides of the glass, to a neat finish as   |         |           |          |        |
|          | per drawings and directions etc., complete.The glass  |         |           |          |        |
|          | sizes subject to design drawing etc.  |         |           |          |        |
|          | From 2135mm level to 2235mm level 1mm   |         |           |          |        |
|          | Laminate (aqua blue color) on both sides as shown   |         |           |          |        |
| -        | in drawing.  Partition above 2235mm level to have 1mm   |         |           |          |        |
|          | Laminate (white color) as shown in drawing.   |         |           |          |        |
|          | All beech wood members to have minimum two  |         |           |          |        |
|          | coats of LOW VOC or NO VOC white duco paint   |         |           |          |        |
|          | finish.   |         |           |          |        |
|          | All sections used should adhere to the manufacturers  |         |           |          |        |
|          | guidelines and the contractor has to submit   | 8.80    | Sq.M.     |          |        |
|          | certificate from the manufacturer on usage of their   | 0.00    | 54.171.   |          |        |
|          | specified sections.   |         |           |          |        |
|          | ELL I HEIGHT DADITITONS SOLID   |         |           |          |        |
| 2.00     | FULL HEIGHT PARITITONS - SOLID  Same as full height partition partly glazed above but               |         |           |          |        |
| 2.00     | for Fully Solid Partitions without glass panels and   |         |           |          |        |
|          | other specifications remaining the same. Glass panel  |         |           |          |        |
|          | area from 1220mm lvl to 2135mm lvl to be replaced   |         |           |          |        |
|          | with soid partition with 1mm Laminate (white  |         |           |          |        |
|          | color)  |         |           |          |        |
|          | Partiton height will be measured up to false ceiling  | 6.25    | Sq.M.     |          |        |
|          | height only.  | 0.23    | 5q.1v1.   |          |        |
|          |   |         |           |          |        |

| Sl.No  | Description   | Qty   | Rate    | Unit | Amount |
|--------|---|-------|---------|------|--------|
| 51.110 | HALF HEIGHT PARTITIONS  | Qty   | Kate    | Unit | Amount |
|        | HALF (1500MM) HEIGHT PARTLY GLAZED  |       |         |      |        |
|        | PARTITIONS FOR SW   |       |         |      |        |
| 3.00   | Providing and fixing half height partition with                           |       |         |      |        |
|        | following specifications:   |       |         |      |        |
|        | (a) Supporting system comprising of (US Boral /                           |       |         |      |        |
|        | Gyproc / Armstrong suspension system make)                                |       |         |      |        |
|        | 50mm x 35mm metal studs of 0.55mm thickness at                            |       |         |      |        |
|        | 600 mm c/c and 50mm x 32mm metal tracks at                                |       |         |      |        |
|        | floor, middle and 915mm level with joints staggered                       |       |         |      |        |
|        | to avoid through joints. The rate should also include                     |       |         |      |        |
|        | necessary strengthening with studs / tracks or                            |       |         |      |        |
|        | channels at openings.   |       |         |      |        |
|        | (b) 12mm HDF (High Density Fiber) Board with                              |       |         |      |        |
|        | 1mm laminate on both sides as per drawings.                               |       |         |      |        |
|        | Wicket gate is to be provided with godrej night                           |       |         |      |        |
|        | latch, handles etc.   |       |         |      |        |
|        | (c) MDF beading with duco painting shall be                               |       |         |      |        |
|        | provided for the partition edges. (which shall be                         |       |         |      |        |
|        | measured seperately) d) The total height of the partition including glass |       |         |      |        |
|        |   | 16.60 | Sq.M.   |      |        |
|        | with etching is 1500 mm.  |       |         |      |        |
|        | DOORS IN PARTITIONS   |       |         |      |        |
|        | DOORS IN FACTITIONS   |       |         |      |        |
| 4.00   | Providing and fixing 32mm thick solid core flush                          |       |         |      |        |
|        | shutter with 85mm x 35mm Teak wood/ beech                                 |       |         |      |        |
|        | wood frame with rebate alround the jamb and                               |       |         |      |        |
|        | shutter fixed with 1mm Laminate as specified on                           | 0.00  | Sq.M    |      |        |
|        | both sides with glass panel of 8mm clear float                            | 0.00  | Squii   |      |        |
|        | glass fixed with 19 x 19mm beading on both sides                          |       |         |      |        |
|        | and glass pasted with 3M privacy film as per design.                      |       |         |      |        |
|        | All BW frame to be Duco painted in approved                               |       |         |      |        |
|        | shade with low VOC or nor VOC white duco paint.                           |       |         |      |        |
|        | ·   |       |         |      |        |
|        | Rate to include all necessary hardware incl the                           |       |         |      |        |
|        | following 3 nos SS hinges, door closure, door buffer, door                |       |         |      |        |
|        | stopper, SS tower bolts etc complete                                      |       |         |      |        |
|        | (Cash officer, BM cabin )   |       |         |      |        |
|        | ,                                   |       |         |      |        |
|        | WICKET GATE - for SWO Counters  |       |         |      |        |
| 5.00   | Wicket gate specified below may also be used with                         |       |         |      |        |
|        | other low height partitions elsewhere in the branch                       |       |         |      |        |
|        | if required, with height of wicket gate modified                          |       |         |      |        |
|        | suitably  |       |         |      |        |
|        | Providing wicket gate made of 32mm solid flush                            |       |         |      |        |
|        | door with alround PVC edge banding / BW lipping                           |       |         |      |        |
|        | and height to match low height partitions. Wicket                         |       |         |      |        |
|        | gate shall be finished with 1.0mm laminate sheet on                       |       |         |      |        |
|        | both faces and shall fixed to partition with 85mm x                       | 6.00  | Sq.M.   |      |        |
|        | 35mm beech wood frame on sides with SS hinges                             | 0.00  | 54.IVI. |      |        |
|        | as required with handles, stoppers, self lock etc                         |       |         |      |        |
|        | complete. Wicket gate shall have self lock from                           |       |         |      |        |
|        | inside fixed at lower height as per instructions and                      |       |         |      |        |
|        | Bank requirement  |       |         |      |        |
|        |   |       | l       |      |        |

| CLAT  | D : (:  | 04    | D 4   | TT *4 |        |
|-------|---|-------|-------|-------|--------|
| Sl.No | Description  EIVED CLASS WORKS FOR BARTITIONS   | Qty   | Rate  | Unit  | Amount |
|       | FIXED GLASS WORKS FOR PARTITIONS: (12MM TOUGHENED GLASS)  |       |       |       |        |
| 6.00  | Providing, making and fixing in position Fixed  |       |       |       |        |
| 0.00  | 12mm toughened glass as fixed glass from  |       |       |       |        |
|       | Skirting/ Floor level upto available Ceiling / beam /   |       |       |       |        |
|       | lintel level and inline with wooden parttions / doors   |       |       |       |        |
|       |   |       |       |       |        |
|       | etc as per layout plan. The glass is to be fixed onto<br>the ply/Exterior Grade MDF base with patch |       |       |       |        |
|       | fittings and all the edges of the glass to be machine   |       |       |       |        |
|       | polished for a smooth finish. The work includes   |       |       |       |        |
|       | cost of all materials, approved hardware, making  | 6.00  | Sq.M. |       |        |
|       | necessary template before toughening of glass and   |       |       |       |        |
|       | fixing the same as per site conditions to a neat  |       |       |       |        |
|       | finished work as per drawings and directions  |       |       |       |        |
|       | including silicon sealant between glass panels etc.,  |       |       |       |        |
|       | complete.Glass from floor levev With ss channel   |       |       |       |        |
|       | fixed to floor only for main entrance   |       |       |       |        |
|       |   |       |       |       |        |
|       |   |       |       |       |        |
|       | 12MM TOUGHENED GLASS MAIN   |       |       |       |        |
|       | ENTRANCE DOOR AND PARTITION   |       |       |       |        |
| 7.00  | DOORS:  |       |       |       |        |
| 7.00  | Providing, making and fixing in position Fixed  |       |       |       |        |
|       | 12mm toughened glass openable shutters work   |       |       |       |        |
|       | as per specifications given below and for the   |       |       |       |        |
|       | openings mentioned. <b>Main Entrance Glass</b> Work comprising of Door opening of approximate size  |       |       |       |        |
|       | ' ' ' ' ' '   |       |       |       |        |
|       | 1830mm x 2135mm - 2440mm in two leaves, and   |       |       |       |        |
|       | Partition Doors of approximate size 900 - 1065mm x 2135mm - 2440mm. The entire work to be done      |       |       |       |        |
|       | as per site conditions with following specifications  |       |       |       |        |
|       | etc., complete as directed.   |       |       |       |        |
|       |   |       |       |       |        |
|       | (a) Entrance door - Providing, fixing in position   |       |       |       |        |
|       | glazed entrance Double door and Single door with  |       |       |       |        |
|       | patch fitting or approved make (Double Door   |       |       |       |        |
|       | approx. Size: 1830mm - 1525mm x 2440mm -  |       |       |       |        |
|       | 2135mm and Single Door approx. Size: 900mm -  |       |       |       |        |
|       | 1220mm x 2440mm - 2135mm using 12mm   |       |       |       |        |
|       | toughened glass edge polished. The Door to consist  |       |       |       |        |
|       | of Heavy Duty Floor spring, Upper Patch, Bottom   |       |       |       |        |
|       | Patch, Lock Keeper Plate, Euro Profile Cylinder   |       |       |       |        |
|       | (EPC), "H" Type Handle 32 x 600mm, Door Lock at   |       |       |       |        |
|       | 915 ht complete as per drawing.   |       |       |       |        |
|       | (b) The work includes cost of all materials,  |       |       |       |        |
|       | approved hardware, making necessary template  | 4.50  | G 3.5 |       |        |
|       | before toughening of glass and fixing the same as   | 4.50  | Sq.M. |       |        |
| 1     | per site conditions to a neat finished work as per  |       |       |       |        |
|       | drawings and directions etc., complete.   |       |       |       |        |
|       | WALL PANELLING:   |       |       |       |        |
|       | WALL PANELLING IN BANKING HALL  |       |       |       |        |
| 8.00  | Same as Full height Partition - Solid, as per relevant  |       |       |       |        |
|       | specifications above, but for Wall Panelling. The   |       |       |       |        |
| 1     | basic frame work to comprise all Exterior Grade   |       |       |       |        |
|       | MDF (EG-MDF) cladding as specified, but only on   |       |       |       |        |
| 1     | one side, to a neat job as per drawings and   |       |       |       |        |
|       | directions etc., complete.  |       |       |       |        |
|       | Providing 18mm thick Exterior Grade MDF   |       |       |       |        |
| 1     | jamb for door and window openings of suitable   |       |       |       |        |
|       | depth as per site conditions and laminated with 1mm thk laminate to match design as per partitions. |       |       |       |        |
|       | min the familiate to match design as per partitions.  |       |       |       |        |
|       | All beech wood members to have NO VOC or LOW  | 22 00 | Ca M  |       |        |
|       | VOC white duco paint finish.  | 23.80 | Sq.M. |       |        |
|       |   |       |       |       |        |
| 0.00  | COLUMN PANELLING  Drawiding and fixing metal stud column nanelling                                  |       |       |       |        |
| 9.00  | Providing and fixing metal stud column panelling with following specifications:                     |       |       |       |        |
|       | with following specifications.  |       |       | L     |        |

| Sl.No  | Description   | Otri | Rate  | Unit | Amount |
|--------|---|------|-------|------|--------|
| 51.110 | Support metal framework on 2 shorter sides made of                                | Qty  | Nate  | Unit | Amount |
|        | the following   |      |       |      |        |
|        | Supporting system comprising of 51mm / 50mm x                                     |      |       |      |        |
|        | 35mm / 34mm x 0.5mm metal studs framework at                                      |      |       |      |        |
|        | 600mm c/c and 51mm / 50mm x 32mm x 0.5mm  |      |       |      |        |
|        | metal tracks at floor, middle, door and ceiling level                             |      |       |      |        |
|        | with joints staggered to avoid through joints. The                                |      |       |      |        |
|        | vertical members should touch the ceiling with                                    |      |       |      |        |
|        | horizontal ceiling channel at slab / beam bottom.                                 |      |       |      |        |
|        | The rate should also include necessary strengthening                              |      |       |      |        |
|        | with study / tracks or channels at doors and other                                |      |       |      |        |
|        | onenings  |      |       |      |        |
|        | 12mm EG-MDF fixed on all four sides with 25mm                                     |      |       |      |        |
|        | dry wall screws for the entire height of the partition.                           |      |       |      |        |
|        | The 12mm EG-MDF fixed onto the metal  |      |       |      |        |
|        | framework on the 2 shorter sides and directly onto                                |      |       |      |        |
|        | the column on the 2 longer sides with levelling                                   |      |       |      |        |
|        | gattas etc as required  |      |       |      |        |
|        | Additional 12mm EG MDF - 100mm high fixed at                                      |      |       |      |        |
|        | skirting level  |      |       |      |        |
|        | Column panelling to be finished as per the following                              |      |       |      |        |
|        | :   |      |       |      |        |
|        | Skirting level upto 100mm from FFL to have  |      |       |      |        |
|        | 1.0mm laminate of dark blue colour  |      |       |      |        |
|        | From 100mm to 2135mm level to have 12mm MDF                                       |      |       |      |        |
|        | Grill board (JALI type MDF sheet) fixed on the EG-                                |      |       |      |        |
|        | MDF on the two longer sides of the column as                                      |      |       |      |        |
|        | shown in drawing and painted with white duco                                      |      |       |      |        |
|        | paint. The base EG-MDF shall be painted with                                      |      |       |      |        |
|        | premium emulsion paint of colour - CORAL  |      |       |      |        |
|        | RADIANCE-code No 2015 of Asian Apcolite   |      |       |      |        |
|        | Emulsion or equivalent - before fixing the MDF                                    |      |       |      |        |
|        | Grill board   |      |       |      |        |
|        | Column Panelling to have 6mm toughened  |      |       |      |        |
|        | lacquered glass - ONE SINGLE PIECE for each                                       |      |       |      |        |
|        | side, pasted with adhesive/sealant onto the existing                              |      |       |      |        |
|        | EG-MDF and of blue colour as per Colour Code                                      |      |       |      |        |
|        | No. RAL 5017-Traffic Blue - fixed on two shorter                                  |      |       |      |        |
|        | sides of the column, to a neat finish as per drawings                             |      |       |      |        |
|        | and directions etc., complete with 12mm x 12mm                                    |      |       |      |        |
|        | button beading on the corners   |      |       |      |        |
|        | 21 2 31   |      |       |      |        |
|        | Column Panelling above 2135mm level to have                                       |      |       |      |        |
|        | 1mm White colour, Matt finish Laminate on all                                     |      |       |      |        |
|        | four sides as shown in drawing.   |      |       |      |        |
|        | All beech wood members and MDF Grill Board to                                     |      |       |      |        |
|        | have minimum two coats of LOW VOC or NO   |      |       |      |        |
| -      | VOC white duco paint finish. All sections used should adhere to the manufacturers |      |       |      |        |
|        | guidelines and the contractor has to submit                                       |      |       |      |        |
|        |   | 0.00 | Sq.M. |      |        |
|        | certificate from the manufacturer on usage of their specified sections.           |      |       |      |        |
| -      | specified sections.   |      |       |      |        |
|        | WALLPAPER   |      |       |      |        |
| 10.00  | Providing and fixing approved quality wall paper                                  |      |       |      |        |
| 10.00  | of washable grade including all adhesive, cutting,                                |      |       |      |        |
|        | pasting etc complete.   |      |       |      |        |
|        | (Basic price Rs. 3800 per roll excluding tax,                                     |      |       |      |        |
| -      |   |      |       |      |        |
|        | Note: Measurement will be taken only for wall                                     | 3.20 | Sqm   |      |        |
| -      | paper actually pasted at site.  |      | -     |      |        |
|        |   |      |       |      |        |

| CLAI  | D   | 0.    |       | <b>T</b> T • |        |
|-------|---|-------|-------|--------------|--------|
| Sl.No | Description  EALSE CELLING:   | Qty   | Rate  | Unit         | Amount |
| 11.00 | FALSE CEILING: Providing, making and fixing in position the                     |       |       |              |        |
| 11.00 | following types of different false ceilings with                                |       |       |              |        |
|       | ~ **  |       |       |              |        |
|       | different materials as specified below for a finished                           |       |       |              |        |
|       | item of work as per drawings and directions etc.,                               |       |       |              |        |
|       | Grid False Ceiling : Mineral Fibre Tile   |       |       |              |        |
| 12.00 | Providing & Fixing of Mineral Fibre Acoustical                                  |       |       |              |        |
| 12.00 | Suspended Ceiling System with 15mm Tiles and                                    |       |       |              |        |
|       | Exposed GRID. The tiles should have Humidity                                    |       |       |              |        |
|       | Resistance (RH) of 90% - 99%, NRC 0.5, Light                                    |       |       |              |        |
|       | Reflectance $\geq 87\%$ , Thermal Conductivity $k = 0.052$                      |       |       |              |        |
|       | 0.057 w/m K, Colour White, Fire Performance UK                                  |       |       |              |        |
|       | Class 0 / Class 1 (BS 476 pt - 6 &7) in module size                             |       |       |              |        |
|       | of 600 x 600 x 16mm, suitable for Green Building                                |       |       |              |        |
|       | application, with Recycled content of 30% - 45%.                                |       |       |              |        |
|       | application, with Recycled content of 5070 - 4570.                              |       |       |              |        |
|       | The tile shall be laid on Misusline / Cilhauette                                |       |       |              |        |
|       | The tile shall be laid on Microline / Silhouette                                |       |       |              |        |
|       | profile grid system with 15mm - 16mm white                                      |       |       |              |        |
|       | flanges incorporating a 6mm central reveal in                                   |       |       |              |        |
|       | white/black colour and with a web height of 38mm                                |       |       |              |        |
|       | and a load carrying capacity of minimum 8 Kgs/M2                                |       |       |              |        |
|       | & minimum pull out strength of 100 Kgs.   |       |       |              |        |
|       | Microline / Silhouette, Main Runners & Cross Tees                               |       |       |              |        |
|       | to have mitred ends & "birdsmouth" notches to                                   |       |       |              |        |
|       | provide mitred cruciform junctions. The T Sections                              |       |       |              |        |
|       | have a Galvanizing of 90 grams per M2 and need to                               |       |       |              |        |
|       | be installed with Suspension system as per                                      |       |       |              |        |
|       | manufacturers details.  |       |       |              |        |
|       | The Instalation to comprise main runner spaced at                               |       |       |              |        |
|       | 1200mm centres securely fixed to the structural                                 |       |       |              |        |
|       | soffit using US Boral / Gyproc / Armstrong                                      |       |       |              |        |
|       | suspension system (specifications below) at                                     |       |       |              |        |
|       | 1200mm maximum centre. The First/Last   |       |       |              |        |
|       | suspension system at the end of each main runner                                |       |       |              |        |
|       | should not be greater than 450mm from the adjacent                              |       |       |              |        |
|       | wall.   |       |       |              |        |
|       | Flush fitting 1200mm long cross tees to be                                      |       |       |              |        |
|       | interlocked between main runners at 600mm centre                                |       |       |              |        |
|       | to form 1200 x 600 mm module. Cut cross tees                                    |       |       |              |        |
|       | longer than 600mm require independent support.                                  |       |       |              |        |
|       | 600 x 600mm module to be formed by fitting                                      | 80.00 | Sq.M. |              |        |
|       | 600mm long flush fitting cross tees centrally                                   |       |       |              |        |
|       | between the 1200 mm cross tees. Perimeter trim to                               |       |       |              |        |
|       | be Wall angles of size 3000mm x 19mm x 19mm,                                    |       |       |              |        |
|       | secured to walls at 450 mm maximum centres.                                     |       |       |              |        |
|       |   |       |       |              |        |
|       | PLAIN GYPSUM FALSE CEILING  |       |       |              |        |
| 13.00 | Providing and fixing Concealed Grid suspended                                   |       |       |              |        |
| 13.00 | ceiling system of 12.5mm Gypsum Boards /  |       |       |              |        |
|       | Standard Plaster Boards fixed to ceiling Frame                                  |       |       |              |        |
|       |   |       |       |              |        |
|       | Work as per manufacturers instructions and details                              |       |       |              |        |
|       | for a concealed grid key lock suspended ceiling system consisting of following: |       |       |              |        |
|       |   |       |       |              |        |
|       | 27 x 37 x 1.6mm Soffit Clip, 5mm suspension rod/                                |       |       |              |        |
|       | 25 x 10 x 0.5mm Ceiling Angle, adjustable spring                                |       |       |              |        |
|       | loaded suspension clip / 2.64mm dia Connecting                                  |       |       |              |        |
|       | Clip, 20 x 28 x 30 x 0.5mm Perimeter Channel, Top                               |       |       |              |        |
|       | Cross Rail of 3000mm long of 0.55BMT Furring                                    |       |       |              |        |
|       | Channel / 15 x 45 x 15 x 0.9mm Intermediate                                     |       |       |              |        |
|       | Channel and 4000mm long made of 0.5mm BMT                                       |       |       |              |        |
|       | the Top Cross Rail / 80 x 26 x 0.5mm Ceiling                                    |       |       |              |        |
|       | Section to be suspended from ceiling at every                                   |       |       |              |        |
|       | 1200mm and Furring / Intermediate Channel to be                                 |       |       |              |        |
|       | fixed to Top Cross Rail / Ceiling Section at every                              |       |       |              |        |
|       | 600mm to make a grid of 1200 x 600mm.   |       |       |              |        |
|       | ı   |       | L     | L            | I .    |

| CLN   | D 1.1   | 0.4    | D 4   | ***  |        |
|-------|---|--------|-------|------|--------|
| Sl.No | Description   | Qty    | Rate  | Unit | Amount |
|       | All sections used should adhere to the manufacturers                    |        |       |      |        |
|       | guidelines and the contractor has to submit                             |        |       |      |        |
|       | certificate from the manufacturer on usage of their specified sections. |        |       |      |        |
|       | Further the rates to include cutouts for lighting                       |        |       |      |        |
|       | fixtures / AC grilles / Fire Alarm Detectors etc.,                      |        |       |      |        |
|       | along with necessary strengthening and supports for                     |        |       |      |        |
|       | fixing of these. The board joints are to be flush                       |        |       |      |        |
|       | finished with jointing compound and paper tape                          |        |       |      |        |
|       | etc., complete as directed.   |        |       |      |        |
|       | The ceiling shall be finished with 2 coats of                           |        |       |      |        |
|       | premium emulsion paint over primer putty etc                            | 45.00  | Sq.M. |      |        |
|       | complete  |        |       |      |        |
|       |   |        |       |      |        |
|       | VERTICAL FACES IN FALSE CEILING -                                       |        |       |      |        |
|       | UPTO 150mm HEIGHT   |        |       |      |        |
| 14.00 | Same as Plain false ceiling above but for vertical                      |        |       |      |        |
|       | faces in false ceiling as per drawing including cut                     | 126.00 | Rmt   |      |        |
|       | outs for AC grilles etc., complete as directed.                         |        |       |      |        |
|       |   |        |       |      |        |
|       | STORAGE UNITS:  |        |       |      |        |
|       | LOW HEIGHT STORAGE UNITS  |        |       |      |        |
| 15.00 | Providing, making and placing in position Storage                       |        |       |      |        |
|       | Units of 1220mm high abutting wall and 760mm                            |        |       |      |        |
|       | high as back credenza or abutting partition made in                     |        |       |      |        |
|       | 18mm EG-MDF to all members except table top                             |        |       |      |        |
|       | and 25mm block board for table top and 8mm EG                           |        |       |      |        |
|       | MDF for backing sheet. The top and front facia of                       |        |       |      |        |
|       | the storage unit to have 1mm thick laminate. All                        |        |       |      |        |
|       | other exposed faces of the unit to have 1mm                             |        |       |      |        |
|       | Laminate as specified and all unexposed faces to                        |        |       |      |        |
|       | have 0.8mm Laminate. NO VOC or LOW VOC                                  |        |       |      |        |
|       | white duco paint finish for all wooden members and                      |        |       |      |        |
|       | all necessary hardware viz., 'W' or wing hinges,                        |        |       |      |        |
|       | locks, handles, tower bolts etc., and PVC edge                          |        |       |      |        |
|       | banding / BW lipping 20mm x 6mm etc., as per                            |        |       |      |        |
|       | drawings and directions etc., complete.                                 |        |       |      |        |
|       | Storage units shall have a internal horizontal shelf of                 |        |       |      |        |
|       | 19mm block board finished with 0.8mm laminate                           |        | 0.34  |      |        |
|       | on both sides with PVC edge banding / BW lipping                        | 3.10   | Sq.M. |      |        |
|       | polished malanine finish  |        |       |      |        |
|       |   |        |       |      |        |
| 16.00 | FULL HEIGHT STORAGE UNITS   | 7.50   | Sq.M  |      |        |
|       | Same as above, but for heights upto 2100mm                              |        |       |      |        |
|       |   |        |       |      |        |
| В     | LOOSE FURNITURE:  |        |       |      |        |
|       | TARLES / GOLDVETTE  |        |       |      |        |
|       | TABLES / COUNTERS   |        |       |      |        |
| 17.00 | BRANCH HEAD TABLE:  |        |       |      |        |
| 17.00 | BM tables size 1950mm x 900mm x 760mm and                               |        |       |      |        |
|       | Side Table 1065mm x 450mm x 750mm                                       |        |       |      |        |
|       | Providing, making and placing in position                               |        |       |      |        |
|       | Executive Table and Side Table with following                           |        |       |      |        |
|       | specifications.   |        |       |      |        |
|       | Main Table and side Table top and to be made in                         |        |       |      |        |
|       | 25mm block board with 1mm thk laminate. The                             |        |       |      |        |
| 1     | front side of the table to have a inverted " C " made                   |        |       |      |        |
| 1     | with 2 x 18mm thick EG-MDF cladded with 1mm                             |        |       |      |        |
|       | thick laminate on the front and the verticals towards                   |        |       |      |        |
|       | the modesty panel. The modesty panel to have                            |        |       |      |        |
|       | 18mm EG-MDF cladded with 6mm thk toughened                              |        |       |      |        |
|       | lacquered glass in blue colour as specified.                            |        |       |      |        |
|       | The H.I. Hahamad table too an electrical state of                       |        |       |      |        |
|       | The "L" shaped table top on the back side to have                       |        |       |      |        |
|       | 50mm edge alround and to be cladded with 1.25mm                         |        |       |      |        |
|       | thick PVC laminate.   |        |       |      |        |

| Sl.No  | Description   | Qty  | Rate  | Unit | Amount  |
|--------|---|------|-------|------|---------|
| 511110 | All other members to be with 18mm EG-MDF and  | ~    | Tutt  | Cint | rimount |
|        | all exposed faces of the table to have 1.25mm thick   |      |       |      |         |
|        | PVC lamiante as specified.  |      |       |      |         |
|        | All the edges of 18mm EG-MDF to have PVC  |      |       |      |         |
|        | edge banding / BW lipping 20mm x 6mm maline   |      |       |      |         |
|        | polished.   |      |       |      |         |
|        | One readymade CPU mobile pedestal.  |      |       |      |         |
|        | One Molded <b>Key Board Tray</b> with channels etc.,  |      |       |      |         |
|        | One Three Drawer Unit made with 18mm EG-  |      |       |      |         |
|        | MDF and 12mm EG-MDF. The unit to have 3nos  |      |       |      |         |
|        | equal drawers. The rate to include all necessary  |      |       |      |         |
|        | hardware viz., telescopic drawer channels, handles,   |      |       |      |         |
|        | locks, etc., and edges finished with PVC edge   |      |       |      |         |
|        | banding / 20mm x 6mm beech wood edge lipping  |      |       |      |         |
|        | etc   |      |       |      |         |
|        | Side Table having one pedestal unit with 450mm  |      |       |      |         |
|        | wide having one drawer & one shutter with 1no   |      |       |      |         |
|        | internal shelf made with 18mm EG-MDF and  |      |       |      |         |
|        | 19mm plywood all laminated and with necessary   |      |       |      |         |
|        | hardware viz., 'W' hinges, handles, locks, tower bolts, etc., and PVC edge banding / 20mm x 6mm |      |       |      |         |
|        | beech wood edge lipping etc   |      |       |      |         |
|        | All the unexposed faces to have <b>0.8mm Laminate.</b>  |      |       |      |         |
|        |   |      |       |      |         |
|        | Ready Made Modular Foot Rest - 400mm x  |      |       |      |         |
|        | 350mm x 65mm.   |      |       |      |         |
|        | The cost to include all materials, labour etc., for a   |      |       |      |         |
|        | finished item of work as per drawings and directions  | 1.00 | Each. |      |         |
|        | etc., complete.   |      |       |      |         |
|        | CDAHAZ MITDA / TECH MITDA TADI E.   |      |       |      |         |
|        | GRAHAK MITRA / TECH MITRA TABLE: GRAHAK MITRA TABLE:  |      |       |      |         |
|        | Size: 1525mm x 610mm x 760mm  |      |       |      |         |
| 18.00  | Providing, making and placing in position Grahak  |      |       |      |         |
| 10.00  | Mitra Table with following specifications.  |      |       |      |         |
|        | Main Table Top to have 25mm block board with  |      |       |      |         |
|        | 1mm thick laminate. The vertical supports of the  |      |       |      |         |
|        | table is to be made with two side boxing of 75mm x  |      |       |      |         |
|        | 700mm x 950 mm made with 18mm EG-MDF and  |      |       |      |         |
|        | the front side boxing to 100mm x 400mm x 950mm  |      |       |      |         |
|        | on either sides and central boxing of 150mm x   |      |       |      |         |
|        | 420mm x 1050mm, all made with <b>18mm EG-MDF</b>  |      |       |      |         |
|        | finished with 1.0mm laminate on exposed sides.  |      |       |      |         |
|        |   |      |       |      |         |
|        | The front of the table to have a 420mm x 1050mm   |      |       |      |         |
|        | proud portion with provision for cove lighting at   |      |       |      |         |
|        | bottom and this central portion to be cladded with  |      |       |      |         |
| -      | 1mm thick laminate. All other members to be with 18mm EG-MDF and                                |      |       |      |         |
|        | all exposed faces of the table to have 1mm  |      |       |      |         |
|        | Laminate as specified to be used.   |      |       |      |         |
|        | All the edges of 18mm EG-MDF to have 20mm x   |      |       |      |         |
|        | 6mm beech wood /PVC edge banding.   |      |       |      |         |
|        | One readymade CPU mobile pedestal.  |      |       |      |         |
|        | One Molded Key Board Tray with channels etc.,   |      |       |      |         |
|        | One pedestal of 400mm width having Three Drawer   |      |       |      |         |
|        | Unit made with 18mm EG-MDF and 12mm EG-   |      |       |      |         |
|        | MDF. The unit to have one vertical filing drawer at   |      |       |      |         |
| 1      | bottom and two equal drawers on top. The rate to  |      |       |      |         |
|        | include all necessary hardware viz., telescopic   |      |       |      |         |
|        | drawer channels, handles, locks, etc., and 20mm x   |      |       |      |         |
|        | 6mm beech wood /PVC edge banding etc.,  |      |       |      |         |
|        |   |      |       |      |         |
|        | All the unexposed faces to have 0.8mm Laminate.   |      |       |      |         |
|        | Ready Made Modular Foot Rest - 400mm x  |      |       |      |         |
|        | 350mm x 65mm.   |      |       |      |         |

| Sl.No  | Description  | Qty  | Rate  | Unit | Amount |
|--------|--|------|-------|------|--------|
| 51.110 | The cost to include all materials, labour etc., for a  | Qij  | Rate  | Cint | Amount |
|        | finished item of work as per drawings and directions   | 0.00 | Each. |      |        |
|        | etc., complete.  |      |       |      |        |
| 10.00  | T. 1. 1500 1650 760 760  |      |       |      |        |
| 19.00  | Table: 1500 - 1650mm x 760mm x 760mm  Providing, making and placing in position Sales          |      |       |      |        |
|        | Table with following specifications.   |      |       |      |        |
|        | Main Table and side Table top and to be made in  |      |       |      |        |
|        | 25mm block board with 1mm thick lamiante on  |      |       |      |        |
|        | top. The front side of the table to have a inverted "  |      |       |      |        |
|        | U " made with 2 x 18mm thick EG-MDF finished   |      |       |      |        |
|        | with 1.0mm laminate incuding the verticals towards   |      |       |      |        |
|        | the modesty panel. The modesty panel to have 18mm EG-MDF cladded with 1mm Laminate as          |      |       |      |        |
|        | specified.   |      |       |      |        |
|        | The " L " shaped table top on the back side along  |      |       |      |        |
|        | with side tabe to have 49mm edge alround, which is   |      |       |      |        |
|        | to be achieved by adding a 75mm piece of <b>18mm</b>   |      |       |      |        |
|        | EG-MDF to the table top from bottom.   |      |       |      |        |
|        | All other members to be with 18mm EG-MDF and   |      |       |      |        |
|        | all exposed faces of the table to have 1.0mm laminate as specified.                            |      |       |      |        |
|        | All the edges of <b>18mm EG-MDF</b> to have 20mm x   |      |       |      |        |
|        | 6mm beech wood lipping /PVC edge banding.  |      |       |      |        |
|        | One readymade CPU mobile pedestal.   |      |       |      |        |
|        | One Molded Key Board Tray with channels etc.   |      |       |      |        |
|        | One Three Drawer Unit made with 18mm EG-   |      |       |      |        |
|        | MDF and 12mm EG-MDF. The unit to have 3  |      |       |      |        |
|        | equal drawers. The rate to include all necessary   |      |       |      |        |
|        | hardware viz., telescopic drawer channels, handles,  |      |       |      |        |
|        | locks, etc., and 20mm x 6mm beech wood /PVC  |      |       |      |        |
|        | All the unexposed feese to have 0.8mm Laminate   |      |       |      |        |
|        | All the unexposed faces to have 0.8mm Laminate.  |      |       |      |        |
|        | Ready Made Modular Foot Rest - 400mm x 350mm x 65mm.   |      |       |      |        |
|        | The cost to include all materials, labour etc., for a  |      |       |      |        |
|        | finished item of work as per drawings and directions   | 2.00 | Each  |      |        |
|        | etc., complete.  |      |       |      |        |
| -      | CINCLE WINDOW COLINTERS.   |      |       |      |        |
|        | SINGLE WINDOW COUNTERS:<br>Counter: 1500-1650mm x 900-975mm x 760mm                            |      |       |      |        |
|        | Counter: 1300-1030mm x 700-773mm x 700mm   |      |       |      |        |
| 20.00  | Side Runner: 1050 - 1220mm x 450mm x   |      |       |      |        |
|        | 760mm.   |      |       |      |        |
|        | Providing, making and placing in position Single   |      |       |      |        |
|        | Window Counters along with necessary Half height   |      |       |      |        |
|        | partitions above (The partitions will be measured  |      |       |      |        |
|        | and paid as per Half Height Partitions) with<br>following specifications and as per dimensions |      |       |      |        |
|        | specified.   |      |       |      |        |
|        | Table top of main table and side table to be made in   |      |       |      |        |
|        | 25mm block board with 1mm thk laminate (SF   |      |       |      |        |
|        | finish) and double thickness at edges alround. The   |      |       |      |        |
|        | acrylic solid surface to continue in the <b>front side</b>                                     |      |       |      |        |
|        | with curvature from the front table top to the   |      |       |      |        |
|        | modesty panel in front with cove lighting provision.   |      |       |      |        |
|        | All other members to be with <b>18mm EG-MDF</b> / 2  |      |       |      |        |
|        | Nos. of 6mm Flexi Plywood in curvature (which  |      |       |      |        |
|        | should be achieved with a frame work of 50mm x   |      |       |      |        |
|        | 50mm sal wood frame to be fixed from the front   |      |       |      |        |
|        | modesty panel / apron and the bottom of this niche   |      |       |      |        |
|        | to have provision of cove lighting with LED strips)  |      |       |      |        |
|        | and all exposed faces of the table to have 1mm   |      |       |      |        |
|        | Laminate as specified in the drawing to be used.   |      |       |      |        |
| L      |  |      | L     | L    |        |

| Sl.No | Description  | Qty  | Rate  | Unit | Amount |
|-------|--|------|-------|------|--------|
|       | Front of SWO Counter to have about 100mm high        |      |       |      |        |
|       | skirting made of 12mm EG-MDF board fixed at          |      |       |      |        |
|       | floor level and finished with 1.0mm laminate of      |      |       |      |        |
|       | dark blue colour                                     |      |       |      |        |
|       | All the edges of 18mm EG-MDF to have 20mm x          |      |       |      |        |
|       | 6mm beech wood /PVC edge banding.                    |      |       |      |        |
|       | One readymade CPU mobile pedestal.                   |      |       |      |        |
|       | One Molded Key Board Tray with channels etc.,        |      |       |      |        |
|       | One Three Drawer Unit made with 18mm EG-             |      |       |      |        |
|       | MDF and 12mm EG-MDF. The unit to have 3nos           |      |       |      |        |
|       | equal drawer and each drawer shall be fixed with     |      |       |      |        |
|       | self locks. Drawers shall have Cash Denomination     |      |       |      |        |
|       | Partitions made of 12mm ply laminated. The rate to   |      |       |      |        |
|       | include all necessary hardware viz., telescopic      |      |       |      |        |
|       | drawer channels, handles, hinges, etc., and 20mm x   |      |       |      |        |
|       | 6mm beech wood /PVC edge banding etc.,               |      |       |      |        |
|       |  |      |       |      |        |
|       | One Side Table with shutters made with 25mm          |      |       |      |        |
|       | block board top and 18mm EG-MDF for all other        |      |       |      |        |
|       | members with necessary hardware viz., 'W' hinges,    |      |       |      |        |
|       | SS handles, locks, SS tower bolts, etc., and 20mm x  |      |       |      |        |
|       | 6mm beech wood /PVC edge banding etc and             |      |       |      |        |
|       | finished with 1.0mm laminate                         |      |       |      |        |
|       | All the unexposed faces to have 0.8mm Laminate.      |      |       |      |        |
|       |  |      |       |      |        |
|       | Ready Made Modular Foot Rest - 400mm x               |      |       |      |        |
|       | 350mm x 65mm.  |      |       |      |        |
|       | All wooden members to have minimum two coats of      |      |       |      |        |
|       | NO VOC or LOW VOC white duco paint finish.           |      |       |      |        |
|       |  |      |       |      |        |
|       | Each Single Window Counter to have half height       |      |       |      |        |
|       | partitions on either sides as per item 1.2 above.    |      |       |      |        |
|       | Each Single Window Counter to have provision for     |      |       |      |        |
|       | 12mm thick clear float glass in the front and sides  |      |       |      |        |
|       | as per relevant item measured separately.            |      |       |      |        |
|       |  |      |       |      |        |
|       | The cost to include the " L " shaped Single Window   |      |       |      |        |
|       | Counter and to include all materials, hardware,      |      |       |      |        |
|       | labour for a neat and finish job as per drawings and |      |       |      |        |
|       | directions etc., complete.                           |      |       |      |        |
|       |  | 2.00 | Each. |      |        |

| Sl.No | Description  | Qty  | Rate  | Unit | Amount |
|-------|--|------|-------|------|--------|
|       | 12MM TOUGHENED GLASS DIVIDERS FOR  |      |       |      |        |
| 21.00 | Providing, making and fixing in position 12mm thick toughened clear float glass dividers in the front side of half height partitions of Single Window Counters of approximate size 1650mm x 500mm - 100mm in tapered shape. All the edges of the glass to be polished for a smooth finish and the glass is to be fixed with "D" brackets from above skirting level. The cost to include all materials, labour, hardware etc., for a neat finished job as per drawings and directions etc., complete.   | 2.00 | Each. |      |        |
|       | 12MM TOUGHENED GLASS FOR <u>FRONT</u><br><u>PORTION</u> OF SINGLE WINDOW   |      |       |      |        |
| 22.00 | COUNTERS (TRANSACTION SIDE): Providing, making and fixing in position 12mm thick clear float glass in the front side and shall be in 2 nos of separate sizes. Lower part shall be fixed with a glass panel of size 1500-1650 x 380mm with a central cut out of 200mm x 150mm. Uppper part shall be fixed with a glass panel of size 1500-1650 x 450mm. A gap of 50mm shall be maintained between the two glass panels. All the edges of the glass to be polished for a smooth finish and the glass is to be fixed with "D" / "L" brackets as required. The cost to include all materials, labour, hardware etc., for a neat finished job as per drawings and diretions etc., complete. | 2.00 | Each. |      |        |
|       | 12MM TOUGHENED GLASS ON LOW HEIGHT PARTITIONS BETWEEN SINGLE WINDOW COUNTERS:  |      |       |      |        |
| 23.00 | Providing, making and fixing in position 12mm thick toughened clear float glass in sizes as per design with cut out of 200mm x 150mm at position to match Voucher tray. All the edges of the glass to be polished for a smooth finish and the glass is to be fixed with "D" brackets. The cost to include all materials, labour, hardware etc., for a neat finished job as per drawings and diretions etc., complete.  |      |       |      |        |
|       | Glass size shall be as per length of low height partiton after leaving about 300mm solid portion at both ends  |      |       |      |        |
|       | Item includes providing Voucher tray of size 200 x 200, made of 19mm BB-laminated with BW lipping /PVC edge banding etc and fixed onto the low partition with all hardware etc complete  | 2.50 | Sq.M. |      |        |
|       | WRITING DESK:  |      |       |      |        |
| 24.00 | WALL MOUNTED WRITING DESK:   |      |       |      |        |
| 24.00 | Providing, making and placing in position Wall Mounted Writing Desk 760mm x 300mm x 450mm with following specifications.  The entire unit is to be made with 18mm EG-MDF   |      |       |      |        |
|       | cladded with 1mm Laminate as per drawing.  The Writing Desk to have 12mm thick toughened clear float glass with 25mm chamfered bull nosing alround at top fixed with SS supports.  |      |       |      |        |
|       | All members to be with 18mm EG-MDF and all exposed faces to have 1mm Laminate as specified.  |      |       |      |        |
|       | All the edges of 12mm / 18mm EG-MDF to have 20mm x 6mm beech wood /PVC edge banding.   |      |       |      |        |

| Sl.No     | Description  | Qty  | Rate     | Unit | Amount |
|-----------|--|------|----------|------|--------|
| 51.110    | All the unexposed faces to have 0.8mm Laminate OR          | Qty  | IXatt    | Cint | Amount |
|           | and members of beech wood to have minimum two              |      |          |      |        |
|           | coats of NO VOC or LOW VOC white duco paint                |      |          |      |        |
|           | finish.  |      |          |      |        |
|           | The cost to include all materials, labour etc., for a      |      |          |      |        |
|           | finished item of work as per drawings and directions       | 1.00 | N. /F. 1 |      |        |
|           | etc., complete.  | 1.00 | Nos/Each |      |        |
|           | etc., complete.  |      |          |      |        |
|           |  |      |          |      |        |
|           | SALES TABLES:(SBI LIFE, DEBITE CARD)                       |      |          |      |        |
|           | Table: 1500 - 1650mm x 760mm x 760mm                       |      |          |      |        |
| 27.00     | Side Runner: 915 - 1050mm x 450mm x 760mm                  |      |          |      |        |
| 25.00     | Providing, making and placing in position Executive        |      |          |      |        |
|           | Table and Side Table with following specifications.        |      |          |      |        |
|           | Main Table and side Table top and to be made in 25mm       |      |          |      |        |
|           | block board with 1mm thick laminate on 8mm glass           |      |          |      |        |
|           | top to shape 1 1/2" hole cut for wire manager;             |      |          |      |        |
|           | cables etc. The front side of the table to have a inverted |      |          |      |        |
|           | " U " made with 2 x 18mm thick EG-MDF finished with        |      |          |      |        |
|           | 1.0mm laminate incuding the verticals towards the          |      |          |      |        |
|           | modesty panel. The modesty panel to have 18mm EG-          |      |          |      |        |
|           | MDF cladded with 1mm Laminate as specified.                |      |          |      |        |
|           |  |      |          |      |        |
|           | The "L" shaped table top on the back side along with       |      |          |      |        |
|           | side tabe to have 49mm edge alround, which is to be        |      |          |      |        |
|           | achieved by adding a 75mm piece of 18mm EG-MDF to          |      |          |      |        |
|           | the table top from bottom.                                 |      |          |      |        |
|           | All other members to be with 18mm EG-MDF and all           |      |          |      |        |
|           | exposed faces of the table to have 1.0mm laminate as       |      |          |      |        |
|           | specified.   |      |          |      |        |
|           | All the edges of 18mm EG-MDF to have 20mm x 6mm            |      |          |      |        |
|           | beech wood lipping /PVC edge banding.                      |      |          |      |        |
|           | govern wood appring/1 ve edge candang.                     |      |          |      |        |
|           | One readymade CPU mobile pedestal.                         |      |          |      |        |
|           | One Molded Key Board Tray with channels etc., One          |      |          |      |        |
|           | Three Drawer Unit made with 18mm EG-MDF and                |      |          |      |        |
|           | 12mm EG-MDF. The unit to have 3nos equal drawers.          |      |          |      |        |
|           | One Three Drawer Unit made with 18mm EG-MDF and            |      |          |      |        |
|           | 12mm EG-MDF. The unit to have 3 equal drawers. The         |      |          |      |        |
|           | rate to include all necessary hardware viz., telescopic    |      |          |      |        |
|           | drawer channels, handles, locks, etc., and 20mm x 6mm      |      |          |      |        |
|           | beech wood /PVC edge banding etc.                          |      |          |      |        |
|           | Side Table having one pedestal unit with 450mm wide        |      |          |      |        |
|           | having one drawer & one shutter with 1 no internal shelf   |      |          |      |        |
|           | made with 18mm EG-MDF and 19mm plywood with                |      |          |      |        |
|           | necessary hardware viz., 'W' hinges, handles, locks,       |      |          |      |        |
|           | tower bolts, etc., and 20mm x 6mm beech wood /PVC          |      |          |      |        |
|           | edge banding etc and finished with 1.0mm laminate.         |      |          |      |        |
|           | All the unexposed faces to have 0.8mm Laminate.            |      |          |      |        |
|           | Ready Made Modular Foot Rest - 400mm x 350mm x             |      |          |      |        |
|           | The cost to include all materials, labour etc., for a      |      |          |      |        |
|           | finished item of work as per drawings and directions etc.  | 0.00 | Each     |      |        |
|           | complete.  |      |          |      |        |
| <b>——</b> |  |      |          |      |        |

| Sl.No    | Description  | Qty   | Rate     | Unit | Amount |
|----------|--|-------|----------|------|--------|
|          | COMPLAINT BOX  |       |          |      |        |
| 26.00    | Providing, supplying & fixing of Complaint box fixed to the wall / partition of size 375mm x 270mm x 450mm made out of 19mm commercial block board for the box, external finished with 1mm th. laminate of approved shade and colour, prior confirmation shall be taken from the architect / bank and before making of box internal surfaces providing all internal surfaces to be finished with 0.8mm laminate of approved colour & design before making box including door shutter, necessary opening and all fixtures and fastenings, adhesives, nails screws etc., complete. | 1.00  | Nos/each |      |        |
| <u> </u> | OTHER WORKS:   |       |          |      |        |
|          |  |       |          |      |        |
|          | BLINDS<br>ROLLER BLINDS  |       |          |      |        |
| 27.00    | Providing and fixing in position of Roller Blinds of approved Fabric of Hunter Douglas / Mac / Vista Levalor make or approved equivalent of approved shade etc., as directed.  |       | Sq.M.    |      |        |
|          | DESIGNER FILM WORK   |       |          |      |        |
| 28.00    | Providing and fixing in position <b>Designer Film</b> on all glasses as per drawings and heights mentioned. The Designer Film is of <b>Harmony / 3M</b> or equivalent approved make. The rate is for a finished item of work etc., complete as directed.   | 10.00 | Sq.M.    |      |        |
| 29.00    | Supplying and fixing aluminium cladding with skin material 0.5mm thk aluminium sheet cover material natural polythylene aluminium cladding panel fixed with extruded aluminium basis frame (50x25x1.5mm) angle cleats, weather sealents, rivets, GI brackets all as approved, using suitable bolts on structural steel work including necessaryaccessories complete in all respects including all labour charges, scaffolding, tools and plants etc. complete.   | 9.40  | Sq.M     |      |        |
| 30.00    | Providing & Fixing Fire retardent door frame of size 130MM x 65MM with 60 minutes fire retardent rating door shall be 55mm thick single shutter, standerd manufactures specifications and finishing with laminate in approved colour door shall be fixed with handles, locks, hinges all hardwares complete etc.,The rate shall include fixing of frame to the masonry with 40mm x 6mm size flat iron hold fasts 450mm long embedded in 150mm thick cement concrete of mix 1:3:6 or as specified.  |       | Sq.M     |      |        |
| 31.00    | CLEARANCE OF DEBRIS  Clearance of Debris and all Waste materials generated during the execution of the work by Vendors of ALL TRADES, including loading, unloading, cariting away, transportation and disposal to suitable location as per site conditions etc complete  (Measurment shall be for Number of Loads of   | 2.00  | loads    |      |        |
|          | tempo / mini truck actually carried away and duly certified by Bank authorities / Security with GATE PASS.)  |       |          |      |        |
|          | TOTAL - INTERIOR WORKS   |       |          |      |        |
|          |  |       |          |      |        |