

BOQ

SECTION -II: INTERIOR FURNISHING AND FURNITURE WORKS					
4. FURNITURE & MISCELLANEOUS WORKS					
S N	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
	TABLE				
4.1	BRANCH MANAGER'S TABLE:- Size: 1800 mm X 830 mm X 750 mm Veneer finish				
	Supplying and installation of Table as per the following description : Table Top: Providing and fixing 18 mm thick IS 303 MR grade plywood with 4mm thick Teak veneer with high gloss PU Coating with necessary intermediate support. Table top shall be supported by 18 mm thick MR grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick toughened glass fixed at a vertical gap of 50mm using SS stud fasteners. The top level of the glass shall be 750mm. Apron (Modesty Panel) made from 18mm thick MR grade plywood finished with teak veneer with melamine Finish & 12 mm thick toughened glass fixed on SS studs & groove pattern as per drawing. Table sides, back & intermediate panels (at 50cm from each sides) made from 18 mm thick BWR ply wood finished with 4 thick teak veneer with melamine finish for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing.				
	Drawer / Storage cabinet: Box of 450 X 800 X 720 mm shall be provided using 18 mm thick MR grade ply wood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick ply wood & bottom of drawers shall be of 8 mm thick MR grade ply wood. The drawer unit box and individual drawers to be fixed with 4mm veneer finished with melamine polish on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer.				
	Computer Key board (550 x 375 mm) of metal / PVC of approved make shall be provided. Exposed surfaces of the drawer unit shall have Teak veneer with PU polish. Foot rest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balacing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and metallic cable Manager shall be provided in table top.				
	All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade	1.00	No.		
	As per drawing and instruction of Architect/Bank, work to be Completed				

SECTION -II: INTERIOR FURNISHING AND FURNITURE WORKS

4. FURNITURE & MISCELLANEOUS WORKS

S N	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
4.2	OFFICER'S TABLE:- Size: 1600 mm X 730 mm X 750 mm				
	Supplying and installation of Table as per the following description : Table top shall be made from 18 mm thick IS 303 MR grade plywood with 1mm thick with necessary intermediate support. Table top shall be supported by 18 mm thick BWR grade ply wood with wooden framing. The top of the table shall be provided with equal sized 12mm thick toughened glass fixed. Apron (Modesty Panel) made from 18 mm thick ply wood finished with 1mm laminate & groove pattern as per drawing. Table sides & intermediate panels (at 50cm from each sides) made from 18 mm thick ply wood finished with 1mm thick laminate for all surfaces shall be provided as per drawing.				
	Drawer / Storage cabinet of 400 X 630 X 720 mm shall be provided using 18 mm thick MR grade ply wood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick ply wood & bottom of drawers shall be of 8 mm thick MR grade ply wood. The drawer unit box and individual drawers to be fixed with 1mm laminate on exposed sides and all the internal surfaces shall be 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer.				
	Computer Key board (550 x 375 mm) of metal / PVC of approved make shall be provided. Foot rest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balacing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and metallic cable Manager shall be provided in table top.				
	All edges to be provided & fixed with teak wood lipping patti finished with melamine polish	10.00	No.		
	As per drawing and instruction of Architect/Bank, work to be Completed				
4.3	Flush Door with venner finish:- Providing & fixing 35 mm Flush doors with 4.0mm Veneer on both sides as per design. Door frame:- Providing and fixing door frames using teakwood members of size 100mm x 50mm and finished with melamine polish. Shutter:- Providing and fixing block board shutters of 35mm thick . Skin:- The shutters shall be finished with 4mm thick venner of approved quality and make and coated with Mat / glossy finish melamine polish. The Doors to have all hardware such as 125mm SS hinges, 450 m long SS handles, SS tower bolts, Mortice Locks (Dorma/ Godrej). Exposed edges of shutter shall be provided with teakwood beading of 30mm width and finished with melamine polish. The item also includes SS rods 6mm x 6mm inserted in grooves and finished properly using putty and polish as per details complete to the satisfaction of Architects/ Bank's Engineer. Size of Door : 1000 x2100mm including frames.	-	Sq.m		-

SECTION -II: INTERIOR FURNISHING AND FURNITURE WORKS

4. FURNITURE & MISCELLANEOUS WORKS

S N	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
4.4	Flush Door Partly glazed with Laminate finish:- Providing & fixing 35 mm Flush doors with 1.0mm laminate on both sides as per design. Door frame:- Providing and fixing door frames using teakwood members of size 100mm x 50mm and finished with melamine polish. Shutter:- Providing and fixing block board shutters of 35mm thick partly solid / opaque partly glazed with 900 mm high glass middle panles finished with laminate on both side Skin:- The shutters shall be finished with 1mm thick laminate of approved quality and make. The Doors to have all hardware such as 125mm SS hinges, 450 m long SS handles, SS tower bolts, Mortice Locks (Dorma/ Godrej). Exposed edges of shutter shall be provided with teakwood beading of 30mm width and finished with melamine polish. The item also includes SS rods 6mm x 6mm inserted in grooves and finished properly using putty and polish as per details complete to the satisfaction of Architects/ Bank's Engineer. Size of Door : 1000 x2100mm including frames.	23.00	Sq.m		
	Finished with 1mm thick laminate finish				
	Finished with 4mm thick Veneer with melamine polish				
4.5	STORAGE CUPBOARDS				
A	Low Height Cupboard with Laminate Finish: Providing & fixing Low Height Storage Cupboard of 750-1200 mm height and 450mm deep Outer exposed structure with to be made with 18mm MR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters and shelves to be made with 18 mm thk.MR ply. All internal and external surfaces to be finished with 1mm laminate of approved shade and make. All edges of the cupboard should be edgebanded using PVC edgebanding tape of approved shade. Shutters to be provided with S.S. 200mm handles, magnetic catchers, self closing SS hinges, locks (Godrej/ Hettich/Hafele), SS towerbolts etc. All shutters to to be made overlapping the frame Only front elevation will be considered for area calculation. Make: Approved make:-Brief list of make are as under or any equivalent make will be permitted by the Engineer/Architect	24.00	Sq.m		

SECTION -II: INTERIOR FURNISHING AND FURNITURE WORKS

4. FURNITURE & MISCELLANEOUS WORKS

S N	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
B	<p>Low Height Cupboard with Veneer Finish: Providing & fixing Low Height Storage Cupboard of 750-1200 mm height and 450mm deep</p> <p>Outer exposed structure with to be made with 18mm MR ply as per IS 303 and back side using 8mm MR grade ply. All shutter and shelves to be made with 18 mm thk.MR ply.</p> <p>All the external surfaces (i.e front side of shutters, top and sides of the cupboard), to be finished with 4mm thick VENEER to be finished with melamine polish.</p> <p>All internal surfaces to be provided with 1mm laminate.</p> <p>All edges of the cupboard should be edgebanded using PVC edgebanding tape of approved shade.</p> <p>Shutters to be provided with S.S. 200mm handles, magnetic catchers, self closing SS hinges, locks (Godrej/Hettich/Haffele), SS towerbolts etc. All shutters to to be made overlapping the frame</p> <p>Only front elevation will be considered for area calculation.</p> <p>Make: Approved make:-Brief list of make are as under or any equivalent make will be permitted by the Engineer/Architect</p>	5.00	Sq.m		
4.6	Pantry Storage (Shutters under Platform)				
	<p>Providing and fixing Storage Shutter fixed on wooden frame under Platform. Shutters to be made of 18mm thk. FIRESAFE IS: 5509 plywood sheet finish with 1mm thick laminate sheet on outer face and 0.8 mm thick white balancing laminate on inner face of the shutter; edge to be covered with aluminum profile section as per selection, shutters to have brass hinges and magnetic catchers with teak wood frame below platform. Inner shelves to made of 18mm thick BWR ply with 1mm laminate on top and exposed edge and painted on other sides etc. complete to as per direction of Architect / Bank's Engineer. The inner depth of shelves shall be 450/600 mm.</p> <p>(Measurement will be counted from front shutter's height & width, no extra measurement and payment will be given for ss basket & shelves).</p> <p>(Base price of laminate to be used to be Rs. 45/- sq.ft.).</p>	2.00	Sq.m		
4.7	SOFT BOARD				
	<p>Providing & fixing soft board for pin up using moulded Steam beach / Teak Wood frame of 25 x12.5 MM with 6 mm thick BWR grade plywood on back side and 12mm th soft board on front covered with cloth of selected design of Basic rate of Rs.110 per Rmt. Steam beach member shall have lacquer polish as directed.</p>	4.00	Sq.m		
4.8	<p>Supplying and fixing Roller Blinds of approved make with selected fabric of approved design and shade having powder quoted rod and adjustable string, etc. complete .</p> <p>(Basic Price of Rs 80 Per Sq.Mtr excluding GST)</p> <p>Approved make:-Brief list of make are as under or any equivalent make will be permitted by the Engineer/Architect</p>	82.00	Sq.m		

SECTION -II: INTERIOR FURNISHING AND FURNITURE WORKS

4. FURNITURE & MISCELLANEOUS WORKS

S N	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
4.9	Supplying and installation of 920 x540x 450 mm height Centre Table Veneer finish & Top in Glass finish				
	Providing & fixing Center Table made out of in 19 mm thk. MR Grade IS 303 plywood frame work for table tops, sides and finish with 4 mm thk approved make Veneer with PU Polish finish. Table top finish in 12 mm thk Glass/ solid surface of approved make. As per detailed drawing given by Architect / instructions given by Architect on site etc. complete.	2.00	No		
	Approved make:- -Brief list of make are as under or any equivalent make will be permitted by the Engineer/Architect				
4.10	Grahak Mitra counter Veneer				
	Providing and supplying Grahak Mitra counter of size 1800mmx 600mm in curvature and 750mm height:- Top: chamfer edged 18mm thk MR IS:303 plywood for top on stainless steel studs of 90mm height. Table sides and back:- Providing & fixing table below the glass to be made out of 18mm thk IS:303 grade MR Plywood with front apron to have 18mm thk IS:303 grade MR Plywood with side and intermediate supports @ max. 600mm or as directed by Engineer in charge / as per Architectural drawings. Finish:- The top in 6mm thk veneer & exposed sides of the table shall be provided with approved 4mm thk Veneer with PU Polish including necessary surface preparation, finishing the same etc complete.	1.00	No		
	Drawer / Storage cabinet of 350 X 630 X 720 mm shall be provided using 18 mm thick MR grade ply wood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick ply wood & bottom of drawers shall be of 8 mm thick MR grade ply wood. The drawer unit box and individual drawers to be fixed with 4mm Veneer with PU Polish on exposed sides and all the internal surfaces shall be 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer. The table shall be provided with readymade keyboard tray (ebco or equivalent) and CPU trolley and top to be provided with wire-managers.				
	Approved make:- Approved make:-Brief list of make are as under or any equivalent make will be permitted by the Engineer/Architect				

SECTION -II: INTERIOR FURNISHING AND FURNITURE WORKS

4. FURNITURE & MISCELLANEOUS WORKS

S N	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
4.11	ACP CLADDING: Supplying and fixing aluminium composite cladding with skin material 0.5 mm thick aluminium sheet cover material natural polyethylene aluminium cladding panel fixed with extruded aluminium basis frame (50x25x1.5mm) angle cleats, weather sealants, rivets, GI brackets all as approved, using suitable bolts on structural steel work including necessary accessories complete in all respects including all labour, scaffolding charges etc., complete for finished item of work. ACP Cladding - 4 mm thick.	39.00	Sq.m		
4.12	TRAP DOOR FOR ROLLING SHUTTERS WITH ACP CLADDING: Framework: Using 50x25x1.2mm aluminium section placed at walls vertically and horizontally and as supports above the mechanical unit of shutter and on sides as directed by the Engineer in charge. Finishing:- The exterior sides, top and shutters shall be fixed and finished with approved aluminium composite panel cladding with 3 mm / 4mm thick ACP sheets fixed over the frame work. Joints of the ACP shall be properly concealed with black / white coloured silicon waterproof sealant. Rate shall be inclusive of necessary fittings like SS hinges of approved make, SS tower bolts, ball catchers etc. Measurement for exterior sides having ACP cladding shall only be taken for billing.	7.00	Sq.m		
4.13	ELECTRICAL STORAGE Providing and fixing 120x30x60(h) cm Cabinet for electrical panel board area:- The shutters (openable and partly louvered) made out of 12mm thick block board shutters with 1mm laminate finish on exposed sides. The inner sides of the storage to be of 12mm. thk MR grade ply with 6mm. thk bision board finished with paint on all internal surfaces. Colour polish to external edges brass hinges, 6" SS handles etc. as per the details. The shutters should be provided with Powder coated louvers having minimum height of 150mm each (50% of total area of shutter) on top and bottom for ventilation. The electric panel shall be fixed over 19mm MR grade ply. Measurement will be taken for a single unit of specified size.	10.00	Sq.m		
4.14	MEETING ROOM TABLE VENEER FINISH Providing & Fixing Conference Table made out of 75mm X 65mm T. W. Wood frame work 450mm center to center bothways for table top covered with 12mm thick BWR ply for bottom, 19mm thick BWR ply for top, table stand and base with necessary 50mm X 40mm vertical supports. Table top to be provided with 4mm thick venner finished with PU polish. All other exposed surfaces shall be finish with appd color 4 mm thk. Veneer with melamine polish. All internal surfaces to be finished with 0.8mm thick laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be inclusive of Brush Finish Stainless Steel Tray with POP UP Flap for electrical switches including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound,claening the site etc. complete as per the detail drawing and instruction of Engineer.	-	Sq.m		-

SECTION -II: INTERIOR FURNISHING AND FURNITURE WORKS**4. FURNITURE & MISCELLANEOUS WORKS**

S N	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
4.15	DISCUSSION ROOM TABLE LAMINATE FINISH				
	Providing & Fixing Table made out of 19mm thick BWR ply for table stand and base with necessary 50mm X 40mm vertical supports. Table top in 12mm thk chamfer edged glass. All exposed surfaces shall be finish with appd color 1 mm thk. laminate. All internal surfaces to be finished with 0.8mm thick laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound,claening the site etc. complete as per the detail drawing and instruction of Engineer.	3.00	Sq.m		
4.16	LUNCH ROOM TABLE LAMINATE FINISH				
	Providing & Fixing Table made out of 19mm thick BWR ply for top, table stand and base with necessary 50mm X 40mm vertical supports. All exposed surfaces shall be finish with appd color 1 mm thk. laminate. All internal surfaces to be finished with 0.8mm thick laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound,claening the site etc. complete as per the detail drawing and instruction of Engineer.	3.00	Sq.m		
4.17	PLASTIC EMULSION PAINT				
	Providing & Applying 3 coats of plastic emulsion paint of approved make and approved shade to walls including cleaning and preparing the surfaces with 2 coats of primer along with applying birla putty to the surfaces including scaffolding,cleaning the floors, fittings, furniture's, handles, ladders, glasses, removing of debris out of compound, cleaning the site etc. complete as per the detail drawing and instruction of Engineer.	47.00	Sq.m		
		TOTAL			