

Interior Furnishing Works for SBI SCAB at SBI Main Branch Dehradun, Uttarakhand Price Bid

S.No.	Description	Quantity	Unit	Rate	Amount (in Rs.)
1	CHIEF MANAGER TABLE				
	<p>Table but size 5'-6" x 2'-6" x 2'-6" Table as per the following description and as design/ details,</p> <p>Table Top: Providing and fixing 18 mm thick IS 303 BWP grade plywood with 1mm thick laminate with necessary intermediate support. Table top shall be supported by 18 mm thick BWP grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick bevelled toughened glass with polished edges. The top level of the glass shall be 750mm.</p> <p>Apron (Modesty Panel) made from 18mm thick BWP grade plywood finished with veneer. Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick MR ply wood finished with veneer for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing.</p>	1.00	NO.		
	<p>Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWP grade plywood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick plywood & bottom of drawers shall be of 8 mm thick BWP grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer. The front ply of the drawers to be overlapping the frame.</p>				
	<p>Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop. All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade. As per drawing and instruction of Architect/Bank, work to be completed.</p>				

Interior Furnishing Works for SBI SCAB , Dehradun

2	SIDE CREDENZA for CM same as above Item (Size 3'-6" x 1'-6" x 2'-6")	1.00	NO.		
	<p>Providing & fixing Side Credenza Outer exposed structure with to be made with 19mm BWP ply as per IS 303 and back side using 8mm BWP grade ply. All shutters to be made from 25 mm thk BWP Ply and shelves to be made with 19 mm thk. BWP ply.</p> <p>The top portion of the side and rear credenza to be finished with 1mm thk. laminate of approved shade and All edges to be provide with 2mm Edge binding tape. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/ Haffele), SS towerbolts etc. All shutters to be made overlapping the frame. As per drawing and instruction of Architect/ Bank, work to be Completed.</p> <p>Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank</p>				
3	HVCC Officer & Cash Box Area Officer TABLE				
	<p>Table but size 6'-6" x 3'-0" x 2'-6" Table as per the following description and as design/ details,</p> <p>Table Top: Providing and fixing 18 mm thick IS 303 BWP grade plywood with 1mm thick laminate with necessary intermediate support. Table top shall be supported by 18 mm thick BWP grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick bevelled toughened glass with polished edges. The top level of the glass shall be 750mm.</p> <p>Apron (Modesty Panel) made from 18mm thick BWP grade plywood finished with veneer. Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick MR ply wood finished with veneer for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing.</p>	2.00	NO.		
	<p>Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWP grade plywood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick plywood & bottom of drawers shall be of 8 mm thick BWP grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer. The front ply of the drawers to be overlapping the frame.</p>				
	<p>Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop. All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade. As per drawing and instruction of Architect/Bank, work to be completed.</p>				

4	SIDE CREDENZA for HVCC Officer & Cash Box Area Officer same as above Item (Size 3'-0" x 1'-6" x 2'-6")	2.00	NO.		
	Providing & fixing Side Credenza Outer exposed structure with to be made with 19mm BWP ply as per IS 303 and back side using 8mm BWP grade ply. All shutters to be made from 25 mm thk BWP Ply and shelves to be made with 19 mm thk. BWP ply. The top portion of the side and rear credenza to be finished with 1mm thk. laminate of approved shade and All edges to be provide with 2mm Edge binding tape. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/ Haffele), SS towerbolts etc. All shutters to be made overlapping the frame. As per drawing and instruction of Architect/ Bank, work to be Completed. Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank				
5	Providing and fixing 12 mm thick Toughened Glass partition on counter Top front side top as follows.	9.00	Sq.Mt.		
	Providing and fixing 12 mm thick Toughened float glass with polished edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. Two cutouts to be made one half round of 150mm dia and another for mouth piece rectangular size of 75mm wide 450mm long. All edges of glass shall have Diamond cut polished edges as directed. Brief list of make are as under or any equivalent make will be permitted by the Engineer. Glass- Asaahi/ Tata / Modi guard / Saint gobain Square bracket (50 mm x 12.5 mm) S S finish - Oswal / Riddhi / Swift or equivalent.				
6	OFFICER AND STAFF TABLE				
	Same as above for CM Table , item SI No 1 but Size: 5'-0" x 2'-6". (Without Top Glass)	12.00	NO.		
7	SIDE CREDENZA for Officer & Staff same as item SI No 2 above for C.M Side Credenza except (Size 3'-0" x 1'-6" x 2'-6") but, all external surfaces including top to be finished with 1.0mm thick Laminate of approved shades.	12.00	NO.		

8	STORAGE CABINATE				
	Supplying and providing storage cabinate same as above but with 1mm laminate on all exposed surfaces like Top, Front Shutter, sides, back if exposed and 0.8 MM laminate from inside, storage to have 2mm thick edge binding tape of same colour as laminate on Edges .	2.00	Sq.Mt.		
	Size : Depth 1'-6" and height as per dwg. having openable shutter as directed. Storage Cabinet shall be made from 19mm thick BWP Ply, for Top with laminate finish and 19mm thick BWP Ply for verticle, shelves, shutters and 8mm thick BWP PLY for backing with 0.8 mm thick laminate on all internal surface. with verticle (at 3'-0" c/c) shelves at 1'-3" c/c Openable shutters in 19 mm thick BWP Ply with all auto hinges, towers bolts, powder coated handle, ball catches, SS approved make multi purpose lock complete, Edges to have 2mm thick edge binding tape of same colour as laminate.				
	Only front surface area shall be measured for payment purpose.				
9	ELECTRIC CUPBOARD	3.00	Sq.Mt.		
	Providing and fixing Electric cup board using 19 mm thick bison board for frame sides verticle and shelves and front shutters with aluminium framing of 50x25x1.5mm thick with 6mm thick bison panel on both side finished with 1.0 mm thick laminate on all exposed surface and fire proof paint & synthetic enamel paint on all internal surface. Shutter with approved make lock handle, hinges, ball catchers, SS Perforated jali shall be provided in shutter for ventilation, complete as directed, depth of cup board 1'-3". Shutter height as required and above area fixed Type with same Aluminum frame and bison board laminate finish up to false ceiling bottom.				
8	P/F LOW HEIGHT WOODEN PARTITION WITH BOTH SIDE LA	19.00	Sq.Mt.		
	Providing & fixing in position Low height wooden partitions with 450mm high glass panel finished with laminate on both sides comprising as under:				
	Total Height of the partitions shall be from 1200 mm including 300 mm high 12 mm clear glass panel as per approved drawing.				
	Framing : Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium sections placed bothways (horizontal and vertical) not exceeding 450 mm c/c rigidly fixed to floor, wall / columns etc including extending end/intermediate vertical members not exceeding 1500 mm c/c for total finished height of LHP.				
	Skin : Providing & fixing 8 mm thick plywood on both sides of the framework and all-round vertical posts extending up to total height of LHP.				
	Finishing :- Providing and fixing 1.00 mm thick approved quality and shade laminates using approve quality adhesive, over ply as per approved design & pattern including providing grooves as per Architectural drawing and as directed by the Engineer-in-charge.				
	Glazing :- Providing and fixing 12 mm thick approved make clear float glass panels (not exceeding 1.50 m in length) with polished edges on all sides, fixed using suitable CP Brass /SS 'D' brackets placed not exceeding 450mm c/c on horizontal surface of partition and at both ends on vertical posts to rigidly hold the glass panels.				

Interior Furnishing Works for SBI SCAB , Dehradun

	Providing finished section size 70/75 x 8mm thick seasoned second class Teak wood moulding to all exposed edges of partition including applying 2 or more coats of melamine polish / Duco paint including necessary preparatory work for surface preparation with putty, priming coat, sealer coat etc. complete as per sample approved by the Bank.				
	Making necessary cutouts for electrical conduits / cables & switchboard etc., including providing additional supports wherever required complete as per drawings and as directed by Engineer.				
	The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
9	P/F FULL HEIGHT SOLID WOODEN PARTITION WITH BOTH SIDE LAMINATE	115.00	Sq.Mt.		
	Providing & fixing in position full height solid/ opaque wooden partitions finished with laminate on both sides comprising as under:-				
	Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm (may slightly vary as per unavoidable site conditions) both ways (horizontal and vertical) fixed rigidly on floor, wall / column & ceiling.				
	Plywood skin:- Providing & fixing 8 mm thick plywood on both sides of the framework.				
	Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design & pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approve quality adhesive complete.				
	Making suitable cutouts/ openings/ channels for Doors, electrical conduits, cables & switch boards, AC ducts etc including providing necessary wooden supports wherever required and directed at site.				
	Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.				
	Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.				
	The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
	Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.				

10	Providing and fixing Isolated flush door shutter (Partly Glazed & Partly Laminate) with frame as follows.				
	Providing and fixing 4"x2" Teak wood member for frame and Flush door shutter made out of 35 mm thick flush door with 8 mm thick clear toughened glass vision panel secured with 12 mm thick TW beading, 31x12 mm thick TW periphery patti around shutter edges, 1 mm thick laminate on both sides, 35x12mm thick steam beach stopper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Approved make Dead Lock, S.S Handles, 150 mm long Door stoppers, doorstop of approved make etc. all exposed surface /edges not laminated be provided with Melamine polish complete as per drawing & instructions.	24.00	Sq.Mt.		
11	Laminated Flush Door for Washroom & Kitchen with TW frame.				
	Providing and fixing waterproof wooden flush doors with 4"x2" Teak wood frame as above & Shutter with 35mm thickness finished with 1mm laminate on both sides, edges of door to have teak wood edging all around & including all fitting & fixtures like Door handle & bolt lock, Al. Tower bolts, door closer door stopper as per specification, including polish and finishing as per drawing and instructions of engineer in charge.	13.00	Sq.Mt.		
12	FULL HEIGHT FULLY GLAZED PARTITION WITH 12MM TOUGHENED GLASS UPTO 7' LEVEL WITH SOLID PARTITION ABOVE 7' LEVEL	8.00	Sq.Mt.		
	Providing & fixing full height glazed partition with 12mm Toughened glass of approved make up to 7' level height with solid partition above 7'-0" level up to false ceiling bottom.				
	The glazed panels shall be fixed to the existing floor and false ceiling with all necessary SS brackets (D, C or U type) Vertical joints between the glass panels shall be sealed with suitable transparent sealant.				
	The solid partition above 7'-0" level shall be made with aluminium framework of size 63mm X 38.10mm X 1.47 mm (0.780Kg /mtr) box section. The spacing of the Horizontal and Vertical members are approximately 600mm c/c (maximum) and the top of the frame shall be fixed to the RCC slab bottom. The exposed surfaces on both sides of framework are covered with 6mm BWP ply finished with 1.0mm thick laminate as per direction.				
	Providing, placing in position & erecting full height partition in desired shape, framework shall be of 50 x 50 x 1.5 mm thick aluminum square section placed at 500 mm c/c both ways or as directed.				
	Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.				

13	FULLY GLAZED DOOR				
	Providing and fixing position 12 mm fully glazed toughened glass door, single/ double shutter, of approx. size 900/ 1500 x 2100/ 2400 mm	6.00	Sq.Mt.		
	Providing and fixing in position frameless glass door shutter made using 12mm thick toughened glass fixed to the partition (glazed/ solid/ gypsum partitions) using heavy duty floor spring with pivot of approved make including necessary cutting of floor and making the surface good to its original position including all necessary Patch fittings of approved make and fixtures & hardware.				
	Approved make: DORMA Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Handle - TG DIH600 - 600mm length) or equivalent brand fittings from Hettich / Hafele / as per sample approved by the Bank. Rate should also include providing film as per design/ instructions of Bank.				
14	POLYESTER FILM OVER GLAZED PARTITIONS				
	Providing and fixing in position high impact resistant Polyester Films of approved design & pattern, which once installed on glass, give additional strength to glass, reduce glare & prevent glass from splintering on impact. thickness not less than 4 Mil (100 mic.) or 7 Mil (175 mic.)	8.00	Sq.Mt.		
15	CUSTOMER WRITING DESK				
	Writing Desk Size 3'-0" x 1'-3" x 0'-6"+3'-0" ht.	1.00	NO.		
	Verticle Sides and bottom shall be made out of 36mm (2X18mm thick BWP Board) and back side 12mm thick BWP Board with Laminate on Top and Edges on all sides including inside divisions. Top shall be made from 12mm thick Toughend glass with polished edges making different divisions by 18mm thick BWP Board with laminate on both side for slips or forms as per detail drawing and instruction complete. (Drawing as enclosed herewith) Laminate to be provided on all visible surface.				
16	NOTICE BOARD				
	Size of Notice board shall be 1200x600 & 150 mm deep.	1.00	NO.		
	Providing and fixing Notice Board with 18mm BWP board frame & sides finished with 1.0 mm thk Decorative texture laminate, Box to have 75 x 35mm teak wood shutters with 6mm clear glass. The back to have 5-6 mm thick BWP board and 12mm soft Ply covered with cloth of approved shade. The item shall include polishing the wood surfaces etc. complete to the satisfaction of Architect/ Bank's Engineer.				
17	PELMET				
	Providing and fixing pelmet made of 18-19 mm thick BWP board, up to 300 mm high and in line with external glazing as per details of Architect. Rate to include finishing exposed surfaces of the Pelmet with 1mm laminate. Edge of Board covered with Edge binding tape.	19.00	R.Mt.		

18	ROLLER BLINDS				
	Providing, fabricating and fixing vertical roller blinds of approved make preferably of "Vista Levelor" with a woven made acrylic coated fabric of 100% polyester of thickness 0.50 – 0.60 mm (+/- 5% tolerance) with the main properties like resistance to Cracking & Fraying, dust repellence, UV proof and virtually maintenance free along with the Vista accessories of like Head rail, Roller tube Idler, Bottom rail, chain, matching colour installation brackets etc. including all fixtures and fittings of Vista like Rainbow curtain rods with electric resistance welded MS pipe having a corrugated virgin PVC extrusions reinforced to minimize friction, finials and along with standard anchoring arrangements etc. all complete done in workmanlike	0.00	Sq.Mt.		
19	P/F GYPSUM BOARD FALSE CEILING				
	Providing and fixing false ceiling at all height including providing and fixing of frame work made galvanized M.S. sections as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/ partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval	192.00	Sq.Mt.		
	Fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound, jointing tapes, finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of Engineer in charge including cost of painting the false ceiling with two coats of acrylic emulsion paint over a coat of putty				
	12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095-(Part I) :2011 (Board with BIS certification marks) to be used.				
20	MINERAL FIBRE GRID TILE CEILING:				

Interior Furnishing Works for SBI SCAB , Dehradun

	Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200 x 600 mm and secondary cross "T" of length 600 mm and size 24 x 25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200 x 600 mm panel to form grids of 600x600 mm and wall angle of size 24 x 24 x 0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc.	93.00	Sq.Mt.		
	Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge.				
	NOTE :-				
	For False ceiling Items the false ceiling design can be curved/architectural design, steps, cove etc. However only Board surface area shall be measured for the purpose of payment. Nothing extra for design or curve or steps upto 150-200 MM except cove measured in R.MT and paid in item				
	Existing floor to slab height on the site shall vary. Ceiling shall be hung from the existing slab through hanger's. Rate quoted in the tender shall be applicable for all floor levels /all floor height (approx. 4-4.5 Mtr floor to floor) including scaffolding, etc complete.				
	The rate of falseceiling items also includes 6 mm ply backing for supporting light fixtures in the false ceiling.				
	The rate of False ceiling items also includes making all necessary cut outs & frame work for electrical fixtures / air conditioning work coves etc.				
21	PAINTING				
	Providing and painting Synthetic Enamel Paint after removing old paint & preparing the base for the same and applying 2 or more coats of paint complete. complete to the satisfaction of Architect/ Bank's Engineer.	30.00	Sq.Mt.		
22	Providing & painting the walls, ceiling with Plastic Emulsion paint after preparing the base by removing existing paint/ finish and applying 2-3 coats of birla white putty for making the surface plane & smooth & applying 2 or more coats of plastic emulsion paint with final coat done with rollers etc complete. Complete to the satisfaction of Architect/ Bank's Engineer.	650.00	Sq.Mt.		
23	Providing & applying approx. 12mm thick POP punning on wall to give a clean smooth and plumb surface.	20.00	Sq.Mt.		

Interior Furnishing Works for SBI SCAB , Dehradun

24	Providing & applying texture paint (Base price 90-1005 per S.FT) in two or more shades with roller & spray, after preparing the base for the same (Okios, Acro or Equivalent) .	10.00	Sq.Mt.		
	Total				