NO	ITENA		ANCH	LINUT	RATE	AMOUNT
.NO.	ITEM	PARTICULARS	QTY.	UNIT	KAIL	AMOUNT
I	LOW HEIGHT SINGLE	Providing and fixing low height Single Window counters / Case Manager's table with a maximum width of 3'0" in required	7.5	RMTR.		
	WINDOW	shape as per typical de-sign. The main structure of the counter				
	COUNTER	is to be made of 19mm thick BWP Phenol Formaldehyde block				
		board of Green/Century / Mayur or equivalent/ Exterior Grade				
		MDF board of Green/Century or equivalent with a teak wood				
		beading of 50 mm x 38 mm in front and necessary beading to				
		cover all the ex-posed edges of board etc. The width of the				
		counter should have 5'0" (with disc credenza / cabinet of 1'4"				
		wide and maximum 3'6" length / depth (in-cluding width of				
		counter). The vertical supporting members of counter are to be				
		made of 19 mm thick BPW Phenol Formaldehyde block board				
		of Green/Century / equivalent or Exterior Grade MDF board of				
		Green/Century or equivalent don-8 box shall be provided by				
		the bank would be fitted properly in right hand side. The key				
		board pullout tray of to be provided in addition to key board				
		drawer with lock and key make arrangement of standard make				
		to be decided by the Bank. The left hand side should have				
		cabinet made of 19 mm thick BWP, PF plywood and cavity				
		keeping CPU as per design / drawing. The counter top have a				
		neat hole to be made in the table for connecting the wires				
		which is to be covered with a dark colored PVC insert (wire				
		manager) with moveable parts to put the wires and sockets to				
		cover the hole neatly. The exposed block – board/ plywood to				
		be covered with 1.0 mm thick blue / white high gloss laminate				
		of Greenlam / Marino / Century or equivalent of approved				
		shade and colour. Exposed portions to be also covered with 1.0				
		mm thick blue / white high gloss laminate of approved shade				
		and colour. The internal and non-visible side of all drawers,				
		cabinets and coun-ter table shall be painted with 3 coats of enamel paint over one coat of primer on the internal side.				
		Glass portion made of 12 mm thick toughen glass of approved				
		make as per design and specification securely fixed in toughen				
		section as per design and details and all necessary standard				
		quality of fit-tings, hard wares, locks (make or equivalent). Door				
		Ishutter of 19 mm BWP board to be fixed at the rear side of				
		counter with automatic locking system from Godrej or				
		equivalent.				
2	HVDDAIIII	Describing and facing halfs to the Parties of Table 1		NO		
2	HYDRAULIC	Providing and fixing hydraulic Hardwyn, Everite or approved	6	NO.		
	DOOR CLOSER	make equivalent door closures of Hardwyn, Everite or				
	GLOSEK	equivalent approved brand and sample – all complete as per				
		instructions of the Bank. All complete work as per drawing,				
		design. Specification and direction of Engineer-in-charge /Bank.				
		// Dailin.				
		1		1		

	_			
3		Providing and fixing double skin partly paneled & partly glazed/ solid full height partition with frames of 50 mm x 38 mm (finished size) seasoned hardwood members (Gamhar, Malaysian Sal wood / hollock) at maximum intervals of 450 mm x 450 mm with provision of bigger members at skirting, fixing to false ceiling (if provided) fixing to RCC Slab, Beams etc. all wood work to be treated with 1st quality anti-termite paint and covered with 6 mm thick BWP grade plywood/ Exterior Grade MDF board of Green/Century or equivalent and 1.0 mm thick (Greenlam / century or equivalent) blue / white high gloss laminate with grooves / small / panels cut and pasted in the same as per typical design, on both sides so as to form able skin partition to level 900 mm and with 5.50 mm clear float toughen glass of approved make as above at item-1 of Modi float or equivalent above, etched / etching film pasted as per design fixed in wooden frame and with teak wood beading as per detail design, which is to be of 1st quality teakwood (all visible wood to be of 1st quality teakwood) and shall be polished and protected with melamine polish. The wooden frame of the partition shall continue right up to the ceiling as shall be firmly fixed to the ceiling and ground by means of Rawal Plugs etc necessary fas-teners so as to form a stable system / partition all complete work with provision for wring to be done by other agencies all complete work as per specification	SQ. MTR.	
4	LOW HEIGHT PARTITION	Providing and fixing low / half height partitions up to 4' 0" with double skin paneling up to 3'-0" and 12 mm thick toughened glass of approved make above frameless on the top and sides and sturdily fixed at the bottom on a polished teakwood frame all complete job with all other specifications and details to be as per item No. 3 above and as per the design i.e. shown in sides of low-height counters all complete work.	SQ. MTR.	
5	12 MM THICK TOUGHENED GLASS PARTTITION	Providing and fixing / fitting 12 mm thick toughened glass fixed partition of approved make with all necessary hard-ware accessories, patch fittining etc including cost of labours and materials etc .	SQM	
6	TOUGHENED	Providing and fixing / fitting mm thick toughened glass of approved make with all necessary hard-ware accessories etc including cost of labours and materials etc .	SQ. MTR.	
-				

7	WOODEN	Providing and fixing glazed door, all complete as per	7.15	SQ. MTR.	I	
	GLAZED	specifications given in item No. 3 above. Doors shall have			I	
	DOOR FOR	separate hard wood chowkhats of 100 mm x 60 mm of Sal			I	
	CHAME-BRS	wood and frames of Gamhar wood which shall be of 150 mm x			I	
		wood and frames of Gamiliai wood which shall be of 150 min x			I	
	ROOMS LIC.	40 mm at the top and sides and 200 mm \times 40 mm at the			I	
		bottom. Beading shall be given as per typical design and			I	
		specifications. Door panel shall be of 8 mm thick clear float			I	
		toughen glass of Modi float or AIS make or equivalent			I	
		approved by the bank. All necessary hardware such as brass			I	
					I	
		hinges (4 nos. heavy qualities for each door), door locks, brass			I	
		tower bolts and any other hardware required for the door shall			I	
		be in the rate. Gamhar frame shall be neatly covered with 4.0			I	
		mm BWP ply and 1.0 mm high gloss laminate as has been			I	
		mentioned in item - 3 above of approved brand as has been			I	
		mentioned at item no.1 above and as per design. All visible			I	
		wooden surfaces shall be covered with high glosive laminate.			I	
		All work to be completed as per Corporate Centre, Mumbai			I	
		· · · · · · · · · · · · · · · · · · ·			I	
		approved mate-rials Colour & laminate etc and specifications			Ì	
	D TE:	and direction of Engineer-in-charge /Bank.	-	NO		
8	D-TEL	Providing D-Tel depository cabinet of Godrej make in counters	5	NO.	I	
		of size-691mm x 460mm x 460mm of weight 33.00 kg of			I	
		automatic locking including of cost of labors & materials etc. to			Ì	
	<u> </u>	complete job as per specification & direction of E/I.		<u> </u>	<u> </u>	
9	WORK	(a). Making and erecting Desk-top with provision of wore				
	STATIONS /	manager having two sides vertical support panels and modesty			l	
	TABLES	panel. All made of 19 mm thick BWP grade block board of			I	
		Green / Century /Mayur or equivalent/ Exterior Grade MDF			I	
		· · · · · · · · · · · · · · · · · · ·			I	
		board of Green/Century or equivalent top laminated with 1.0			I	
		mm blue / white high gloss laminate of Green/ Marino / Century			I	
		or equivalent. All edges shall be covered with teak wood			I	
		lapping and front-edge shall be covered with half round			I	
		molding. Inner portion of table shall be painted with matt finish			I	
		3 coat of synthetic enamel paint with primer. All wooden			I	
					I	
		surfaces shall be well polished with melamine/sprit polish.			I	
					I	
		(b) Making & providing drawer chest with two drawers and one			I	
		cupboard with concealed hinges and Godrej multipurpose			I	
		locks. Box made of 19 mm thick and bottom with 6 mm BWP			I	
		grade ply of Green/ Century or equivalent / Exterior Grade			I	
		MDF board of Green/Century or equivalent front shall be			I	
		l · · · · · · · · · · · · · · · · · · ·			I	
		cladded with 1.0 mm thick high gloss blue /white laminate of			Ì	
		Green lam / Century or equivalent side edges of drawers and			I	
		cupboard shall molded in round shape with Gamhar wood. All			I	
		drawers shall have 'Z' shape powder coated MS runners with			Ì	
		PVC sound less rollers. All work to be completed as per			Ì	
		approved ma-terials Colour Laminate and specifications .			I	
		''			I	
					I	
		(c). Providing and fixing key board tray (as per design and			Ì	
					Ì	
		specification at 1- above) try and made of PVC / Laminated			I	
		board on 'Z' shape powder coated runner with PVC soundless			I	
		rollers.	.=		 	
	I	'L' shaped 2400 mm x 900 mm x 750 mm (For R.M.)	0	NO.	<u> </u>	
	II	4800 mm x 900 mm x 750 mm (For Meeting Hall)	0	NO.	 _	
	III	L' shaped 1800 mm x 900 mm x 750 mm(For C.M)	1	NO.	<u> </u>	
	IV	'L' shaped 1500 mm x 1650 mm x 750 mm	2	NO.		
		,				
	V	'L' shaped 1500 mm x 1500 mm x 750 mm	0	NO.	l	
		All complete work as per drawing, design. Speci-fication and			I	
		direction of Engineer-in-charge /Bank.			<u> </u>	
			_			
				ļ		l i

10	FOOT REST	Providing and placing foot rest made of 19 mm BWP grade block board with wooden lippings top cladded with rubber mat. All inner portions shall have a coat of mat finish enamel paint all complete work as per drawing, design. Specification and direction of Engineer-in-charge /Bank. Materials shall be above at item	8	NO.	
11	CORIAN LAMINATE	Supplying & fixing/fitting of corian laminate of 6mm thickness of approved make of Du-Point/Mairino on table top, table front, & designer beads SBI fa-cia, back black color & rounding of edges to complete in all respect, as per site condition with rounding of edges etc to complete job. (C.M's table table tops).		SQ. MTR.	
12	LOW TYPE STORAGE CABINET	Making and fixing low type storage cabinet with drawer and cupboard with shelf as per the drawing / design all made of 19 mm thick BWP block board of Green/Century /Mayur or equivalent/ Exterior Grade MDF board of Green/Century or equivalent top and front laminated with 1.0 mm thick blue / white high glosive laminate of Green/Marino /century or equivalent top edges shall have Gamhar wood moulding. Drawer shall run of 'Z' type drawer slides with PVC rollers. All inside portion shall be painted with matt finish enamel paint and all wooden surface shall be melamine/sprit polish. All work to be completed work with necessary and required hardware of standard quality as per approved materials Colour laminate and specifications.		SQ. MTR.	
13	FALSE CEILING (GYPSUM TILE GRID)	Providing and fixing of Gypsum tile false ceiling tile of size 600mm x 600mm x 12mm with square / tegular edge at all heights laid on Prelude XL Hot dipped galva-nized exposed grid with 15 m with T-Section exposed flingers which shall be powder coated white. The framework will comprise of main Runner made from 0.33 mm thick GS sheet and of size 24 mm x 38mm x 3600 mm and spaced at 1200 mm centre securely fixed to the structural soffit by approved hangers at 1200 mm maximum centre. Hangers (GI wire of 4.0 mm diameter) to be fixed by approved Rawl plug, level adjusters and screws etc. All complete work as per drawing, design. Specification and direction of Engineer-in-charge /Bank. The last hanger at the end of each main Runner should not be greater than 450 mm from the adjacent wall. Flush fitting of 1200 mm long cross tee (with double stitching) to be inter-locked between main Runners at 600 mm centre to form 1200 mm x 600 mm modules. Cut cross Tees longer than 600 mm to be supported independent-ly. 600 mm x 600 mm modules top be formed by fitting 600 mm x 600 mm modules to be formed by fitting 600 mm x 600 mm long cross Tee centrally between the 12 mm cross Tee. Perimeter wall Angle shall be of 0.45 thick GS Steel and of size 22 mm and 3000 mm long of white color. The work shall be as per standards and specifications laid down by the manufacturers. Full provision of weight of a/c ducting (if provided) and light fittings, wiring for any use, including cocoordinating with all trades and making any cutouts required for the same, all complete with a minimum of 2 coats of premium quality Acrylic emulsion paint and full finishing for light fittings all complete work as per drawing, design., specification and direction of Engineer-in-charge /Bank.		SQ. MTR.	

		<u>-</u>		1	1
14	FALSE CEILING (GYPSUM)	Providing and fixing in position Seamless Gypsum Board Plain False Ceiling in one or more levels as directed including vertical surfaces between dif-ferent levels. The Ceiling including vertical surfaces is to be done with 12.5 mm thick plain Gypsum boards of approved make, duly finished with recommended filters, tapes, etc. to have a seamless flush look. The ceiling system is to be fixed to a concealed GI framework(Gypsteel Ultra make or approved equivalent) by 25 mm long GI drywall screws at 250 mm intervals along both ways. The framework shall be suspended securely from MS angle hangers fixed to true ceiling surface by dash fasteners. The whole system is to be fitted with all necessary arrangements like perimeter channels, intermediate channels, ceiling sections, ceiling suspension an-gles, rawl plug, soffit cleat etc. The work includes applying two coats of approved putty & primer suitable for Gypsum boards after necessary surface preparation and final painting with approved acrylic emulsion paint on the sur-face. Provisions for openable type lids for facilitating arrangements for rolling shutters are to be made as required. Lids shall be made out of 9 mm thick BWR ply-wood duly painted to match the ceiling surface and provided with 2 No. 75 mm SS butt hinges & 1 No. 100 mm SS tower bolt along the surface. The work is to be completed with all materials, ac-cessories. Labour, tools & tackles and in strict conformity with manufacturers specifications & recommendations. Rate is to include the cost of making openings for ceiling mounted electrical & air-conditioning ac-cessories. All materials should be approved by Bank. Plan area is to be measured for finished wor	38.5	SQ. MTR.	
15	PANELING	Providing and fixing wall & Column Paneling as per drawing & design: The Paneling shall be fixed on a concealed wooden framework of required section placed at 600 mm c/c both horizontally & vertically. The framework is to be fixed by means of Alumin-ium angles of appropriate size for proper fixity. The framework is to be covered by 6 mm thick BWP plywood /Exterior Grade MDF board of Green/Century or equivalent on exposed side with suitable fix-tures. The surface is to be finished with 1 mm thick high gloss laminate of approved shade & make. Provisions are to be made for fixing LED strips. The work is to include all necessary materials, ac-cessories, labour, tools & tackles and also allow provisions for electrical, computer & telephone wiring conduits, switch boxes etc. Executed elevation area is to be measured for fin-ished			
	Α	Interior Columns in Banking Hall	10.92	SQ. MTR.	
	В	With 12 mm thick MDF board fixed on frame fin-ishing paneling surface with high gloss PU paint/1 mm thick high gloss laminate-In the wall.	113.17	SQ. MTR.	
		•			Ī.

16	CEILING	Providing and fixing Ceiling Highlighter panel over transaction	8.5	SQ. MTR.	
		area as per design.	0.0	OQ. WITT.	
	PANEL	The Ceiling Highlighter Panel is a recessed con-tinuous strip			
	1711122				
		with blue high gloss polyurethane coating on its surface and is			
		provided to accentuate the Bank's blue color.			
		The panel shall be made with 12.5 mm thick plain Gypsum			
		board of approved make duly finished with recommended			
		fillers, tapes etc to have a seamless flush look.			
		A cut-out 600 mm wide with desired length is to be made on			
		the false ceiling as directed with GI intermediate channels,			
		ceiling sections, ceiling suspension angles etc. fitted to it as			
		required.			
		The cut-out is to be surrounded by 25 mm wide plain Gypsum			
		sections fixed above & around its periphery by GI screws.			
		The panel board is then to be placed on the Gyp-sum sections			
		surrounding the cut-out and shall be fixed on it by 25 mm long			
		GI drywall screws at 250 mm intervals along the perimeter.			
		The panel board shall have a projection of at least 25 mm			
		beyond the perimeter of the cut-out.			
		The panel board is to be finished with blue paint and high gloss			
		polyurethane coating of approved shade & make on its surface.			
		Provisions are to be made for fixing LED strips.			
		The work is to be completed with all materials, accessories,			
		labor, tools & tackles and in strict conformity with			
		manufacturers specifications & recommendations.			
		All materials should be approved by Bank.			
		Visible plan area is to be measured for finished work.			
		'			
17	ROLLER	Providing & fixing of roller blind (vista level or classic/ or equivalent of	11.15	SQ. MTR.	
17	BLIND	standard make) in off-white or any approved color on all windows &	11.10	OQ. WITT.	
		opening of C.M's chamber. All com-plete with all mechanisms etc.			
		(Note: The area of the blinds shall be measured for payment). All			
		complete work as per drawing, design Specifica-tion and direction of			
		Engineer-in-charge /Bank.			
		Engineer-in-charge /Bank.			
		Engineer-in-charge /Bank.			
		Engineer-in-charge /Bank.			
40	400.00/55			00.1177	
18		Providing and fixing ACP Cover for Rolling Shutter Box :	5	SQ. MTR.	
18	FOR ROLLING	Providing and fixing ACP Cover for Rolling Shutter Box : The cover is to be set with an inner wooden framework of 50	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box : The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections,	5	SQ. MTR.	
18	FOR ROLLING	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c.	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood.	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved shade & make with grooves duly treated with silicon sealant.	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved shade & make with grooves duly treated with silicon sealant. The work is to include all necessary materials, ac-cessories,	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved shade & make with grooves duly treated with silicon sealant. The work is to include all necessary materials, ac-cessories, labour, tools & tackles.	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved shade & make with grooves duly treated with silicon sealant. The work is to include all necessary materials, ac-cessories,	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved shade & make with grooves duly treated with silicon sealant. The work is to include all necessary materials, ac-cessories, labour, tools & tackles.	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved shade & make with grooves duly treated with silicon sealant. The work is to include all necessary materials, ac-cessories, labour, tools & tackles.	5	SQ. MTR.	
18	FOR ROLLING SHUTTER	Providing and fixing ACP Cover for Rolling Shutter Box: The cover is to be set with an inner wooden framework of 50 mm x 50 mm well seasoned Ma-laysian sal wood sections, placed at suitable spac-ings not exceeding 600 mm c/c. The framework shall be covered by 12 mm thick BWR plywood. The work is to be finished with 3 mm thick exteri-or/interior grade Aluminium Composite Pan-el(ACP) cladding of approved shade & make with grooves duly treated with silicon sealant. The work is to include all necessary materials, ac-cessories, labour, tools & tackles.	5	SQ. MTR.	

19 WRITING DESKS	Providing and fixing Column-mounted Circular Writing Desk as per design. The Desk is to be fixed to the column along the perimeter through peripheral 19 mm thick BWP block boards/Exterior Grade MDF board of Green/Century or equivalent with angled MS plate support as re-quired. The Desk shall have two parts viz. head and stand. The Head, circular in plan, is to have an average 450 mm projection around the column periphery for facilitating writing. The Stand, conical in shape on elevation, is to be fixed to the column with a projection of 200 mm at the junction with head, and 50 mm at the floor-column junction all around. The head is to be provided with two circular disks made out of 19 mm thick BWP block board. The disks are to be fixed to the column keeping one on top & the other at bottom, 200 mm apart to have pigeon hole-shaped cells. Dividers, made out of 12 mm thick BWP block board sections/ Exterior Grade MDF board of Green/Century or equivalent, shall be provided to pigeon hole cells, 200 mm wide at the openings for keeping vouchers, slips etc. Each of the disks shall have an octagonal shaped hole in the centre around the column. The stand is to be made with an inner wooden framework of 50 mm x 37.5 mm well seasoned Malaysian sal wood sections to have a conical shape as per design. The framework shall be covered with 12 mm thick flexi-ply all around. The work is to be finished with 1mm thick high gloss laminate on the surface. The desk is to be fixed properly on the column by angled M.S plates as required with GI screws. The plates shall be welded firmly with rawl plug in RCC along the vertical surfaces. The inner surfaces are to be finished with French polish. The work is to be completed with necessary lipping & polishing to exposed block board edges. A Glaz-ing on the work top is to be done by fixing of 12 mm thick transparent toughened glass on it with SS stud fittings. All edges of the glass are to be finished with mirror polishing.	1	NO.	
	to exposed block board edges. A Glaz-ing on the work top is to be done by fixing of 12 mm thick transparent toughened glass on it with SS stud fittings.			

19	DROP BOXES	Providing, fitting and fixing Drop Boxes as per drawings: The box shall havean approximate size of 400 mm width, 200 mm depth and 450 mm height. One drop-slit, 200 mm long & 5 mm wide with edges smoothened properly, is to be provided on the top of the box. Thr box shall be provided with a small lockable door with 2 no. 75 mm SS butt hinges and a small SS hasp bolt. The item is to be made out of 12 mm thick BWR block board to a pigeon hole shape. The work is to be finished with 1mm thick high gloss laminate of approved shade. The inner surfaces are to be finished with French polish. The work is to be completed with necessary lipping & polishing to exposed surfaces. The box shall be fixed to a wall or column in the hall at a height of 1.2 m from FFL or as directed. The work is to include all necessary materials, ac-cessories, labour, tools & tackles. Payment shall be made for finished work. Boxes of the following categories are to be provid-ed -				
	i	Suggestion Box	1	NO.		
	ii	Cheque Drop box	1	NO.		
	iii	Voucher Rack	1	NO.		
20	LOCKS	S/F/F Godrej mortise locks/ Night latches including cost of labor &	5	NO.		
		materials etc. to complete job.				
21	GRAHAK MITRA	Providing Grahak Mitra Counter of size 3"-0" x 3'6" with side credenza of 2'3" x 6'0" in approved shape as per design of Bank made up of 19 mm thick BWP grade block board of Green / Century brand/ Exterior Grade MDF board of Green/Century or equivalent and make as above mentioned at item — 1 above, top laminated with 1.0 mm high glosive laminate with all complete work as per drawing, design., specification and direction of Engineer-in-charge /Bank.	1	NO.		
22	SYNTHETIC ENAMEL PAINTING	Providing two or more coats painting with finest 1st quality synthetic enamel paint of Asian paints / ICI Dulux/ Berger Nerolac/ equivalent approved brand of specified colour to give an even after proper scrapping, sand-papering, etc. as per direc-tion of bank.		SQ. MTR.		
23	WALL PUTTY	Providing and applying wall putty of 2 mm aver-age thickness over plastered & white washed walls & ceiling to prepare the surface even and smooth compete as per direction of Bank.		SQ. MTR.		
24	DISTEMPER (ACRYLIC)	Providing two or more coats of oil bound acrylic distemper paint, 1st quality Asian paints / ICI Du-lux/ Berger/Nerolac or equivalent approved brand over a coat of cement primer to give an even shade over newly plaster of parish finished walls & ceilings as per direction of Bank.		SQ. MTR.		
25	PLASTIC EMULSION PAINT	Providing two or more coats of Plastic emulsion paint over a coat of cement primer of ICI, Berger Paints (India Ltd, Jenson & Nicholson (India) Ltd, Shalimar Paints Ltd and Asian – do—to	205.5	SQ. MTR.		
				TOTAL	_	
RS.				TOTAL	<u> </u>	

NOTE:-

^{*} ABOVE PRICE IS EXCLUDING GST.

^{*} GST PAID EXTRA BY THE BANK AS PER RULE.