	BOQ FOR INTERIOR & FURNITURE WORKS OF SBI DIBRUGARH BRANCH						
S.N.	DESCRIPTION	UNIT	QNTY	RATE	AMOUNT		
1	FALSE CEILING WORK						
1.1	Plain gypsum ceiling: Providing and fixing suspended 12mm thick Gypsum board false ceiling with GI framework of standard gauge and as per the specifications of India Gypsum Co. The rate to include painting with lustre paint and making necessary design,pattern & cut outs for light fittings, cove light etc. complete as per design direction by bank. Rate shall inclueds dismantling of existing flase ceiling if any. Make: Gyproc/ amrstrong or equivalent	sqm	532.00				
1.2	Ply ceiling with laminate finish: 12 mm ply fixed on gypsum framed ceiling with 0.8 mm laminet finish. The ceiling shall have necessary cut out for installation of LED light fixture complete in all respect as per instruction by Bank's Engineer in charge.	sqm	21.00				
1.3	Grid ceiling: Providing and fixing suspended false ceiling with 600x600 mm size & 12mm thick mineral fiber ceiling tiles of Armstrong dune or approved make. Suspender, frame work as per manufacturer's specifications. The item to include cost of making necessary cut-outs for lights/air-conditioning grills as per design direction by bank. Make: Gyproc/ amrstrong or equivalent	sqm	130.00				
2	PARTITIONS						
2.1	Full ht Solid partitions with both side Laminate: Fabricating and fixing full height solid partition, made of 9 mm ply approved brand both side and to be finished with not less than 0.8 mm thick laminate of approved brand, color and shade over 50mm X 50mm (thickness not less than 1.5 mm) alluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. All exposed edge shall be covered wit teakwood bidding/lipping of required size with polishing complete in all respect. Rate shall inclueds deismantling of existing partition. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	sqm	160.00				
2.2	Full Ht. Solid partitions with one side Laminate finish and the other side veneer finish with PU polish: Fabricating and fixing full height solid partition, made of 9 mm ply approved brand both side and to be finished with not less than 0.8 mm thick laminate of approved brand, colour and shade on one side and 4 mm thick veneer on other side over 50 mm x 50 mm (thickness not less than 1.5 mm) alluminium section framework of approved brancd at spacing not exceeding 600 mm both ways (horizontal and vertical) Frame should be firmly fixed to the ceiling. All exposed edge shall be covered wit teakwood bidding/lipping of required size with polishing complete in all respect. Rate shall inclueds deismantling of existing partition. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent.	sqm	21.00				

2.3	Full Ht. semi-glazed partitions with one side Laminate finish and the other side with Veneer finish and PU Polish: Fabricating and fixing full height semi glazed partition, made of 9 mm ply of approved brand in both side and to be finished with not less than 0.8 mm thick laminate of approved brand, colour and shade on one side and 4 mm thick veneer on other side over 50 mm x 50 mm (thickness not less than 1.5 mm) alluminium section framework of approved brancd at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. Middile portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick teak wood lipping/bidding with polishing complete in all respect. Payment will be made for the area upto false ceiling only. Rates shall includes dismantling of existing partitions and etching of glass as requierd at site. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent.	sqm	9.00	
2.4	Full Ht. semi-glazed partitions with both side Laminate finish: Fabricating and fixing full ht. semi glazed partition made of 9mm ply of approved brand in both side and to be finished with 0.8 mm thick laminate of approved brand, colour and shade over 50mm X 50mm alluminium section framework at spacing not exceeding 600mm both ways(horizontal and vertical). Frame should be firmly fixed to the ceiling. Middle portion at 900mm to 2100mm height shall have 6mm thick plain float glass fixed with 10mm thick teak wood moulding duly polished. All expose edge shall be covered with teak wood lipping/bidding with polishing complete in all respect. Payment will be made for the area upto false ceiling only. Rates shall include dismantling of existing partitions and etching of glasses as requierd at site. Rate shall inclueds deismantling of existing partition and etching of glasses as per Banks requierments. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	sqm	28.00	
2.5	Low ht. semi-glazed partitions with both side Laminate: Providing and fixing low ht. semi glazed partitions made of 9 mm ply of approved brand in both side to be finished with 0.8 mm thick laminate of approved brand, colour, shade over 50mm X 50mm alluminium section framework of approved brand spacing not exceeding 600mm both ways. Top portion at 900mm to 1500mm height shall have 12 mm thick plain float glass fixed with 10mm thick teak wood moulding duly polished. All expose edge shall be covered with teak wood lipping/bidding with polishing complete in all respect. All exposed edge shall be covered with teakwood lipping of required size with polishing complete in all respect. Rate shall include making provision for fixing of countertop 12 mm glass with on its edges with necessary fixing arrangement as directed. Rates shall include dismantling of existing partitions and etching of glasses as requierd at site. Rate shall includes deismantling of existing partition and etching of glasses as per Banks requierments. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or	sqm	48.00	
2.6	Low ht. Solid partitions with both side Laminate: Fabricating and fixing full height solid partition, made of 9mm ply approved brand both side and to be finished with not less than 0.8 mm thick laminate of approved brand, color and shade over 50mm X 50mm (thickness not less than 1.5 mm) alluminium section framework of approved brancd at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. All exposed edge shall be covered wit teakwood bidding/lipping of required size with polishing complete in all respect. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	sqm	190.00	

3	WALL PANELLING			
3.1	 Wall panelling with 12 mm thk ply with laminate finish: Fabricating and fixing wall/column paneling, with 12 mm thick ply finshied with not less than 0.8 mm thick laminate of approved shade & brand over 25 mm x 35 mm (thickness not less than 1.5 mm) alluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical.) Panelling framework to be secured to wall surface / column surface Design and detail shall be as per direction of EIC and Bank's new uniform colour, layout & elevation policy. Rate shall inclueds dismantling of existing paneling if any. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent. 		33.00	
3.2	 Wall panelling with 12 mm thk ply with 4mm thk Veneer with PU polish finish: Fabricating and fixing wall/Column paneling of CM Chamber, with 12 mm thick ply finshied with 4 mm thick veneer of approved shade & brand over 25 mm x 35 mm (thickness not less than 1.5 mm) alluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical.) Panelling framework to be secured to wall surface / column surface. Design and detail shall be as per direction of EIC and Bank's new uniform colour, layout & elevation policy. Rate shall inclueds dismantling of existing paneling if any. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent. 	sqm	51.00	
3.3	Wall panelling with 12 mm thk MDF with top coat finish: Providing Aluminium frame of approve brand of size 50x25 x1.8 mm thk (finished) comprising of horizontals and verticals at, 600 mm c/c or part thereof with insertion of 25 mm thk glass wool, vertically and horizontally fixed firmly to walls / floors / RCC roof etc. Providing 12 mm thk. MDF Board over the aluminium frame of approved make , finished with required top coat. The cost to include provision for extra framewark as necessary to make provision for skirting, switch boxes, light fittings/ lights etc, making provision for laying conduit etc. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	sqm	15.00	
3.4	Column panelling with 12 mm thk ply with laminate finish: Fabricating and fixing wall/column paneling, with 12 mm thick ply finshied with not less than 0.8 mm thick laminate of approved shade & brand over 25 mm x 35 mm (thickness not less than 1.5 mm) alluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical.) Panelling framework to be secured to wall surface / column surface Design and detail shall be as per direction of EIC and Bank's new uniform colour, layout & elevation policy. Rate shall inclueds dismantling of existing paneling if any. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	sqm	10.00	
3.5	Wall panelling with 12 mm thk ply over wall Surface with SF Laminate finish: Providing and making wall paneling by fixing 12 mm thk. Ply MR Grade/ IS -303 over existing walls on line an level and further finished with 0.8 mm thk. SF Laminate finish complete in all respect. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent. DOORS	sqm	15.00	

4.1	12 MM Toughened Glass Door: Providing and Fixing full glass door made out of 12 mm thick toughened glass , in patch fittings, and with heavy duty floor spring with SS cover plate. The doors to be provided with locking arrangement in patch fittings as well as ss 25 mm dia, and approx. 600 mm long approved model handles. Rate shall inclueds etching of glass area as requierd by Bank.	Sq.m.	10.00	
4.2	Semi Glazed Door: Providing and fixing Semi glazed doors shutter made up of 38 mm thick block board of approved brand and quality, finshed both side with not less than 0.8 mm thick laminate on one side and 4 mm thick veneer on other side of approved brand, colour and shade. Middile portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make Saintgobin/Modigurd) fixed with 10 mm thick teak wood bidding duly polished N C lacquer as per design and direction by bank. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect. Rate shall includes etching of glass area as requierd by Bank.		11.00	
	Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.			
4.3	Semi Glazed Door with one side laminet and one side veneer: Providing and fixing Semi glazed doors shutter made up of 38 mm thick block board of approved brand and quality, finshed one side with not less than 0.8 mm thick laminate and other side 4mm thick veener of approved brand, colour and shade. Middile portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make Saintgobin/Modigurd) fixed with 10 mm thick teak wood bidding duly polished N C lacquer as per design and direction by bank. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect. Rate shall inclueds etching of glass area as requierd by Bank. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/ veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.		4.00	
4.4	Solid Door: Providing and fixing Solid doors shutter made up of 38 mm thick block board of approved brand and quality, finshed both side with 0.8 mm thick laminate of approved brand, colour and shade. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani		5.00	
	/kitply or equivalent. Laminate Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.			

4.5	Solid Door with one side laminet and one side veneer: Providing and fixing Solid doors shutter made up of 38 mm thick block board of approved brand and quality, finshed one side with 0.8 mm thick laminate of approved brand, colour and shade and othe rside with 4mm thick veener of approve dbrand and colour. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.		5.00	
4.6	WICKET GATE: Providing and fixing low height door shutter in back side of SWO counter made up of 38 mm thick block board of approved brand and finshed with 1 mm thick laminate of approved shade and brand as per design and direction of bank. The door shall includes all hardware such as: ss hinge with countersunk ss screw, handle, door coloser, door stoper etc. of approved make. All exposed edge shall be covered with teakwood lipping with polishing complete all respect. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/ veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.		7.00	
5	BUILT IN FURNITURE			
5.1	Low ht storage unit (veneer finish): Providing, fabricating and fixing (450 mm. deep) low height 750mm with 4mm thk. Veneer finish (on external face) storage cabinet including feature cabinet as per drawing consisting of 19mm block board- IS303/MR Grade (Gattani,Archidply, Century), at top, bottom, sides, horizontal & vertical partition, drawers and shutters and 6mm thick ply backing and with 0.7 mm thk. laminate finish on all inside faces .Rate to include cost towards PU Polish, fixing of stainless steel hinges, tower bolts, locks etc. complete in all respects . Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	RM	2.00	
5.2	Low ht storage unit (Laminate finish): Providing and fixing storage units of size 450 mm x 750 mm, made up of 19 mm thick block board of approved brand on top & vertical support and finished with 0.8 mm thick laminate of approved brand on side and top. The storage units shall have openable/sliding shutters made up of 19mm thick plywood and finished in 1 mm thick laminate of approved shade. The storage units shall have intermediate horizontal and vertical shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/bidding of requierd size, stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brancd. The works to include all hardwares such as: castors, brass hinges, ball catchers, locks , handles etc. of Godrej or equivalent.	RM	29.00	

		1		1	,
5.3	Full ht storage unit: Providing and fixing storage units of size 450 mm x 2400 mm, made up of 19 mm thick block board of approved brand on top & vertical support and finished with 1 mm thick laminate of approved brand on side and top. The storage units shall have openable/sliding shutters with locking arrangment made up of 19mm thick plywood and finished in 1 mm thick laminate of approved shade. The storage units shall have intermediate horizontal and vertical shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/bidding of requierd size, stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brancd. The works to include all hardwares such as: castors, brass hinges, ball catchers, locks , handles etc. of Godrej or approved make. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent.	RM	1.60		
5.4	Over Head Storage: Providing, fabricating and fixing (350 mm. deep) Over Head Laminated storages consisting of 19mm block board, at top, bottom, sides, horizontal & vertical partition, shutters with 6mm thick ply backing and with 0.8 mm thk. laminate finish on all exposed faces and enamel paint finish on inside surface.Rate to include cost towards fixing of stainless steel hinges, tower bolts, locks etc. complete in all respects. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	RM	3.00		
6	TABLES				
6.1	Assistant Branch Mnager Table: Supply and installing Table of size- 2130 mm x 1830 mm x 900 mm including cost of side credenza (1080mm x 600mm x 750 mm) made up of 19mm thick Block board all around, finshed with 4 mm thick teak veneer of colour, shade & brand as approved. The table cost to include (pedestal), three drawers of 450 mm wide made with 6mm/12mm ply on telescopic slider and a keyboard tray 250mm wide, CPU stand, foot rest as per design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/ bidding of requierd size stained to match the desk and melamine finished. All inner surface to be finished with mat finish 1 mm thick laminets of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved brand. Locks to be of single control type. Design and detail of the table shall be as per direction of EIC. All the surfaces to be in veneer & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	Each	1.00		

6.2	Officer and Staff table: Supplying and installing Officers & Staff Tables of Overall size - 1680 mm X 1830 mm x 750 mm including cost of side credenza (1230 mm x 450 mm x 750 mm) made up of 19 mm thick block board of approved brand all around and finished with 0.8 mm thick laminate colour, brand and shade as approved by the Bank. The table cost to include (pedestal) three drawers of 375 mm wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard tray 250mm wide with CPU stand and foot rest as per design and direction by Bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/bidding of required size, stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of single control type. Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.		35.00	
6.3	Fabricating and installing Grahak mitra table and cross selling staff table of overall size - 1520mm x 600mm x 750 mm in straight or curved profile made up of 19mm thick block board of approved brand all around and finished with 0.8 mm thick laminate of brand, colour and shade as approved by the Bank. The table cost to include three drawers of 375 mm wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard tray 250mm wide, foot rest & CPU stand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of single control type. All exposed edges to have wooden lipping/bidding of requierd size, stained to match the desk and melamine finished. All the surfaces to be in laminate finish & 8mm thick glass duly finished to be placed on table and necessary cut-out to accommodate wires, edges to be m/c polished, with m.s. powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent.	Each	1.00	

	-			-	
6.4	SWO COUNTER with corian top: Supply and installing new SWO Counters of overall size 1680 mm X 1830 mm X 750 mm, including cost of side credenza (1200mm x 450 mm x 750 mm) made up of 19 mm thick Block board of approved brand finished with 8.0 mm thick FROSTY WHITE QUARTZ CORAIAN only on top and other surface finished woth 1mm thick laminate as approved by the Bank and wooden beading / moulding all round melamine polished. The cost to include three drawers of 375 mm wide made up of 6mm/12mm ply of approved brand on right hand side of the table on telescopic slider with partitions for keeping of notes of different denominations, a keyboard tray 250 mm wide, CPU stand, foot rest as designe and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood.All exposed edges to have teak wood bidding/lipping stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved make. Locks to be of single control type. Design and detail of the counters shall be as per Bank's new uniform colour, layout & elevation policy, with curvature on front with flexi ply finished with 8.00 mm thick FROSTY WHITE QUARTZ CORAIN. Necessary cut to accommodate wires, edges to be m/c polished, with ms powder coated wire manager, complete as directed by EIC and placement as per layout given. Ply/Block Board Make: MR Grade of Century/ Green /Archidply /Gattani /kitply or equivalent. Laminate/veneer Make: Greenlam /Centurylam /Merinolam /Archidlam or equivalent. Corian make: Dupont.	Each	8.00		
6.5	Providing and fixing floor mounted writing desk of size 1200mm x 300mm x 900mm(H) made of 19 mm/ 12 mm ply with 12 mm thick float glass on top and voucher pigeon holes as per design & direction of bank, with laminated boards support.		2.00		
7	MISCELLENEOUS ITEMS				
7.1	Providing and installation of Roller Blinds (Vista/ Alps industries/Legstrong or equivalent) by fixing Roller Tube of extruded aluminium alloy 38-mm O.D. with a minimum wall thickness of 1mm duly anodized.Clutch shall be wrap spring design with high strength fibre glass reinforced polyester assembly and high carbon steel springs to transmit motion from driving to driven members of clutch mechanism. IDLER shall be of high strength Fibreglass reinforced polyester. INSTALLATION BRACKETS shall be of tomised steel powder coated. BOTTOM WEIGHT of the blind shall be provided with aluminium tube powder coated. FABRIC BLINDS will be roller Fabric blinds as per following specification Composition 80% + PVC, Thk. 0.8mm +, UV Block 70%, flame resistant	Sq.m.	10.00		
7.2	Providing & fixing in place 100 mm. Vertical blinds with scotch guard of approved make, quality and colour shade & pattern. Rate shall include necessary fittings, scotch guard treatment on both sides etc. complete. The overlaps should be uniform & adequate.	Sq.m.	26.00		
7.3	Supplying, providing and fixing Godrej Cylindrical night latch lock at cash enclosure doors	Nos	8.00		
7.4	Supplying and Fixing Wall covering as per shade selcted by the Bank's eng and Architect	Sq.m.	19.00		
7.5	Providing and applying Texture paint (Rustic finish) on Made up wall as per approved color , Texture and shade including applying of 2 coats oil primer over the surface compete in all respect as per Banks engineer instruction	Sq.m.	22.00		
7.6	Providing & fixing counter Front 12 mm thick float glass with polished edges, fixed with necessary S.S Brush finish brackets support on wooden partition as directed. Rate shalll includes fixing of frost film as per design & directed, cost of studs, making cut-outs for transaction and voice hole.	Sq.m.	6.00		

7.7	Providing & Fixing 12 mm thick float glass of size 320mm (width) x 1100mm (height) & tapering towards bottom as per the design and shape as shown in Bank's new uniform colour, layout & elevation policy, fixed with silicon and T.W beading support on wooden partition as directed, on either sides of SWO as per design. Rate shall includes etching of glass as directed by bank. All edges of glass shall be duly beveled & polished as directed complete.	Sq.m.	12.00		
7.8	Providing and fixing 12 mm thk soft board (pin-up board), padding, and upholstered with fabric costing not less than Rs.200/- per metre as approved over existing ply surface The edges of soft board to have Teak wood moulding with pu polish.The work shall also include installation of white board of size 600x450 mm along the tightened edges of soft board complete in all respect	sqm	12.00		
7.9	Providing and installation of Vinyl/ Frosted film on Glass and other surface	sqm	12.00		
7.1	Providing and installing of 250mm thk. Planters box by using 19 mm thk. ply For the base including the walls of the box and further finishing the surface by fixing 1mm thk laminate finishing as per architect's choice.		5		
8	SBI HERITAGE ARCHIVE GALLERY				
8.1	Providing,making and installation of HERITAGE WALL AND DISPLAY SECTION with the use of 19 mm thk Ply with 4 mm thick veneer finish. The display unit shall be made as per the Design , layout and elevation drawings as per the specification incorporated. The display section shall be made into three parts upto the height of false ceiling with required intermediate shelves with veneer finish including fixing of 10mm thick clear glass with wooden bead . The middle section of the display unit shall be projected by 75mm. The top edge of the Heritage display unit shall consist of 100x75mm TW cornice and the bottom portion of the show window shall consist of 65x50 mm TW cornice. The display unit finished with 4mm thick natural veneer of Century make and TW cornice shall be finally finished with Natural Pu polish complete as per satisfaction of Architect in charge.The work shall further include openable service shutters from back with highlighter laminate finish pasted at the backdrop of show window including provisiobrand. The works to include all hardware	Sq.m.	12.1		
8.2	Providing and and making of 150mm thk full height partition by using 8mm Thk Ply on aluminium frame and further finishing the surface by fixing of 4mm Thk. MDF board ready for paint finish. The work shall include finished partition extended upto the false ceiling level with required frames upto the main ceiling	Sq.m.	5.96		
				TOTAL	-