

PROJECT NAME-SBI GIFT CITY AT GUJARAT GANDHINAGAR					
PRICE BID - COMPACTOR WORKS					
SR. NO	ITEM DESCRIPTION	TENDER QTY	UNIT	RATE	AMT
	<p>Gernal Note: All works Quoted in the BOQ shall be inclusive of the following: 1) Transportation, overhead charges,loading, unloading &amp; carrying the materials from the staircase from ground floor to 13th floor to the respecive rooms &amp; also including packing &amp; unpacking, cleaning, &amp; carrying away the debris from the premise as directed. 2) Before execution of all works floor protection sheet shall be laid as directed &amp; after completion of works the same shall be removed &amp; carted away.The entire place shall be cleaned to the satisfaction of Engineer In charge.</p> <p>Technical Notes: - All the hardware &amp; fittings as per Architect's approval &amp; specification. - Hardwares &amp; fittings like Locks,Hinges,Channels etc. shall be of Godrej/Annox/Hafele/Hettich or equivalent.</p>				
1	<b>COMPACTOR (DEPTH- 450 MM)</b>				
	<p>Supply and installation of 450mm depth compactors as shown in architectural drawing. It's base frame shall be fabricated in C channel (25mm X 100mm X 35mm), with guide rails of 30mm round bar placed on A.M.S late with end stoppers. Superstructure shall be consisting of knock down type panels in 20/22 G. Shelves, vertical panels, drive cover panels shall be made up of 0.8 thick CRCA prime quality steel design to carry UDL of 70 kgs. Vertical panels shall be connected to shelevs in boltless type. Shelves and vertical panels shall be as per architects drawings and shall be painted with anti-rust epoxy polyester powder coating paint. Central locking system shall be provided on the last unit. each moving unit shall be provided with safety lock which will prevent moving. Trolly drive mechanism shall be supporyed on special grade antifriction bearig with gear and sprockets. Indexing aprrangement shall have acrylic card holders. Finish:The bodies including shelves are given anti-rust surface treatment &amp; are powder coated with epoxy polyester powder. Finish color shall pe approved by APMC / SBI before applying. Drive Type Configuration: The movement of units is achieved mechanically through a PU Drive wheel and 'Sprocket-Chain-Tensioner'arrangement mounted rigidly onto body side. The torque from hand wheel is transfer to drive shaft via sprocket chain arrangement Prior to the embedding of the guide channels with the help of rawl plug &amp; screw, the ground has to be in properly levelled condition. As per the instruction of Architect/APMCE design &amp; drwaings. Mode of meaurment shall be horizontal and vertical dimension of elevated surface. (Make:Godrej,Methodex,Kompress India Pvt Ltd,Guardwell, Durian ) (Location :- 2nd,4th,5th,7th,8th,9th,11th floor)</p>	800	Sq.m		
<b>Sub Total for Compactors</b>					
<b>ADD GST @18%</b>					
<b>GRAND TOTAL AMOUNT INCL. GST (Rs.)</b>					