

	<b>Price Bid for Furnishing of RACPC-2, Nayapalli, Bhubaneswar</b>				
	<b>(See approved make mentioned below the last item)</b>				
1	<b>Wooden flooring:</b> P&L 15mm thick 3 strip wooden flooring of OAK Sailzburg/Noce Imperial/ Noce weathered) prestine Vermont of MIKASA Floor of Greenlam/ equiv as approved by engineer-in-charge including all matching accessories that covers the edge of trasit between other floors, underlays, skirting and profiles etc complete for coference hall.	sqm	26.00		
2	<b>Modular Tables:</b> Providing & supplying Table top with 25mm thickness. Top fabricated out of 25mm thk. MDF Board with 0.6 mm Post forming laminate on top and Balancing core laminate on bottom. All edges will be chamfered and non postforming parts will be finshed finished with PVC lipping of 1mm / 2.0 mm thickness. The top is supported on two nos of board side.Board side are fabricated out of 25 mm thick both sidePrelaminated MDF Board. All exposed will be finshed with 1 mm / 2.0 mm PVC lipping.Two board side is connected with Apron which is fabricated on 18mm MDF board with Decorative Laminate pested on visiable side while the balancer laminate pested on nonvisiable side.All exposed edges will be finished with PVC lipping.The Modesty Panel will be minimum of 600mm high. <b>Make: M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank</b>				
2.a	2100mmx900mmx750mm (AGM Table)	No	1.00		
2.b	1800mmx900mmx750mm (AGM Table)	No	1.00		
2.c	1500mmx750mmx750mm (CM Table)	No	21.00		
2.d	1500mmx600mmx750mm (DM/MNG/ASS Table)	No	4.00		
2.e	1200 mmx600mmx750mm (Associate Table)	No	3.00		
2.f	1050 mmx600mmx750mm (Associate Table)	No	9.00		
3	<b>Modular Workstation Top:</b> Providing & supplying Table top with 25mm thickness. Top fabricated out of 25mm thk. MDF Board with 0.6 mm Post forming laminate on top and Balancing core laminate on bottom. All edges will be chamfered and non postforming parts will be finished finished with PVC lipping of 1mm / 2.0 mm thickness.Each top have one no of Grooumet of 65 mm Dia with PVC covering.Please consider the rate for the necessary Gable End and Modety Panel of 25 mm Prelam MDF and 18 MM Prelam MDF. <b>Make: M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank.</b>				
3.a	Sizes: 1200 mm (L) x 600mm(D) x 25 mm (T)	no	16.00		
3.b	Sizes: 1050 mm (L) x 600mm(D) x 25 mm (T)	No	6.00		
4	<b>Modular Pedestal Unt:</b> Providing & supplying '3-D Pedestal ( Post Formed Top)(Mobile) 'Size: (Minimum 400 W x 495 D x 702 H ). It is mounted on twin wheel lockable four nos of castors and consists of two small drawer and one full drawer.The bottom and sides are fabricated out of 18 mm thick one side prelaimated board. The facia is fabricated out of 18 mm MDF board with laminate finish. The top is of 18 mm MDF board, 0.8 mm thick Post formed laminate on top portion, 0.6 mm thick balancing laminate on back. Back will be of 9mm thick MDF board. The side panels of drawers are fabricated out of MS sheets and bottom with MDF board and assembled with drawer runners for smooth operation. A Singles-locking system is provided. All metal components will be finished in epoxy powder coating. All exposed edges will be 1 mm thick PVC lipping finished. <b>Make: M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank</b>	No	61.00		
5	<b>Modular Partition-Panels for Half Height ( Mimimum 63 mm Thk. Frame).</b> Providing & fitting Alluminium Extrusion /CRCA made panel framework with powder coated ( 40 to 50 micron).The Vertical members to be placed maximum @900 mm centre to centre, will be made from 1.5 mm thk. Alluminium /CRCA members which are interconnected with minimum 4 nos inter horizontal 1.5 mm thk. Alluminium /CRCA member. The horizontal sections made of 1.5 mm. thk. Alluminium /CRCA section. Panels made of 8mm / 9 mm to 9.5 mm / 12 mm thk. prelaminatd MDF board to be hanged on both sides. All slots in Vertical & Horizontal are of dimension 100x20 mm and are meant to carry wire. Two box type powder coated CRCA/Alluminium raceway skirting (128 mm / 146.5 mm / 85 mm wide) to be provided, one at the bottom of the partition and other will be either below the table top or over the table top with wire management system fabricated out of sheet of 0.8 mm mm thk. with appropriate powder coating (40 to 50 micron). All exposed portion will be covered with Alluminium /CRCA trims of 1.5 mm Thk. are provided on top & free end of sides.All caps should be Alluminium /CRCA casting. <b>Make: M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank</b>				

5.a	Providing & fitting Alluminium Extrusion /CRCA made panel framework with powder coated ( 40 to 50 micron).The Vertical members to be placed maximum @900 mm centre to centre, will be made from 1.5 mm thk. Alluminium /CRCA members which are interconnected with minimum 4 nos inter horizontal 1.5 mm thk. Alluminium /CRCA member. The horizontal sections made of 1.5 mm. thk. Alluminium /CRCA section. Panels made of 8mm / 9 mm to 9.5 mm / 12 mm thk. prelaminatd MDF board to be hanged on both sides. All slots in Vertical & Horizontal are of dimension 100x20 mm and are meant to carry wire. Two box type powder coated CRCA/Alluminium raceway skirting (128 mm / 146.5 mm / 85 mm wide) to be provided, one at the bottom of the partition and other will be either below the table top or over the table top with wire management system fabricated out of sheet of 0.8 mm mm thk. with appropriate powder coating (40 to 50 micron). All exposed portion will be covered with Alluminium /CRCA trims of 1.5 mm Thk. are provided on top & free end of sides.All caps should be Alluminium /CRCA casting .				
5.b	Finish : Prelam / Soft Board / Fabric / White Board / Single Glass / Glass on both sides				
5.c	Powder coating is seven to eight Processing Powder coating. There should be ht. adjustment system below the partition so that it can be adjusted upto 20 mm / 50 mm above the floor, if required.The half ht. partition for workstation will be of Prelaminated finish for below the Worksurfaces, while over table top will be either White Board or Magnetic Fabric Board or Fabric or Glass.	sqm	280.00		
6	<b>Key Board Tray</b> ( Size:480 x 180 x 55 mm ) ( MS) made with CRCA steel with 40 to 50 micron seven to eight processing powder coating. It will be fixed with the table with telescopic channel.	No	60.00		
7	<b>Modular Composite Storage Unit:</b> Providing & supplying composite storage unit 900 mm (L)x450 mm(D)x750mm(H). The storage will have '3-D Pedestal (Minimum 400 W x 495 D ) have one site and Rest site will have with one shutter with locking system.The bottom and sides are fabricated out of 18 mm thick one side prelaminated board. The facia is fabricated out of 18 mm MDF board with laminate finish. The top is of 25 mm MDF board, 0.6 mm thick Post formed laminate on top portion, 0.6 mm thick balancing laminate on back. Back will be of 9mm thick MDF board. The side panels of drawers are fabricated out of MS sheets and bottom with MDF board and assembled with drawer runners for smooth operation. A Singles-locking system is provided. All metal components will be finished in epoxy powder coating. All exposed edges will be 1 mm thick PVC lipping finished. <b>Make: M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank</b>	Nos	23		
8	<b>Full height and Low height Partition:</b> (64mm thick) Providing and fixing solid and glazed partition made with GI Channel section 50mmx25mmx0.55mm thick spaced at 600mmx600mm grid and duly finished with <b>6mm MR grade ply and 1mm thick Satin finish Premium quality P-10 greenlam laminate laminate</b> (colour & shade approved by engineer as solid/ teak wood / texture premium quality on each side. The frame shall be properly anchored at true ceiling, wall/ column sides and floor with long screws at 900mm centres. The glass panel shall be 8 mm thick duly supported by 6 mm MR ply and finished with laminate.	sqm	50.00		
9	P&F aluminium section partition made with 50x25mm section finishe with 6mm cement board on each side including doors (3'x7') , handles, cylindrical locks (Gold colour o Godrej make), hinges etc complete for UPS room	sqm	9.00		
10	Wall panelling with Ply board: Providing and fixing aluminium frame 25mmx40mmx0.80mm with a grid of 600mmx600mm duly anchored with wall screws to the walls and finished with <b>6mm MR grade ply and 1mm thick Satin finish Premium quality P-10 greenlam laminate laminate</b> of approved colour and shade*. Price per laminate sheet is Rs 2500 to Rs 2800 per sheet.	sqm	80.00		
11	Column panelling with Ply board: Providing and fixing aluminium frame 25mmx40mmx0.80mm with a grid of 600mmx600mm duly anchored with wall screws to the walls and finished with <b>9mm MR grade Ply and 1mm thick Satin finish Premium quality P-10 greenlam laminate laminate</b> of approved colour and shade to the satisfaction of engineer. Price per laminate sheet is Rs 2500 to Rs 2800 per sheet	sqm	108.00		
12	<b>Modular Circular discussion table</b> Providing & supplying Table top with 36 mm thickness. Top fabrictaed out of 36 mm thk prelaminated MDF with 2mm PVC Edge Binding. The dia of the table will be 900 mm . The top will be supported on the MS Base of minium 400 mm Dia at Bottaom .The base and Top will be conneted with 80 mm dia 1.6 mm Thick Round Tube.All metal componenet will be finished with 50 minimum 50 micron Powder Coating with 7 to 8 Trunk processed. <b>Make: M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank</b>	No	4.00		

13	Storage units 450mm deep: Made with 19mm MR grade Block board on all five sides and 6mm backing ply. Vertical separators shall be provided at each 3' Centres with door leaf of each shutter of 18" wide supported by auto closing hinges. All inside surface shall be finished with 0.80mm thick laminate. Exposed surface including shutter edges shall be finished 1mm thick Satin finish Premium quality P-10 greenlam laminate. Hardware like locks, handles shall be provided. (conferenc hall and RM Chamber). Price per laminate sheet is Rs 2500 to Rs 2800 per sheet	sqm	40.00		
14	<b>Modular Vertical Storage Unit ( Post Formed Finish):</b> Providing & supplying vertical storage unit. All component except top,back & shutters , sides and bottoms are fabricated out of 18 mm prelaminate MDF Board and the back is 8 mm prelaminate board while shelves will be fabricated out of 18mm thick prelaminate MDF Board. The necessary knock down fittings, lock and stoppers will have to be provided. All board component edges are finished with PVC lipping. The 750 mm high VSU will be provided with sliding shutter while 1200 mm high VSU will be provided with openable shutter. The top is fabricated of 25 mm prelaminate MDF Board with Post Formend Finish. There should be minimum of 100 mm skirting and 10 to 20 mm hieght adjustable system at the bottom to adjust unevenness of the floors. <b>Make: M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank.</b> While for				
14.a	1200 mm high there should be two shelves and for 750 mm high there should be one shelf and for 2100 with 5 nos Self along with 4 shutter . All selves will be adjustable.				
14.b	Sizes ( HEIGHT 1200 MM X DEPTH inside 450 MM)	sqm	40.00		
14.c	Sizes ( HEIGHT 750 MM X DEPTH inside 450 MM)	sqm	10.00		
15	P&F 12.5mm thick <b>Gypsum false ceiling</b> of India Gypsum / Saint gobain make which includes G I perimeter channels , GI runners with perimeter of ceiling, screw fixed to brick work/ partition with the help of Nylon sleeves and screws at specified enters. Then suspending GI intermediate channels from the soffit at specified centres with ceiling angle fixed to soffit with GI cleat and steel expansion fasteners, ceiling section having knurled web etc complete. GI channels, runners etc shall be IS marked. Ceiling frame shall be rigidly fixed to the wall, RCC rigidly so that it will not fall down while fixing boards, providing lights, electrical cables, pipes etc. Provision shall be made for light fitting, fire equipment, CCTV equipment. Extra support shall be given if necessary as per site requirement. Ceiling type : Plain, stepped, cove type as directed by engineer.	sqm	350.00		
16	P&F <b>mineral fibre ceiling tiles</b> with Indian Gypsum/ Saint gobain/Armstrong make Rh-95/99 and tegular edge 600x600 x15mm as specified by manufacturer. Installation to comprise main runner at 1200 centres fixed to structural outfits and peremeter channes of required width as per manufacturers specification The work shall be executed as per manufacturers specification. Ceiling frame shall be rigidly fixed to the wall, RCC rigidly so that it will not fall down while fixing boards, providing lights, electrical cables, pipes etc. Provision shall be made for light fitting, fire equipment, CCTV equipment. Extra support shall be given if necessary as per site requirement. (Fine fissured/Pin holes/Dune as approved by engineer in charge)	Sqm	350.00		
17	<b>Modular Glass Door:</b> 900x2100: Providing and fixing 12 mm thick frameless toughened glass (IS-2835).door shutter of approved brand and manufacture, including providing and fixing top & bottom pivot & double action hydraulic floor spring type fixing arrangement and making necessary holes, Door handle (Stainless Steel 'D' or 'H' type of size 300 mm x 19 mm tubular Handle with Grade 304, CE certified, marked & conforming to EN - 1154, of approved quality) ,locking arrangement and stopper etc. for fixing required door fittings, all complete as per direction of Engineer-in charge. All floors & roof. The rate shall include all design, any support (if required) above false ceiling for fixing the partition, Engineering, 3d view and shop drawing (cad & hard copy) including approval from client, labour, T&P, scaffolding, other incidental charges including wastage, enabling temporary services all fitting fixers nut bolts, washer, Buffer plates, fastener, anchors, SS channel laminated glass etc. The above item should be as per specification and sample approved by client. All hardware fittings are stainless steel 304grade. Above item complete in all respect. All floors & roof.	Sqm	4.20		
18	P&F <b>12mm toughened glass</b> in fixed position with patch fittings, duly supported at top, bottom and sides as directed by engineer with edge polish. Cost of extra member for fixing glass ( Aluminium sections, ply, door frames shall be paid extra. (WPC door frame may be provide for fixing the glass)	sqm	4.00		
19	P&F frosted film of Garware make of approved design pattern, shade and colour to glass panels including cleaning glass panels etc complete.	Sqm	30.00		
20	Finishing the wall surface, gypsum ceiling with two or more coats of wall primer mixed with putty.	sqm	750.00		
21	Finishing the wall surface, gypsum ceiling with 2mm average thickness wall care putty and rubbing the surface to receive paint	sqm	750.00		

22	Finishing the wall surface, gypsum ceiling with two or more coats of tractor emulsion paint of two or more coats	sqm	750.00		
23	P&F <b>35mm thickness MR grade flush door</b> finished with 6mm thick teak wood lipping on all edges duly polished, three SS Hinges for each door, one door stopper, one mortise lock combo set per door finished <b>with 1mm thickness laminates on one side and 1mm thick satin finish greelam p-10 laminates approved shade and colour</b> (solid and glazed with 5.5mm thickness float glass). Price per laminate sheet is Rs 2500 to Rs 2800 per sheet	sqm	12.00		
24	P&F 28mm thick <b>WPC door</b> including hinges, teak wood lipping with all accessories (handles, locks etc complete as directed by Engineer. Make: Black cobra/ Kit ply/ SNG as approved, Hinge: Dorset/ equiv. Toilets and utilities areas	sqm	9.00		
25	P&F Wood Plastic Composite ( <b>WPC</b> ) <b>door frame</b> 4"x3" including all accessories (holdfasts, bolts etc) as directed by engineer in charge. Make: Greenply/Saburi ply/ Kit ply/MBPL as approved for door frame	Rm	52.00		
26	P&F <b>Zebra blind</b> of Vista/ Décor or as per sample approved by engineer in colour and shade in Conference hall windows and other openings	sqm	30.00		
27	P&F door closer two speed of Godrej/Ebco/Hettich as approved with all accessories to the doors.	no	9.00		
28	P&F best quality mortise lock with handles, with all fixed accessories (SS colour) to the doors. Make: Godrej/ Ebco/Hettich or equiv as approved	no	9.00		
29	P&F 6mm thick dark brown, blue or any other shade (excluding white or frosty white colour) <b>Corian solid surface</b> duly mirror polished and jointing base material with adhesives as per manufacturers specification to the satisfaction of engineer ; Make: Du point/ Marino/ Green / as approved	Sqm	10.00		

Total Cost excluding GST

**Approved Make**

1	Modular manufacturer	M/s Nutech (9051322159) / M/s New Age Interior (9437020127), M/s Kripa (98610-25542) or equivalent Modular units manufacturer as approved the Bank
2	Laminates: Premium quality P-10 Satin finish	Greenlam, Marino, Royal touch
3	MR Grade Block board / Ply	Century (sainik) /Saburi ply/Green ply (Ecotech)
4	Mortise Lock, Sliding channel, Multipurpose locks, Door closer, floor spring, KBT	Godrej, Hettich, Ebco
5	MDF Board interior grade	Century, Green, Saburi ply
6	Paints, primers	Asian, Berger, ICI Dulox
7	Putty	JK white, Birla white, Asian
8	Glass	Saintgobain, Asahi, Modi
9	Wooden flooring: (15mm thick)	Greenlam (Mikasa), Armstrong/equiv as approved by engineer-in-charge,
10	Handles of glass door	Godrej/ Ebco/ Hettich, Ebco
11	Concealed handle, D-type handle	
12	Wood plastic door frame	Saburi, Black cobra. Kitply
13	Flush door	Greenply/Centry/Saburi ply
14	Gypsum ceiling	Saintgobain / Indiagypsum
15	Grid ceiling	Armstrong/Saingobain/India gypsum

Signature of contractor