	PRICE BID OF ELECTRICAL WORKS FOR STATE BANK OF INDIA, NSM , MANDI DABWALI HARYANA BILL OF QUANTITIES (ELECTRICAL INSTALLATION)						
5. No	SUB HEAD 1 (COMPUTER POINTS AND DISTRIB) TION	Quantity	Units	Rate	Amount		
1.1	Supply all materials, receiving, storing, handling, fixing and laying 3 x 2.5 sq.mm PVC insulated copper conductor armoured cable and fixing of cable on wall with suitable size of clamps/saddles or laid in floor or recessed wall including cutting of floor/wall for computer points with suitable size GI Box with modular plate and cover in front including providing and fixing 3 no. 5 amp 5 pin modular sockets controlled by 1 no. 5 Amp switch with indicator (to be provided above the table top in partition) connection end terminations with suitable size of glands etc. complete as	20.00					
	trouned (Only two points can be connected in series with single cable) 4 points for CM Cabin, 2 points per Manager Seat, 2 point per Counter, 2 per N/W Rack	28.00	each				
	as per the drawing provided.						
1.2	As per nem 1 above but with 2 no. 16 amp 5 pin modular sockets controlled by 1 no. 16 amp modular switch and 6 am indicator Lam including the cover plate. (For ATM)	2.00	each				
2	As per item 1 above but with 1 no. 5 amp 5 pin modular sockets controlled by 1 no. 5 amp modular switch including the cover plate. (For T.V on Pillars/ Machines / Premium Customer						
3	Lounee: Providing and fixing, testing and commissioning of Heavy Duty modular air-conditioning plug & socket arrangement:	4.00	each		:		
3,1	25 amp air-conditioning point modular type socket { to be fixed 1.5 foot below false ceiling } with 25 amp DPMCB C SERIES { to be fixed at Normal Height }.	6.00	each				
4	As per the Plan provided by the Architect. Supply, installation, testing and commissioning of following capacity 3 pin metal clad industrial type plug and socket arrangement with plug top, cap and chain controlled by under noted capacity: (Make: Hav lks/HPL/Standard/Legrand/L&T)						
	30 Amp with 32 Amp. DP MCB for A.Cs (for 2.0 TR Cassette AC's) To be fixed in Panel Room	6.00	each	*			
5	Point Wiring Wiring for light point/ ceiling fan point/ exhaust fan point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit ISI Mark, with 6 Amp modular switch, modular plate, suitable GI junction & switch boxes & clip and carthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required. (Wires Make: Havells/ RR Kable / KEI/ Finolex) (Switches: Make: Anchor/Crabtree/North-						
1)	Single 6 Amp Switch controlling 1 light point for T-5, exhaust Fans, Ceiling fan and other seprate						
'ו (ני	room supply only Single 6 Amp Switch controlling 4 no. LED downlight / 2 no. 2'- 0"x 2'-0" 36 watt light fittings	30.00	110				
()	Single 6 Amp Socket controlling by 5 Amp Modular switch in switch boards etc complete as	45.00	no.				
	wouned Extension of wall fans:	8.00	110.				
.d)	Extension of points with 2 x 1.5 sq.mm. PVC insulated copper conductor cable in suitable dia MS conduit in recess conduit wiring system for wall fan points with modular switches of 6 amp (to be fixed at Normal Height) and 5 amp 5 pin modular sockets { to be fixed 1.5 foot below false	20,00	no.				
6	Circuit Wiring:						
a)	Circuit wiring from the MCB/ALCB from the Distribution Board to the Switch Board with 2 x 2.5 sq.mm + 1-1.5 sq.mm copper conductor (FR) in PVC Conduit concealed/open and making good the damaged surfaces as per direction of the Engineer-in-charge, including the cost of the	6.00	Each				
7	Supply and Installation of Points for Wiring for power plug point (Raw Power Point) 16A with 2 x 2.5 sq.mm - 1 x 1.5sq.mm copper conductors . including the modular switches, sockets and plates Including the cost of 2mm thick PVC conduits. (Switches: Make: Anchor/Crabtree/North-West/ MK) (Wires Make: Havells/ RR Kable / KEI /Finolex/		each				
	1 points for CM Cabin, 1 point per Counter, 2 for Pantry and 1 for VIP Room as per the drawing provided. Extra points only as per requirement.						
8	Providing at laying following sizes of PVC insulated copper conductor cable of 1100 V in flexible/PVC conduit with accessories such as glands, bends etc.(as per requirement) including making necessary Inter connection etc complete as reqd.						
a)	2 x 6 su, mm with 1 no. suitable PVC insulated earth wire	15.00	inti.				
9	Supply Installation, testing & commissioning of factory fabricated distribution board rust inhibited, powder coated Sheet sheet fabricated comprising of incoming & outgoing isolator & M.C.B's neutral link or neutral bus,top and bottom detachable entry earthing bolts Interconnection and grouting bolts etc complete as reqo. as per details below:-						
a)	8 way MCBDB comprising of 1 no 63 amp DPMCB "C"Series and 6 no 6/10amp SPMCB's "C" SERIES. (for the UPS points each DB to be connected to 12 UPS points i.e only two points shall be connected with one MCB)	3.00	each				
b)	4 way TPNDB compusing of 1 no. 100 amp 4 pole isolator and 6 no. 32 amp DPMCB (for A.Cs). DPMCB must be of C Series.	2.00	each				
c)	4 way TPNDB comprising of 1 no. 63 Ampere TPN MCB "C" Series and 6 nos. 16 amp and 6						
d)	nos. 10 app SPMCB "C" Series. (For Powir Point Circuits). 4 way TPNDB comprising of 1 no. 63 Ampere TPN MCB "C" Series and 12 nos. 6/10 amp SPMCB "C" Series, (For Light Point Circuits).	1,00	each				
	TOURTED COCHES, IFOI EIGHT FORK CITCHES).	1,00	Caul				
e)	4 way DB com rising of 1 no. 100 amp 4 pole Isolator (for UPS I/C Branch & ATM)	2.00	each				

. No	Item	Quantity	Units	Rate	Amount
10	Supply, fixing and testing of following 3 pin metal clad industrial type plug & socker arrangement				
	with plug top cap & chain controlled by 1 No. MCB (Make: Havells/HPL/Standard/				
	Haser/Le rand/L&T				
a)	20/25 amp with 20/25 amp SPMCB { UPS O/G 3 Branch & 3 ATM}	6.00	no.		
lı)	32 amp with 32 amp SPMCB { UPS I/C 3 Branch & 3 AT31 }	6.00	110.		
11	Providing, fixing, testing and commissioning of 15 Amp Power Point modular type socket with 25				
	amp DPMCB C SERIES along with Plug or the rooms so that the supply is connected and when				
	the plug is inserted in the socket outside the rooms for fire safety {1 each for Record Room }				
	The program of the control of the co	2.00	no.		
12	Providing & fixing suitable size of MS box fabricated with16 S.W.G.M.S. sheet either In recess				
	wall or on surface to accommodate dedicated earth from earth electrode and further distribution of				
	earth to computer points including providing 5mm backalite sheet on base connector strip and				
	painting of box etc complete as regd.	2.00	job		
	TOTAL SUB-HEAD -1			RS.	
	SUB HEAD 2 PANELS & CABLES)				
ì	Providing & fixing 3 No. 200 amp kitkats (fuse carrier & base) with 1 no. neutral link on suitable				
	size of backalite sheet of thickness not less than 6 mm etc. complete as regd.	1.00	job		
2	ESSENTIAL PANEL				
	Supply at site installation, testing & commissioning of panel fabricated with 16 S.W.G.M.S. sheet.				
	The panel shall be free standing type totally enclosed dust & vermin proof construction with				
	rubber gaskets. The floor mounting panel shall have ISMC mounting channels, G.1. earth bus bar,				
	bus bar chamber cable alleys interconnections with solid bar/PVC insulated copper conductor as				
	per requirement, and suitable supports of bus bars. The panel shall be painted with 2 coats of				
	enamel paint (grey shade)over the primer and shall also be provided with designation of incoming				
	INCOMING				
a)	160 amp MCCB 4 pole with 35 KA breaking capacity at 415 Volts/ HIGHEST AVAILABLE.				
b	1 set of 200 amp TPN aluminium busbar chamber				
c)	I no 0-500 V Volumeter with selector switch in a separate compartment and amp meter with				
	selector switch and one set of CTs (3 no.) with CT ratio 200/5 A with LED type indication lamps				
	with protection fuses in a separate compartment				
	OUTGOING				
a)	3 No. 100 AMP 3 pole MCCB and 3 No. 63 AMP 3 pole MCCB (MCCB'S WITH 25KA				
,	BREAKING CAPACITY at 415 Volts.) (For A.C D.B, UPS, Light & Power Points)	1.00			
		1.00	set		
	In Panel for All MCCBs connected the interconnections must be with solid Bus Bar only.				
3	Supply, installation, testing & commissioning of PVC insulated PVC sheathed armored cable of				
	1100 V (IS-1554 part I) and fixing of cable on wall with suitable size of clamps/ saddles or laid in				
	floor/recess wall including cutting of floor/wall and making good the damages etc. complete as				
	reed of following sizes - (Make: Havells/ RR Kable / KEI/Finolex/Pymen)				
a)	3.5 x 50 sq.mm. aluminium conductor with 2 no 8 S.WG.G.1. wire (from the Meter to the				
	Change Over and from the Genset to the Change over and from change over to the Essential				
	panel I/C	30.00	per mir.		
b)	3.5 x 25 sq.mm. aluminium conductor with 2 no 8 S.W.G G.1 wire (from Essential panel to the				
	AC DB, UPS I/C Heating D.B.)	60.00	per mtr.		
c)	3 x 6 s mm copper conductor (for UPS DB)	60.00	per mtr.		
d)	4 x 10 sq.mm, aluminum conductor with 1 no. 8 S.W G. G.1. wire (from the Essential panel to				
	the Lighting DB & ATM UPS I/C	45.00	per mtr.		
e)	3 x 2.5 sq.mm. copper conductor (for the Air-conditioning wiring from 4way TPNDB to A.C				
	Socket	80.00	per mtr.		
4	End termination with Brass compression glands including providing lugs/ferruls and making				
	necessary connections etc. complete as reqd. of following sizes:-				
a)	3.5 x 50 sq. mm. aluminium conductor	4.00	each		
b)	3.5 X 25 sq.mm aluminum conductor	8.00	each		
C	3 X6 s j. mm Comper conductor	6.00	each		
d	4 X 10 s ₀ , mm aluminium conductor	2.00	each		
cl	3 X2.5 sq. mm Copper conductor	20.00	cach		
5	Providing & fixing suitable size of angle iron frame suitable for installation on wall/floor				
	including grouting of frame &painting etc. complete as reqd. comprising of the following: (Make:				
	Havells/HPL/Standard/ Legrand/L&T)				
a	1 NO.4 pole 200 amp capacity changeover switch.	1.00	job		
6	Providing & fixing 16 S.W.G.M.S.sheet adaptor box, and also base frame for installation of				
	M.C.B.D B s plug & socket arrangement and to cover cables in system room including painting				
	etc. complete	2.00	sq.mtr.		
	TOTAL SUB-HEAD 2			RS.	
	SUB-HEAD_3 (EARTHING)				
	Supply & fix copper plate earth station with 600x6000x3 mm thick copper plate including all				
1					
1	accessories such as watering pipe & funnel and providing masonary enclosure at top with cover				
1	accessories such as watering pipe & funnel and providing masonary enclosure at top with cover plate i/c excavation of pit supplying & filling of salt charcoal, refilling of pit ete complete as requ				

. No	. Item	Quantity	Units	Rate	Amou
2	Supply & fix G.I. plate earth station with 600x600x6 mm thick G.I. plate including all accessories				
	such as watering pipe & funnel and providing masonary enclosure at top with covel plate i/e				
	excavation of pit, supplying & filling of charcoal, refilling of pit etc complete as regd as per IS				
	3043-1987 (for the neutral earthing from the point of neutral link beside the fase connection				
	and second for the body earthing connected to bothe panel body and the ups base panel [4] 1	2.00	0.31		
		2.00	set		
	Chamber for the earthing shall be available at site without it the earthing cost shall not be				
	paid for all the Earthings. You are also required to provide picture of earthing taken at the				
	time of execution of the same.				
3	Supplying and laying 20 mm X 3 mm copper strip at 0.50 meter below ground as strip earth				
to the section of the sec	electrode, including connection/ terminating with nut, bolt, spring, washer etc. as required	5.00	per intr.		
4	Supplying, fixing & termination of 20 mm X 3 mm GI strip with earth station below ground level				
	and on wall saddle etc complete as reqd.	10.00	per intr.		
5	Providing & fixing 8 S.W.G Copper earth wire on surface or in recess for loop earthing etc. as				
	rend.	20.00	per mtr.		
6	Providing & fixing 8 S.W.G G.f. earth wire on surface or in recess for loop earthing etc. as reqd.	30.00	per intr.		
7	Supply & laying following dia 2 mm in thickness PVC pipe under floor or in recessed walls from				
	earth electrode to UPS room for computer dedicated earthing, for data cabling, electrical cabling				
	etc. including providing 1 no. G.I. pull wire for data cabling making good the damages etc.				
	wherever re. jd.	50.00			
)	25mm	50.00	per mtr.		
	TOTAL SUB-HEAD - 3				
	SUB HEAD 4 (NETWORKING)				
l	Wiring for computer networking starting from mounting rack with UTP CAT-6 cable in 2 mm				
	thick 25mm dia ISI mark PVC conduit with accessories such as bends, junction boxes including				
	providing and fixing I/O plates and SMB complete with all networking accessories etc complete as				
	TO A TANGE OF A SECULOR OF SAME OF SAM	30.00	no.		
	3 points for CM Cabin, 2 points per Manager Seat, 2 point per Counter, 3 for ATM and in				
	Hall as per the drawing provided.				
2	Supply, installation, testing and commissioning of 24-port Patch Panel	2.00	no.		
3	Supply installation, testing and commissioning of mounted rack 12U height made of powder				
	coated MS sheet.	2.00	no.		
4	Supply, fixing and commissioning of patch cable Cat-6 complete with 2 no connectors etc.				
	complete as read.	1			
a)	2m long	30.00	110.		
b)	Im long	30.00	no.		
5	Wiring for telephone points with 0.6 mm dia 2 pair insulated annealed tinned electrolatic copper				
	conductor in 2 mm thick 25 mm dia ISI marked PVC conduit complete with accessories such as				
	bends, junction boxes etc. with suitable size of G.l. box modular plate and cover in front on				
	surface or in recess including providing and fixing modular type telephone socket outlet and	50.00			
	making necessary connections etc. complete as reqd. (Make: Dglink/KEI/Finolex)	50.00	no.		
5	Supply, fixing and commissioning of 20 pair tag Block Box i.e FRP/PVC/Metal junction box with				
	KRONE disconnection module necessary tag for identification for the telephone points (box and	1			
	strips Krone make	1.00	110		
7	Providing, Laying, testing & commissioning of 20 pair telephone cable from outside govt. / bsnl				
	DB to Rack for lease line, ISDN of Make: Delton, finoley, polycab,	12.00	per intr.		
	TOTAL SUB -HEAD 4			RS.	
	SUB-HEAD 5 (AIR CONDITIONING PIPING WORK)				
	Supplying & Laying of following COPPER REFRIGERANT PIPING Thickness 22 SWG For Hi-				
1	wall Split AC complete with fittings Suction / Discharge line insulated with 12 mm SUPERLON /				
	ARMAFLEX suction line. Multi-runs between Indoor & Outdoor units shall be considered as				
	ONE length for the purpose of measurement.	50.00			
1)_	1/4" + 1/2" Refrieerant Corper piping - For Hiwall Split AC's (1.0Tr / 1.5Tr)	60.00	per mtr.		
)	5/8" + 3/8" Refrigerant Cooper piping - For HWS/Cassette AC (2.0Tr / 3.0Tr)	75.00	per mtr.		
2	Supply and laying following dia 3.38mm (confirming to ASTM D1785 standard) in thickness,				
	heavy duty PVC pipe under floor or recessed in walls for AC drains, { To nearest To including				
	bends. Tees etc as required complete in all respect (Make: Diplast/Supreme)	90.00	per intr		
3	Cutting of floor/wall for laying of refrigerant/drain pipe including making good the damages etc.				
-	Complete as required.	70.00	per mtr.		
4	Electrical flexible cable of 3 x 2 5sq.mm FRLS Cu cable multi strand suitable for 2 Tr H.W Spiin				-
. 1					
	& 1.5 Tr H.W Split, Multi-runs between Indoor & Outdoor units shall be considered as ONE	210.00	par untr		
	length for the purpose of measurement, Make: Havells/ RR Kable / KEI/Finolex) TOTAL SUB -HEAD 5	210.00	per mtr.	RS.	

S. No	ltem	Quantity	Units	Rate	Amount
	SUB HEAD 6 (SUPPLY AND INSTALLATION OF FANS AND FIXTURES)				
1	SITC of 2"x2" Celing grid 33-36 watt LED panel fixtures with essential driver in false ceiling				
	including making necessary arrangement for mounting the fixtures and connection with 2 x 1.5		ļ		
	sq.mm insulated copper cable from adjacent point in PVC flexible pipe etc Complete as read.				
	Make Philips cat. RC 380 B- LED-30-6500PSE OD WIL or equivalent of Wipro / Bajaj.	34.00	110.		
2	SFTC of 15 watt LED fixtures /dowlighters with essential driver in false ceiling including making				
	necessary arrangement for mounting the fixtures and connection with 2 x 1.5 sq.mm insulated				
	copper cable from adjacent point in PVC flexible pipe etc complete as reqd. Make Phillips cat 4.0.				
	DN - 192 - 1000 or equivalent of Winro / Bajaj.	60.00	no.		ļ
3	SITC of 5 watt recess mounted LED down light with assembly complete with including making				
	necessary for mounting the fixtures and connection with 2 x 1.5 sq.mm insulated copper cable				
	from adjacent point in PVC flexible pipe etc complete as read. (Make: Philips/Wipro/Ba'a)	6.00	no.		
4	SITC of 18 watt of T5 LED fixtures directly on ceiling / wall including making necessary				
	connections with 2x1.5 sq.mm insulated copper cable conductor wire etc. complete as reqd. Make				
_	Phillips cat no. DN - 192 - 1000 or equivalent of Wipro / Bajaj.	15.00	110.		
5	Supply of 450 mm sweep Metal Body Crompton greaves (or equivalent) SDX BLCK GOLD / SSTROM				
	2 wall fan etc 1325 rpm High Flow Model with 2 Pin Plug complete as required. (M/s equivalent of Bajaj / Havells/Usha	15.00	110.		-
6	LED Strip light (4,5/5 watt) for cove (M/s Phillips /Wipro / Bajaj Complete in all respects with		no.		
	suitable drivers. (Blue / Warm White)	80.00	per mtr.		
7	SITC of 1200 mm CEILING fans complete as reqd. (M/s Crompton High Breeze or equivalent of		J.C. 1111.		
	USHA / Bajaí).	5.00	110.		
8	SFTC of 200 mm exhaust fans complete with self opening louvers / shutters including necessary				
	frame etc, complete as regd, (M s Crompton High Breeze or equivalent of USHA / Ba ai)	5.00	110.		
9	SFTC of 30 watt LED Street light /Flood light for lighting the front side of the branch (M/s				
	Crompton Cat No. LSTS-30-CDL or equivalent of Philips/Wipro.	3.00	no.		
	TOTAL SUB - HEAD 6			RS.	
	TOTAL SUB-HEAD-I			RS.	
	TOTAL SUB-HEAD-2			RS	
	TOTAL SUB-HEAD-3			RS.	
	TOTAL SUB-HEAD-4			RS.	
	TOTAL SUB-HEAD-5			RS.	
	TOTAL SUB-HEAD-6			RS.	
	TOTAL AMOUNT			RS.	
	DISCOUNT(IF ANY)			RS.	
	GRAND TOTAL			RS.	1
	GST shall be paid extra as applicable				

(IN WORDS) RS
NAME OF CONTRACTOR:
ADDRESS OF CONRACTOR: