

**PRICE BID : S.B.I., RACPC -BAWLA - LOOSE, FIXED & FURNITURE WORK**

NO	PARTICULARS	QTY	UNIT	RATE	AMOUNT
1	<u>WORK STATION/ COUNTER</u>				
	<u>GENERAL NOTES FOR : For all work stations-up to item no 6</u>				
	The W.S. should have <u>READY MADE leg rest</u> . HIGH IMPACT POLYSTYRENE WITH CROME PLATED METAL STRUCTURE				
	There should be provision for <u>cable manager</u> system with necessary cutouts in top surface				
	<u>C.P.U. trolley</u> from Steel with lockable roller supports/ Nylon castors.				
	<u>Key board tray</u> made from CRCA steel duly powder coated. It must have built-in slides which, must have a soft palm rest and a stow-away design of mousepad mounted underneath it.				
	<u>FINISHING DETAILS IN NUTSHELL:</u>				
	1) Table Top : 1 mm thick thick laminate & Burma Teak beading on Edges with lacquer polish				
	2) Front Apron & Sides: 1 mm thick thick laminate & Burma Teak beading on Edges with lacquerpolish				
	3) Facing of Drawers: 1 mm thick thick laminate & Burma Teak beading on Edges with lacquerpolish				
	4) All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
	5) All the wooden surface : polished of approved shade				
	As per drawing and instruction of Architect/Bank Complete				
1	<u>MANAGER TABLE SIZE : 6'-6" X 2'-9" X 2'-6"+ SIDE RACK - SIZE: 3'9"X1'4"X 2'6"</u> with 1 mm thick LAMINATE finish on Table Top , sides & Edges and all other visible surfaces etc complete as follows	1.00	NO		
	Supplying and installation of Table as per the following description : Size 6'-0" x 2'-9". Table top shall be made from 18 mm thick commercial ply wood with 1 mm thick laminate with necessary intermediate support. Table top shall be supported by 18 mm thick commercial ply wood with wooden framing. . Computer Key board of metal of approved make shall be provided. Exposed surfaces of the unit shall have 1 mm th laminate finish <u>ready made Foot rest</u> shall be provided. All internal surface will have 0.60 mm thick balancing laminate				
	Apron (Modesty Panel) & Table side made from 18 mm thick ply wood finished 1 mm laminate Finish All visible area should be in 1 mm laminate finish.				
	The sides/back/base of drawers be made of 12 mm thick Ply wood & Bottom of drawers shall be of 6 mm thick ply wood drawer unit of 1'-4" x 2'-0" x 2'-0" shall be provided using 18 mm thick commercial ply wood having 4 Nos drawers as directed with heavy duty telescope sliding channel of approved make , grouplock, S.S. Handle				
	<u>SIDE RACK - SIZE: 3'9"X1'4"X 2'6"</u>				

	Supplying and providing side cabinet : Having openable shutters as directed. Cabinet shall be made from 18mm thick commercial ply wood with 1.00mm thick laminate. back shall be made from 6mm th commercial plywood. Openable shutters shall be made from 18 mm thick commercial ply wood with veneer finished and approved make group lock, handle, hinges, magnet catch. , Rate includes all necessary provisions for installing computers.			
	As per drawing and instruction of Architect / Bank Complete			
	FINISHING DETAILS IN NUTSHELL:			
2	<u>MANAGERS W.S. - SIZE : 5'-5"X 2'-6"X 2'-6"</u>	1.00	NO	
	+SIDE RACK - SIZE : 3'-3"X1'-4"X2'-6"			
	As / item no. 1 / 01 but with different in size & without pencil drawer. Other specifications remains the same.			
3	<u>OFFICER'S W.S. - SIZE : 5'-0"X 2'-6"X 2'-6"</u>	4.00	NO	
	+SIDE RACK - SIZE : 3'-3"X1'-4"X2'-6"			
	As / item no. 1 / 01 but with different in size & without pencil drawer. Other specifications remains the same.			
4	<u>CODS' W.S. - SIZE : 6'-0"X 2'-6"X 2'-6"</u>	3.00	NO	
	+SIDE RACK - SIZE : 3'-3"X1'-4"X2'-6"			
	As / item no. 1 / 01 but with different in size & without pencil drawer. Other specifications remains the same.			
5	<u>ASST.S' W.S. - SIZE : 4'-3"X 2'-6"X 2'-6"</u>	3.00	NO	
	As / item no. 1 / 01 but with different in size & without pencil drawer/ <u>WITHOUT SIDE RACK</u> . Other specifications remains the same.			
6	<u>RUNNING COUNTER - SIZE: 7' X 2'-3"X 2'-6"</u>	2.20	RMT	
	RUNNING COUNTER with Drawer Unit- 1'-4" W x 2'-0" D, 4 Nos Drawers			
	Providing and fixing RUNNING COUNTER having width of 2'-0" using 18 mm thick Commercial plywood for Top and verticle support at 4'-0" c/c, Providing storage cabinet of 4 drawer Unit at Every 4'-0" c/c,Group lock, SS handle in counter as directed complete. 1.0 mm thick Laminate finish on table Top and front side of shutter. All internal surfaces shall have 0.60 mm thick balacing laminate as directed.[FOR DETAIL REFER DRG NO-08]			
7	<u>MEETING TABLE - SIZE : 8'0" X 3'6" X 2'-6"</u>	1.00	NO	
	BASIC STRUCTURE: The basic structure of the MEETING TABLE shall be made out of 18 mm thick ply wood. with all open edges covered with wooden beading of req. size. The top shall be of 18 mm th. ply + additional 18 +6 mm th. ply patta with T.W.beadding of 2"x 1/2" on external sides & 4 1/2" X 1 1/2" T.W. support to be provided below the top ,can be used for switch board fixing purpose . The middle vertical supports shall be of 18 mm thick ply ,fixed to the base of 18 + 18 mm ply. ,with 1 mm laminate on all exposed side .also cable manager at 2 places.			
	FINISHES:			

	The entire top of the table to be finished with Installation of Solid surface of 6 mm thk. corian. To minimize material usage and facilitate installation a corner block of corian should be made square (Butt) rather than mitered. The edges to be joined should be straight, smooth and clean. Joints should only be made with joint Adhesive for manufacture specification. All corners of a cutout must be rounded to 5mm radius and the edges smoothed, both on top & bottom, all around a cutout. "L" & "U" shaped corners need smooth 5mm radius inside corner. The base of table shall be of 1.00 mm laminate finish			
8	<u>DOCUMENT ROOM TABLE - SIZE : 5'3" X 2'6" X 2'-6"</u>	1.00	NO	
	As / item no. 1 / 08 but with different in size & but it is covered with 1 mm laminate instead of solid surface top. Other specifications remains the same.			
9	<u>DINNING TABLE Approx Size 5'-0" x 2'3" x 2'6"</u>	1.00	NO	
	Supplying and installation of Dining Table of 2'-6" height, 1" x 1.5" ht. T.W beading shall be fixed on border. Top shall be made of 18 mm thick commercial plywood with additional 18 mm thick Ply wood patta of required width on edges with 1.0 mm thick laminate on top of approved shade and supports of the Table shall be made of 2" x 2" T.W. members in a Design as directed. All surfaces not laminated shall be lacquer polished.			
	Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.			
<b><u>II PARTITIONS / GLAZING</u></b>				
1	FULL HEIGHT PARTITITONS			
a	P & F FULL HEIGHT PARTITIONS - PARTLY PANELLED / PARTLY GLAZED including door	46.00	SMT	
	<u>BASIC STRUCTURE:</u>			
	P & F full height partitions made from internal frame work of size 2"x1" x min. 1.5 mm th. Alu. sections, fixed by means of al. angle of 1"x1"x1" size for proper fixity. The entire Alu. frame work shall be covered with <u>12 mm th.MDF</u> on both the sides. All open sides of the framework shall be covered with the <u>12 mm th.MDF</u> to cover the entire thickness of the partition. The upper portion rom 3 ' to 7 ' of the partitions will have 6 / 8 mm th. clear glass required as per size of glass, fixed with 2 1/2"x1/2" (F.S.) wooden molding with suggested grooves to cover the full thickness of the partition.The hinge side aluminum frame shall be in filled with wooden section. The same shall be than covered by 12 mm th. MDF panels to get the flush type partitions.			
	<u>GENERAL:</u>			
	All the gaps either vertical or horizontal shall be filled properly with ideal material. All the vertical members of the partitions shall be carefully inserted / fixed in the floor (without damaging the floor) & also shall be fixed to the structural ceiling for proper strength.Necessary provision shall be made in the partition for ele. Conduits, switch boards,a.c. drain lines & ac's. etc.as req. (The item does not include various door shutters as it being a separate item. The common member of partition and frame of door will be considered in the item of partitions). Only below ceiling area will be considered for measurement purpose, however the partition shall be raised atleast by 3" above the false ceiling level for having fixity for the ceiling & also all vertical member shall be taken up to the slab / beam bottom.			

	P & f of internal door shutters made out of 30 mm th flush door with suggested grooves with 6/8 mm th. clear glass fixed with 10 mm th. wooden molding to cover full th. of the shutter. including 3 Nos 5" long SS hinges with countersunk SS screws, Godrej Mortice lock, S.S Handles, Door stoppers, doorstop of approved make etc. complete as per drawing & instructions			
	<u>FINISHES:</u>			
	All the external plywood components shall be finished with 1 mm th. laminate in on both the sides & also in the thickness of the partition. All external wooden members shall be in melamine matt polish finish.			
	THE PPPG FHP SHALL BE FIXED IN POSITION AS / INST.			
3	P & F <u>LOW HEIGHT PARTITIONS</u> – 4'-0"HT	31.00	SMT	
	As / item no. II / 02a but with <u>different in ht &amp; REGULAR glass</u> . Other specifications remains the same.			
<b>III VARIETY OF DOORS</b>				
2	Providing and fixing UPS door shutter with Aluminium Frame and both side Hilux sheet	1.96	SMT	
	Providing and fixing door shutter made out of 50x25x1.5mm thick aluminium framing at maximum 1'-6" C/C both way with 8 mm thick Hilux Board on both side with painting. Steam beach beading of size 31x 12 mm should be placed around shutter edges, aluminium stoper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Approved make Dead Lock, S.S Handle OF 8", Door stoppers, doorstopper to be fixed as per drawing & instructions. All beadings should be polished.			
4	Providing and fixing "Dorma/Ozone/Godrej " or equivalent make door closure.	8.00	NO	
5	Providing & fixing fire rated metal door( RADIANT) OR EQUIVELENT. size ; 3'0" x 7'	2.00	SMTR	
	'Radiant' Fire Resistant Door Single / Double Leaf Hinge Type (2 Hours Fire Rated)1.20 mm			
	Accessories:			
	S.S. Ball Bearing Hinges - 1 NO			
	Dead Lock with Cylinder - 1 NO			
	S.S. "D" Type Handle (1 Set) - 1 NO			
	Heavy Duty Door Closer - 1 NO			
	GLASS DOORS AND PARTITIONS - 2 NO			
	PANELLING WORK - 3 NO			
<b>IV PANELLING &amp; BOXING</b>				
a	P/F Wall panelling with framing laminate finishing for wall and Pillar etc	20.0	SQMT	
	Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect. .			
b	Providing and fixing 18 mm thick plywood of 4" height skirting with 1.0 mm thick laminate finish runner patta on Storage Top / Table Top if required.etc complete as directed.	9.0	RMT	

c	P/F Wall panelling with framing laminate finishing for wall and Pillar etc /Creating Box for fixing AC machine and concealing of copper and drain pipe and around front side main entrance door top, jambs using 18 mm thick MR Grade plywood with 1.00 mm Thick Laminate as per requirement and drawing etc complete as directed.	47.0	SQMT		
<b>V STORAGE CABINETS</b>					
1	<u>GENERAL PURPOSE STORAGE CABINETS – OF VARIOUS SIZES &amp; VARIOUS HEIGHTS (DRG. NO. 09)</u>				
	NOTE : FINISHES for all storage				
	The entire unit shall be in 1 mm laminate finish on external vertical sides and in balancing laminate finish on internal surface. The wooden borders shall be in melamine matt polish finish.				
1	GENERAL PURPOSE	27.00	SQMT		
	BASIC STRUCTURE:				
	P & F 1'-4" deep storage cabinet. The basic structure of the cabinet including shelves shall be made of 18 mm ply. It will 6 mm th. plywood puthi. For low height storage the top shall be like additional 1/4" ply patta to get 1" thickness . The storage unit should have 18 mm th. ply openable shutters. It should with all S.S hinges, towers bolts, powder coated handle, ball catches, S.S approved make (group lock) multi purpose lock complte. Edges to be finished with teak wood lipping etc have 18 mm th. ply vertical & horizontal fixed shelves. The top will have 1"x1" wooden beading on 1 longer side.				
2	<u>ELECTRIC PANEL CABINET</u>	2.70	SQMT		
	P & F 1'- 4" deep storage cabinet as shown. The basic structure of the cabinet including dividers & shelves shall be made of 18 mm Bison panel sheet. It would not have any puthi but shall have req. additional supports to fix the same to the wall. It will have openable shutters as required & shall be made with 2"x1"x min. 1.2 mm th. Alu. Section framework covered with 6 mm bison panel sheet on all sides with 16. Gu. powder coated perforated S.S sheet as infill material. shutter with approved make handle, hinges, ball catches				
3	P/F PANTRY PLATFORM CUB BOARD SHUTTER / drawer unit	1.30	SQMT		
	Providing and fixing cupboard shutters below pantry platform using 1 1/2" x 2 1/2" second grade T.W members for frame, 18 mm Tk plywood with 1.0 mm lamiante for shutters. Providing 1/2" th T.W beading all around shutter. Providing S.S hinges, Handles, stoppers and magnetic catch as directed.				
	IT WILL HAVE 1 DRAWER UNIT OF 3 NOS OF DRWERS /AS / DRAWING				
<b>VI MIS. FURNISHING ITEMS</b>					
1	PINUP BOARD	1.50	SQMT		
	P & F pinup boards. It consist 12 mm th. soft boards of good density to be mounted over 12 mm ply. & covered with 3/4" x 1/4" beading before putting the fabric. The soft board will be covered with a plain (Basic rate Rs. 240 /- per mtr.) from front and edges. Molding of size: 3/4"x1/4" will be fixed on all four sides & will be finished in melamine polish. (Only soft boards provided other than the partitions will be measured and soft board made in the partitions will be the part of the partition)fabric				
2	Supplying and installation 1'-9" x 1'-9" x 1'-3" height for Corner Tepoy	1.00	NO		

	Providing and making open box structure type Tepoy made out of 36 mm (2X18) thick plywood with all over 1.0 mm thick laminate finish provided with bevelled & diamond polished edges 12mm thick glass top supported on 75 mm X 25 mm SS studs complete as directed. [REFER DRG NO-5]			
3	<u>Frosted polyster film</u>	15.00	NOS.	
	Providing and Fixing Frosted polyster film of 3M (Scotchcal 7725 - 324) or equivalent make over glass surface as per drawing & direction with all labour & materials to the satisfaction of the Architect/Bank as per manufacturer's specification. No deduction will be made for any cutting in the film.			
5	<u>visitors sofa</u>	4.80	RMT	
	The seat shall be made out of 19 mm BB in a box form. The back shall be made out using internal wooden frame work of size 2"x1 ½" covered with 6 mm ply. It shall be covered with 100 mm & 50 mm th. 40 density u foam in seat & back respectively. This should be again covered with 14 mm th. 40 density u foam with madarpat cover on it & upholstered of suggested shade & finish in seat & back on all open visible sides with basic rate of Rs.900/- per meter. It will have wooden handlesas / drawing. outer length with armrest will be considered for measurement purpose. [REFER DRG NO-5]			
6	<u>ROLLER BLIND</u>	27.00	NOS.	
	Supplying and fixing Roller Blind Blackout of approved make with selected fabric of approved design and shade. (Basic Price of Rs 135=00 Per Sq.Ft Including GST)			
6	<u>P/A WALL PAPERS on Digital wall</u>	16.00	SQMT	
	Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft			
<b><u>VI FALSE CEILING WORK</u></b>				
1	<u>P/F GYPSUM BOARD FALSE CEILLING</u>	189.00	SMT	
1	Providing and fixing Gypsum board 12.50 mm thick false ceiling in steps and design using Original Indian Gypsum board with original GI sheet section of Gypsteel ULTRA ( Gypsteel Ultra shall be used) supporting system in line and level. Finishing the surface and applying 3 coats of Plastic emulsion paint as directed complete. Entire work to be done as per standard specifications of Saint Gobin Gyproc India.			
	After completion of work, certificate from Saint Gobain Gyproc Company shall be submitted along with bill stating that work is satisfactorily completed as per their specification.			
	Note : (1) Rate includes making necessary cut-outs for lighting fixtures (2) Pattas if any shall be measured in SqM and not in RMT and paid in SqM (3) Only finished visible surface area shall be measured for payment.			
2	Providing and Fixing of Suspended ceiling system	79.00	SMT	

<p>P &amp; F of modular grid type false ceilings at all heights of 600 x 600 x 15mm armstrong mineral fiber ceiling tiles of type dune supreme ml edge rh – 99 % laid on armstrong silhouette 15mm black reveal grid systems or eq.the frame work comprise of main runner of size 15 x 42 x 3000 mm spaced at 600 mm centers securely fixed to the structural soffit by approved hangers at 1200 mm maximum centers. hangers (BUTTER FYLY CLIP) to be fixed by approved roof plug, level adjusters, screws etc. the last hanger at the end of each main runner should not be greater than 450mm from the adjacent wall. 600mm x 600mm modules to be formed by fitting 600mm long flush fitting cross tees of size 15 x 42 x 600mm centrally between the main runners. Perimeter wall angle of size 19 x 19 x 3000mm secured to walls at 450mm</p>				
<p>maximum centers. finally dune supreme ml edge rh – 99 % 15 mm thick (nrc-0.50, light reflectance &gt; 85 %, cac – 34 db, k value = 0.052 to 0.057 w / m k) micro look edge has to be laid on the 600 mm x 600 mm module. (the same ceiling shall be fixed by using full size tiles only &amp; shall be fixed to the gypsum false ceiling)</p>				
<p>Tiles: mineral fiber acoustical tiles shall be of armstrong adria micro look edges with sanded backing &amp; finished with a reinforced scratch resistance coating on the face side suitable for grids of nominal sizes 600mm x 600mm as per the specification below:</p>				
<p>Type: dune supreme ml edge rh – 99 % tile thickness: 15 mm, humidity resistance: rh 99 %, fire performance: class 0/class1 (bs – 476), noise reduction co-efficient (nrc): 0.50 (average), sound attenuation: 34 db, light reflectance: &gt; 85 %, thermal conductivity: 0.052 – 0.057 w / m k</p>				
<p>Suspension system: suspension system shall be armstrong silhouette 15 mm white reveal suspension system (hot dipped galvanized steel) section consisting of the following members: main runner: main runner shall be t-shaped section with rotary stitch of size 15 x 42 x 3000 mm long, cross runners: size 15 x 42 x 600 mm long, wall angle of size 19 x 19 x 3000 mm long colour white</p>				
<p>The area of the celing where full tile size light fixtures are installed, will be NOT dededucted from the total quantity executed. However the cost of tiles will be deducted from the bill amount. The work shall be executed through authorized applicator of armstrong. The contractor has to submit the certificate from the company for the use of company sections &amp; boards along with the final bill.</p>				
<p>I TOTAL OF ABOVE</p>			Rs.	