STATE BANK OF INDIA ADMINISTRATIVE OFFICE, DURGAPUR

SCHEDULE OF WORKS: INTERIOR FURNISHING WORKS AT SME PURULIA BRANCH

PROJECT : INTERIOR WORKS AT SME PURULIA BRANCH UNDER RBO PURULIA (REGION — VI)

NO	ITEM DESCRIPTION	UNIT	SCHEDULY QTY	QUANTITY	Rate (in Rs.)
1	Modification of existing Metallic Grid-based False Ceiling, to be laid on a 15 mm tee with	Square	15.00	QUANTITY	Nate (III No.)
	white revealing prelude profile grid of 600 mm X 600 mm size in concealed GI framework	Metre	15.00		
	with MicroLook Mineral Fibre board acoustical tegular ceiling tiles.				
2	Full Height Double Skin Partly-glazed Partition in metal stud (GI / Aluminium) framework, to	Square	18.00		
	be placed at 600 mm c/c both vertically & horizontally, with 9 mm thick BWP plywood	Metre			
	skinning & 1 mm thick laminate-finishing with horizontal / vertical grooves including glazing				
	with 8 mm thick clear float glass, fitted with SS patch fittings / polished wooden beading as				
	per direction from 900 mm to 2000 mm for glazed portion				
3	Full Height Double Skin Opaque Partition with same specification of fabrication & finishing as	Square	12.00		
	in Item No. 4, but without any glazing	Metre	10.00		
4	Modification of full height solid partition	Square Metre	10.00		
5	Double Skin Partly glazed Partition, max. 1200 mm high, with same specification of	Square	10.00		
-	fabrication & finishing as in Item No. 5 including partition top, but without any glazing	Metre	10.00		
	(Partition Type 'D')	metre			
6	Partly-glazed Door Shutter, made out of 35 mm thick phenol-bonded solid core flush door	Square	3.78		A Section 1
	and finished with 1 mm thick laminate on both surfaces including glazing with 8 mm thick	Metre			
	clear float glass, fitted with polished wooden beading from 900 mm to 2000 mm for glazed				
	portion, along with accessories such as 4 No. 125 mm heavy-duty SS butt hinges, 1 No. SS				
	handle & 1 No. door stopper for single-leaf door shutter, and / or, a pair of 600 mm SS handle				
	for double-leaf door shutter, with 1 No. SS tower bolt for each door shutter as per direction				
7	Opaque Door Shutter with same specification of fabrication as in Item No. 10 and finishing	Square	3.00		
	with 1 mm thick laminate on both surfaces, but without any glazing (Door Type 'P2')	Metre			
0	Oppose does Shutter May 1200 mm high with some specification	Sauren	3.00		
8	Opaque door Shutter, Max 1200 mm high, with same specification.	Square Metre	3.60		
9	Fully Glazed Door, made with 12 mm thick machine polished toughened glass, fitted with	Square	3.50		
,	heavy-duty floor spring assembly (separate item), SS patch fittings, locking up arrangements	Metre	3.30		
	& a pair of 600 mm SS handle				
-	The state of the s	Cubia Mata	0.47		
10	Door Frames (size : 75 mm X 50 mm), made out of clear steam beech wood or well-seasoned	Cubic Metre	0.17		
	knots-free teak wood, to be fixed to partitions with screw and polished / laminated / painted				
11	finishing Heavy-duty Hydraulic Door Closer to all door shutters of 2100 mm height or as directed	No.	2.00		
11	including fitting & fixing with necessary hardware, screw, etc.		2.00		
12	Inside opening 7-lever Night Latch to all doors of 1200 mm height in Transaction Area	No.	1.00		
	including fitting & fixing with necessary hardware, screw, etc.		2.00		
13	Mortise Lock (Godrej Stella or equivalent) to Single-Leaf Door Shutters of 2100 mm height or	No.	4.00		
	as directed including fitting & fixing with necessary hardware, screw, etc.				
14	Heavy-duty Floor Spring Assembly to glazed doors / double-leaf door shutters of 2100 mm	No.	2.00		
	height as per direction including fitting & fixing with necessary hardware, screw, etc.				
15	Modification of Single Window Counters (SWC) –	Nos	1.00		
16	Front Glass at SWC fascia with 12 mm thick machine polished transparent toughened glass,	Square	1.00		
	fitted with SS patch fittings	Metre			
17	Side Glasses on both sides of SWC with 12 mm thick machine polished transparent	Square	1.00		
	toughened glass, fitted with SS patch fittings	Metre			
18	Branch Head Table – 1800 mm long, 900 mm wide, rectangular in shape, & 750 mm high from	No.	1.00		
	FFL, to be fabricated out of 19 mm thick BWP block boards for work-top, sides & front				
	modesty panel, fitted & fixed by dove-tail jointed junctions, with front modesty panel at 150				
	mm back from front edge of work-top, including a 500 mm wide drawer unit, made out of 19				
	mm thick BWP block boards, having top two drawers of 150 mm depth each & the third one				
	of remaining depth, duly fitted with locks, along with PVC keyboard tray, wire manager, etc.,				
	and with laminate-finishing on exposed surface & polished finishing to inside surface				
10	Officer's Table – 1500 mm long, 750 mm wide, rectangular in shape, & 750 mm high from FFL	No.	1.00		
19	with same specification of fabrication & finishing as in Item No. 18		1.00		
20	Modification of existing officer and assistant table.	No	9.00		
21	Side & Back Storage Units with sliding shutters, overall depth: 450 mm, max. height: 750 mm,	Square	5.00		
21	to be made as per same specification of fabrication & finishing as in Item No. 30 including all	Metre	3.00		
	necessary hardware like tower bolts and having sliding mechanism with polished wooden /				
	PVC slide channels				
22	Rolling Shutter Cover Box Paneling in metal stud / wooden framework, to be placed at 600	Square	3.80		
	mm c/c both vertically & horizontally, with 9 mm / 12 mm thick BWP plywood skinning and	Metre			
	finished with 1 mm thick laminate				
23	Self-adhesive Sparkle Series Frosted Film and / or One-way Vision Film of 3M make as per	Square	14.00		
	design, to be affixed on glazed surfaces as directed with all necessary arrangements	Metre			
24	Free standing Writing Desk, made out of 19 mm thick BWP block boards including provision	No.	1.00		
24	of pigeon hole cells at 200 mm clear distance to one another for keeping vouchers, slips, etc.,				
	to be fixed to the wall / column through stand encloser back with angled MS plate support,				
	with laminate-finishing on exposed surface & polished finishing to inside surface				
	I with laminate-finishing on exposed surface & polished finishing to hiside surface		The state of the s		

out of 12 mm thick BWR block boards including provision of 200 mm long & 5 mm wide drop- slit along with a small lockable door with 2 no. 75 mm SS butt hinges & a small SS tower bolt, to be fixed to the wall / column through proper support, with laminate-finishing on exposed		
surface & polished finishing to inside surface		
TOTAL		

Signature of the Contractor with Official Seal # Bank reserves the right to select any material out of the specified make.

