

PRICE BID -BOQ - FURNITURE WORKS FOR (EMERALD) SBI WELTH LOUNGE- ST.XAVIERS BRANCH

Sr.no	Description	Quantity	Unit	Rate	Amount
	Rate should be inclusive of material,labour,tools, machinery, scaffolding, final disposal of debris, cleaning cutting wastage & removing of all existing furniture items and relocating the same as per instruction by bank etc. All taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills				
I	NEW FURNITURE WORK				
1A	OFFICER'S TABLE- Size 1500mm x 750mm x 750mm	1.00	NO		
	Supplying and installation of Table as per the following description and as designed by the Architect:Table Top: Providing and fixing 19 mm thick IS 303 BWR grade plywood with 1 MM thick laminate with melamine finish with necessary intermediate support. Table top shall be supported by 18 mm thick BWR grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick toughened glass with polished edges. The top level of the glass shall be 750mm. Apron (Modesty Panel) made from 18mm thick BWR grade plywood finished with 1mm laminate.				
	Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick MR ply wood finished with 1mm laminate for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing.				
	Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWR grade plywood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick plywood & bottom of drawers shall be of 8 mm thick BWR grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer. The front ply of the drawers to be overlapping the frame.				
	Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop.				
	All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. All the surface without teak 1 MM thick laminate / laminate / balancing laminate shall be lacquered polished of approved shade.As per drawing and instruction of Architect/Bank work to be completed				
	Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.				
2	COUNTER FOR REFRESHMENT	1.20	RMT		
	Providing & fixing counter of 900 height and 450mm with top 600 mm deep. Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters to be made from 25 mm thk BWR Ply and shelves to be made with 19 mm thk.BWR ply. The top portion of the side and rear storage to be finished with approved 1 MM thick laminate and finished. All the other internal and external surfaces to be				

Sr.no	Description	Quantity	Unit	Rate	Amount
	finished with 1mm laminate of approved shade and All edges to be provide with TW lipping patti finished with melamine polish. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Hafele), SS towerbolts etc. All shutters to be made overlapping the frame Only front elevation will be considered for area calculation. As per drawing and instruction of Architect/Bank, work to be Completed.Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.				
	It will have series of drawers (1 small at top6" HIGHT), made out of 12 mm th. ply sides, 6 mm th. Ply bottom & 18 mm ply front facia & side supports sliding on channels. A wooden member of size: 2 1/2" x 3/4" shall be fixed between drawers& shtters.				
3	WALL/ COLUMN PANELING WITH LAMINATE FINISH.	4.30	SQMT		
	Wall paneling made from 25 x 25 x 1.00 mm thick hollow aluminum sections, over which BWR grade ply of 10 mm shall be fixed and additional 6-8mm ply in layers to create grooves as per the design in the drawing or as directed by Architect, with decorative molding patty on the edges.Providing and fixing in position wooden paneling to column / walls finished with laminate comprising as under:-provision for cove light to be provided at 3' & 7' level to light up the logo wall (i) Framework:- Made out of 25mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb. (ii) Panel Finishing:- Providing & fixing 9 mm thick approved make BWR plywood and additional 6-8mm ply in layers to create grooves as per the design to Aluminum framework finished with 1.00 mm thick approved quality and shade laminate, using approved adhesive, in approved pattern & design, including providing grooves, decorative moldings etc. as per Architectural drawings and as directed at site by the Engineer-in-charge. (iii) Providing approved quality, seasoned, full length, Teak Wood molding 15 mm thick with adequate width as required at site, to all openings, cutouts etc duly polished with melamine polish complete as directed by the Engineer-in-charge at site. (iv) The rate should include cost of necessary hardware, making cutouts / including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in-charge at site. (v) Applying 2 or more coats of melamine polish to exposed edges of paneling, moulded beadings etc. including preparation of surface, sealer coats etc. complete including wastage of material, if any, scaffolding for execution of work at all heights and locations etc. complete.				
	Approved make:- (a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank. (b) Plywood:- Greenply, Century, Duro or equivalent approved by the Bank. (c) Laminate:- Dorby Mica, Greenlam/Century/Archid / Aerolam or equivalent approved by the Bank. (d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank. Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.				

Sr.no	Description	Quantity	Unit	Rate	Amount
3c	BACK PAINTED GLASS + LOGO	4.90	SQMT		
a.	<p>Back painted glass (Lacquer Glass) paneling: Providing and fixing in position wooden paneling to column / walls finished with Back painted (4 mm th Lacquer Glass) comprising as under:- (i) Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed upto 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb. (ii) Panel Finishing:- Providing & fixing 9 mm thick approved make BWR plywood to Aluminum framework finished with 8 mm thick approved quality and make back painted Lacquer Glass panels of required size, rigidly fixed using 3M adhesive / double side self-adhesive tape complete as directed by the Engineer-in-charge.</p>				
b.	<p>Logo:- Providing and fixing in position with SS studs or as directed laser cut Logo as per design made from 18 mm MDF board (exterior grade) and finished with enamel paint</p>	1.00	JOB		
4	SIDE/ REAR CREDENZA- For officer and clerical staff table	2.20	SQMT		
	Low Height Cupboard with Laminate Finish				
A	<p>Providing & fixing Low Height Storage Cupboard of 750 height and 450mm deep. Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters to be made from 25 mm thk BWR Ply and shelves to be made with 19 mm thk.BWR ply. The top portion of the side and rear credenza to be finished with approved veneer and finished with melamine polish. All the other internal and external surfaces to be finished with 1mm laminate of approved shade and All edges to be provide with TW lipping patti finished with melamine polish. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Hafele), SS towerbolts etc. All shutters to be made overlapping the frame Only front elevation will be considered for area calculation. As per drawing and instruction of Architect/Bank, work to be Completed.Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.</p>				
5	FULLY GLAZED DOOR	1.80	SQMT		
	<p>Providing and fixing position 12 mm fully glazed toughened glass door, single/ double shutter, of approx. size 900/ 1500 x 2100/2400 mm Providing and fixing in position frameless glass door shutter made using 12mm thick toughened glass fixed to the partition (glazed / solid / gypsum partitions) using heavy duty floor spring with pivot of approved make including necessary</p>				
	<p>cutting of floor and making the surface good to its original position including all necessary Patch fittings of approved make and fixtures & hardware. Approved make: DORMA Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Handle - TG DIH600 - 600mm length) or equivalent brand fittings from Hettich / Hafele / as per sample approved by the Bank. Rate should also include providing film as per design/ instructions of Bank.Mode of Measurement: Door opening size shall be measured.</p>				

Sr.no	Description	Quantity	Unit	Rate	Amount
6	FULL HEIGHT FULLY GLAZED PARTITION WITH 12MM TOUGHENED GLASS UPTO 7' LEVEL WITH SOLID PARTITION ABOVE 7' LEVEL	14.00	SQMT		
	<p>Providing & fixing full height glazed partition with 12mm Toughened glass of approved make up to 7' level height with solid partition above 7'-0" level up to false ceiling bottom.</p> <p>The glazed panels shall be fixed to the existing floor and false ceiling with all necessary SS brackets (D, C or U type)</p> <p>Vertical joints between the glass panels shall be sealed with suitable transparent sealant.</p> <p>The solid partition above 7'-0" level shall be made with aluminium framework of size 63mm X38.10mm X1.47 mm (0.780Kg /mtr) box section. The spacing of the Horizontal and Vertical members are approximately 600mm c/c (maximum) and the top of the frame shall be fixed to the RCC slab bottom. The exposed surfaces on both sides of framework are covered with 6mm BWR ply finished with 1.0mm thick laminate as per direction.</p> <p>Providing, placing in position & erecting full height partition in desired shape, framework shall be of 50 x 50 x 1.5 mm thick aluminum square section placed at 500 mm c/c both ways or as directed.</p>				
7	FULL HEIGHT SOLID WOODEN PARTITION WITH BOTH SIDES LAMINATE	3.50	SQMT		
	<p>Providing & fixing in position 70mm thick +/- 2mm full height solid/opaque wooden partitions finished with laminate on both sides comprising as under:-</p> <p>(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm (may slightly vary as per unavoidable site conditions) both ways (horizontal and vertical) fixed rigidly on floor, wall / column & ceiling.</p> <p>(ii) Plywood skin:- Providing & fixing 12 mm thick MDF boards on both sides of the framework.</p> <p>(iii) Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design & pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approve quality adhesive complete.</p> <p>(iv) Making suitable cutouts/ openings/ channels for Doors, electrical conduits, cables & switch boards, AC ducts etc including providing necessary wooden supports wherever required and directed at site.</p> <p>(v) Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.</p> <p>(vi) Applying 2 or more coats of approved matching shade and finish, melamine</p>				
	<p>polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.</p>				
	Approved make:-				
	(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.				
	(b) MDF Board:- Greenply, Century, Samrat or equivalent approved by the Bank.				

Sr.no	Description	Quantity	Unit	Rate	Amount
	(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.				
	(d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank.				
A	Chair for Officers (Godrej model- PRIME 0015 ,Revolving HIGH Back with Fixed Loop Arms)	1.00	NOS		
B	Chair for Visitors (Godrej model56101522SD04340, Revolving MID Back with Fixed Loop Arms)	2.00	NOS		
8	Providing & Supplying Sofas, Sofa chairs of various types & categories (Single seater, Two seater & Three seater) etc complete as per the manufacturers specifications as mentioned below. The rights to select & approve the sofas & seating shall vest with the clients. The contractor shall submit brochures of manufacturer at the time of quoting for this item etc complete as per layout. The consultants reserve the right to select the sofas in line with the technical specifications envisaged & meeting the specifications standards expected. (Approved makes: Godrej / Durian / Featherlite)				
B	Two seater sofa	1.00			
9	Center Table (3'-0" X 2'-0" Oval / Rectangular)	1.00			
	Providing and supplying in position oval or rectangular centre table to be made out of 2" X 2" teakwood frame including 12mm thk clear glass top with bevelled edges including bottom glass shelf with etching etc complete. The rate shall also include SS lining design to the teakwood frames including all the necessary hardware, fittings, fixtures as per manufacturers specifications complete.				
10	WOODEN FLOORING + SKIRTING	25.00	SQMT		
	Providing and placing in position wooden laminate flooring with planks of size not less than 1200 mm X 190 mm (with unlinked panels / tongue-groove locking arrangement) having a 0.2 mm thick top abrasive layer followed by decorative layer upon HDF (high density fiberboard) substrate core over raisin saturated backing layer installed using tongue-groove system over 2 mm thick underlayer of polyurethane foam on 250-micron polythene sheet over a smooth, flat, hard and free from moisture floor surface complete in all respect with required accessories like end profile, transition profile, reducer 'T' profile etc. and preparation of base including all other incidental works as per direction & satisfaction of Architect in charge. Cost of Laminate Floor Accessories, Skirting, End edge, T- molding, Reducer shall have to be added in the cost, wherever required.				
11	Polyester Film over glazed partitions:	13.00	SQMT		
	Providing and fixing in position high impact resistant Polyester Films of approved design & pattern, which once installed on glass, give additional strength to glass, reduce glare & prevent glass from splintering on impact. thickness not less than 4 Mil (100 mic.) or 7 Mil (175 mic)				
12	P & F PLAIN FALSE CEILING INCLUDING VERTICAL DROPS	28.00	SMT		
	REMOVING OF EXISTING GYPSUM CEILING CAREFULLY WITHOUT DISTURBING ADJOINING AREA & CARRIED AWAY THE SAME & PROVIDING & FIXING OF NEW GYPSUM CEILING AS PER REVISED DRAWING IS PART OF THIS ITEM.				

Sr.no	Description	Quantity	Unit	Rate	Amount
	P & F suspended gypsum (Saint Gobin) plain false ceiling by using standard company sections (GYPSTEEL ULTRA), which includes providing and fixing g.i. perimeter channels of size 0.55 mm thick having one flange of 20 mm. and another flange of nylon sleeves and screws, at 610 mm centers. then suspending g.i. intermediate channels of size 45 mm, 0.9 mm th with two flanges of 15 mm each from the soffits at 1220 mm centers with ceiling angle of width 25 mm x 10 mm x 0.55 mm thick fixed to soffits with g.i. cleat and steel expansion fasteners. ceiling section of 0.55 mm. thickness having knurled web of 51.5 mm. and two flanges of 26 mm each with lips of 10.5 mm. area then fixed to the intermediate channel with the help of connecting clips and in direction perpendicular to the intermediate channel at 457 mm. centers. 12.5 mm tapered edge gyp board (conforming to is - 2095-1982) is then screw fixed to ceiling section with 25 mm drywall screws at 230 mm centers. screws fixing is done mechanically either with screwdriver or drilling machine with suitable attachment. Standard company manufactured sections (GYPSTEEL ULTRA) should be used for the entire framework. Finally the board of size 6' x 4' are to be jointed and finished so as to have a flush look which includes filling and finishing the tapered and square edges of the boards with jointing compound, paper tape only and two coats of primer suitable for gyp-board (as per recommended practices of india gypsum / Saint Gobin).				
	General notes for the item rate include: The job includes applying two or more coats of acrylic emulsion paint in the standard procedure of the painting job as per shade and finish suggested by the architect. The cut outs for variety of light fixtures and other equipments etc. and the same have to be made with the frame of perimeter channels of size:				
	20 mm. x 27 mm. x 30 mm. x 0.55 mm. thick, supported suitably. no extra will be paid for this. edge bead has to be used to protect the exposed gypsum core i.e. cut edges of opening for light fixtures. "v" grooves should be cut at every square edge joints and filled with jointing compound and paper tape. additional g.i. or c.p. teakwood supports shall be provided for fixing of variety of light fixtures, a.c. continues grill, diffusers etc.				
	The contractor must co-ordinate with electrical & AC contractor for working out various levels for the false ceiling & make the marking on the walls / columns before starting the false ceiling work. All sections visible from the ac grill shall be painted in black color. The final visible plan and elevation area will be considered for the measurement purpose. The work shall be executed through authorized applicator of gypsum india (Saint Gobin). The contractor has to submit the certificate from gypsum india for the use of company sections (all) & boards along with the final bill. The contractor must get the work checked from the company's representative – one on completion of framing work & second on completion of boarding but before putting top coat. The unit measurement will be considered as the sq.mtrs. only. No R.mtr. (running length) measurement will be considered.				
13	COVE IN FALSE CEILING	28.00	RMT		
	Same as Gypsum false ceiling but providing, making, and fixing Gypsum cove (inside height 150 - 200 mm and border 75 mm) to hide strip/cove light in ceiling or to act as pelmet for roller blinds on windows or for projector screen, etc.				
I	TOTAL OF ABOVE				
	SONAL HITESH PARIKH				