A	SCHEDULE - INTERIOR FIXED ASSETS WORKS		
	GENERAL NOTES: -		
	The plywood considered in this estimate shall be of approved make MR ply confirming to IS 303 (as per sample approved by theBANK) for all the items of Interior & Furniture works.		
	All internal framework shall be of Aluminium Sections. All exposed edges of Plywood shall be fixed with C.P. Teak Lipping of size as directed by BANK.		
	The skinning shall be in 12 mm thk Exterior Grade, Phonol Bonded, Teak wood Particle Board confirming in IS3087-1995, Grade-I unless otherwise specified.		
	All exposed veneer surfaces shall be finished with melamine polish . The thickness of the veneer shall be 4.0mm & that of laminate shall be 1.0mm thk. However if the same shall vary, no extra charges are payable for the additional thickness. The approved veneer shall be finished with natural melamine polish of minimum 2 coats to have desired matt melamine finish where ever specified.		
	Measurement of Partition & Panelling shall be limited upto False ceiling .		
	Additional item if executed for AC Melaminerpose shall be measured in the relevant item.		
	The rate shall be also inclusive of Doors(in the partitions),pattas & bands , grooves at any level (in Panelling and Partitions), any design in veneer, textures etc including the necessary framing/ openings for Electrical, Telephone & AC outlets.		
A	PARTITIONS / PANELLING		-
~	General Specification for partition/Panelling :-		-
	Centre spacing approx. and 50mmX38mm size Aluminium sections horizontal at 450mmX600mm Centre-Centre spacing approx. Extra frame below slab soffit for conduit to run above. All verticals shall be secured to the ceiling. But for billing only partition upto false ceiling will be considered. Aluminium sections Make: Jindal,Hindalco, MAAN or equivalant.		
	MAIN FRAME -PANELLING : Main frame comprising of 38mm X 25mm size Aluminium sections of equivalent approved make fixed to wall at 450mm to 600mm C/C in both horizontal as well vertical direction including providing extra frame/members as required as per site condition below beam/slab soffit for running conduit etc.		
	SKIN: -12mm Exterior Grade particle Board shall be screwed to frame work on both sides with joints as shown or directed. Make: Associate / Action Tesa / Eco boards/ Archid / Willson.		
	SKIRTING : In the same alignment,75mm high in 12mm thk teek wood phenol bonded Particle Board with a groove finished with laminate / veneer as the case maybe, or as directed by the BANK.		
	FINISHING: VENEER:- 4mm thk natural venner with matching superior approved grade to be fixed to the plywood having joints as shown or directed complete with melamine polish finish. Make: Century, Duro,Durian, Archid,Century or equivalent approved make.		
	LAMINATE: Laminate shall be of 1.00mm thick of approved make and colour.Make: Royale touche/Century/Green lam/ Merino or equivalent approved make.		
	CALCIUM SILICATE BOARD: Calcium silicate shall be of minimum thickness of 12 mm having fire rating of 4 hrs. calcium silicate Boards should be finished with 2 coats of approved acrylic emulsion paint including POP Melaminenning for surface preparation including necessary grooves, skirting etc complete as shown or directed byBank. Make :Hilux, Ramco hilux or equivalent.		
	POLISHING: Finishing with melamine polish including all the necessary surface preparations, final finish etc complete of approved shade, colour & texture as directed byBANK, including necessary grooves, skirting etc complete.		
	PAINTING: Finishing with 2 or more coats of approved Acrylic Emulsion paint etc including all the necessary surface preparations, final finish etc complete of approved shade, colour & texture as directed byBANK, including necessary grooves, skirting etc complete.		

	Description	Qty.	Unit	Rate	Amount
	Providing & Fixing full height/Low height Semi-Glazed partition with following specifications	938	SQFT		
	Same as above including providing and fixing 12 mm thk. clear glass of (of saint goblin/ Asahai India or equivalent make) approved fixed with teak wood moulded beading duly melamine polished/painted as directed by the BANKs/SBI complete. The rate should include providing and pasting frosted Polyester film of Garware or equivalant approved make & design and as per drawing and as directed by BANK				
		112	COFT		
	12MM THICK GLASS PARTITION Providing and erecting in position full height 12mm thick Toughened Glass (of saint gobain/ Asahai India or equivalent make) partiton fixed on Patch fittings of Dorma/Hefle/Ozone of equivalant approved by BANK including 12mm thick Toughened Glass door, fixed on Heavy duty Dorma or equivalent approved make Floor spring, 30mm dia. & 600mm long S.S handle and locking Assembly from Dorma/Ozone complete.The rate includes providing and pasting frosted.polyester film or bank's approved advertising film of 3M with comMelamineter aided design & cutting in various colours & shade on the glass partitions & Doors.The scope of work includes cutting chases to the floor and reinstating the same to its original position without any extra cost including the cost of other fittings & fixtures & hardware such as spider panels, glass to glass contactors etc complete, making necessary holes, joints to be sealed with silicone sealant on all sides complete in all respects etc as per directions ofBANK.The rate shall be inclusive of bent curved glass panels wherever the partition is curved in profile as shown in the layout plan. Make: Dorma,Hefle,Ozone , Godrej, Dorset or	113	SQFT		
	Equivalent.				
	PANELLING : - General specifications as described in above Finished with 1.0 mm thk laminate of approved make including skirting & band	1444	SOFT		
	at top complete as shown in detailed drawing or as directed. Finished with Gypsum board of approved make including skirting & band at top	1444	SQFT		
	complete as shown in detailed drawing or as directed.	2682	SQFT		
A4	FULLY GLAZED DOOR :	86.00	SQFT		
	Providing and fixing in position 12mm thick toughened glass (of saint gobain/ Asahai India or equivalent make) door including fixed side panel. The door to be fixed with heavy duty Dorma make floor spring, providing 300mm long 25mm dia SS pipe handle and door lock of Ozone/Dorma or equivalent make with necessary cutting chases in floor and restoring the same to its original position complete. Rate to include providing suitable wooden Top and bottom rail, frosted film as per detailed BANKural drawing complete. Make: Dorma, Dorset, Godrej or Equivalent.				
-	FALSE CEILING General :				
	The filler, paper tapes, finishes and primers suitable for Gypsum boards, shall be as per recommended practises of India Gypsum.				
	Framework grid and suspenders shall be fixed to avoid fouling with services such as ducting, sprinklers, electricals fixtures, etc				
	T.W. framing may be allowed in certain areas for the Gypsum Board ceiling with				
	the approval of theBank . The same should have three coats of fire resistant paint. Note: All the hardware such as fastners, hangers, suspenders, etc. required for erection of the false ceiling shall be of INDIA GYPSUM make. And approved by theBank.				
A6	GYPSUM BOARD CEILING :	454.00	SQFT		
	Providing and fixing Gypsum False ceiling (of India Gysum/Gyproc or equivalent make) on the frame work of galvanised iron for suspended false ceiling which includes galvanised iron perimeter channels of size 27 mm & 0.5 mm thick having one flange of 20 mm and another of 30 mm along with perimeter of the ceiling, fixing in brick wall / partition with the help of rawal plugs and screws, suspending galvenised iron intermediate channels of size 45 mm and 0.9 mm thick with teek woodo flanges of 15 mm each from the soffit at 1200 mm centers with steel				
	galvanised iron hanger of width 25 mm x 0.5 mm fasteners,ceiling section of 0.5 mm thickness having curved wedge of 51.5 mm and teek woodo flanges of 26 mm each with lips of 10.5 mm fixed to the intermediate channel with the help of connecting clips and in direction perpendicular to the intermediate channel at 450 mm centers, 12.5 mm dry walls screws at 230 mm centers; fixing screws mechanically either with screw driver or drilling machine with suitable attachment				

Providing and erecting false ceiling of Mineral Fiber ceiling Board Armstrong or equivalent approved make with framework, runners, cross runners & suspenders from the existing ceiling as per the manufacturers details and specification and 600X 600mmX 15mm thk tiles of approved design, texture & in microlook pattern including the grids in black / white silhoutte pattern, 15mm as per manufacturers specifications complete including making necessary cut-outs for electrical fixtures, AC diffusers, access etc as per the instructions of theBank.Approved preminum Tile in Dune RH Microlook category with black silhouette locking supporting system, 15 mm grid. Make: Armstrong /Gyproc.		

A8 BL				
	DLLER BLINDS:	212.00	SQFT	
	ller Blinds of Std Make vista, Mac or Equivalent with steel rod and Accessories of			
Ap	proved colour and brand.			
SU	M TOTAL OF SCHEDULES - INTERIOR FIXED ASSETS WORKS			
	scription	Qty.	Unit	Amoun
B <u>SC</u>	HEDULE - FURNITURE WORKS			
	3: - The plywood considered in this estimate shall be IS: 303 grade MR Plywood			
-	all the items of Interior & Furniture works. The rate shall be inclusive of anti			
	mite coating on all sides to plywood, teak wood & all the other wooden			
	nponents of Asian paints or equivalent approved make. eleton - made out of 19 mm. Thk IS:303 Grade MR Plywood (IS:303) at end			
	ticals, top and bottom and verticals 450mm to 600mm Centres as shown in			
	awing and 6 mm thk back plv.			
	ELVES - 19mm Thk. IS:303 Grade MR plywood finished with approved quality			
0.8	mm thk. Laminate on both faces including edges to accommodate file height			
	novable and supported on pins.			
	UTTERS-made out of 19mm thk. IS:303 MR plywood.			
	NGES - Each shutter shall have 100mm long oxidised brass butt hinges.			
-	nimum 4 nos. hinges for each of the shutter for Full height Storage and 3 Nos.			
	LTS - Flush tower bolts from inside at top and bottom to the shutters and ignetic catch fixed top and bottom.			
	CKS - of approved make 4 -lever brass body dead lock with S.S. Key.			
	NDLES - 100mm wide handles of C.P brass as approved by theBank.			
	IRTING -As instructed, in plywood finished in approved 1.0 mm thk laminate or mm thk veneer with melamine polish.			
	CK - Unexposed back side of storage to have 6mm thk IS 303 MR plywood with	<u> </u>		
	lish.However exposed back of the storage shall be finished with 1.0 mm thk			
	ninate finish.			
	P - To be finished with 1.5 mm thk laminate.			
	W HEIGHT STORAGE	104.00	SQM	
	widing and fixing Low height Storage of ht. 2' 6" or 4'-0" as desired and depth		<u> </u>	1
	18" as specified in the drawings as per specification below.			
Fin	ishing :- All external surface finish with 1.5 mm thk approved laminate .			
	posed top to be finished in 12mm thk approved Corian and shutters in IS: 303			
	ply with Melamine including necessary surface preparation, finishing the same			
	complete. All exposed surfaces shall have beading patti in laminate. Inside			
	ible surface complete with 1mm thk Laminate. Rate shall also include teek wood			
	ulding for the top duly polished wherever instructed.			
	ANCH MANAGER TABLE (Maximum 7'-0" X 3'-0")	1	Nos	
	widing and supplying table for the B.M with side credenza to be made out of			
	mm thk. IS: 303 Grade MR Plywood finished with approved 4.0mm thk high end			
	neer with polycoat polish for the top & melamine polish for all other exposed as. The top of the table to have t.w. moulding all around. The rate shall be			
	lusive of providing a keyboard tray on sliding telescopic channels, wire			
	inager & a pedestal drawer unit made out of 16mm thk IS: 303 MR plywood on			
	e with 3 nos of drawers on Telescopic sliding channels and the side			
	denza. All internal surfaces to be finished in approved 1 mm thk laminate.			
	the external surfaces shall be finished with 4.0 mm thk approved high end			
	neer with melamine polish including the pedestal drawer unit with castors			
	nprising of 3 nos of drawers on side to be finished with approved 4.0 mm			
thk	approved veneer with mellamine polish, etc complete in all respect.			
	e table shall have 12mm thk clear glass (of saint gobain/ Asahai India or			
	uivalent make) on top with bevelled edges. The rate shall also includeheavy			
	ty steel CPU trolley with castors , heavy duty keyboard tray as per the approved			
	ikes. The necessary hardware such as automatic locking, ball catches,			
	e managers etc. to be provided as per the instructions of the BANK. The			
	vation of the table shall be as directed by Bank on site.			
	FICERS/STAFF TABLES (5'-0" X 2'-6")(Laminate Finish)	5	Nos	
	widing and supplying table with Credenza for the Officer to be made out of			
	mm thk IS:303 Grade MR plywood finished with approved 4 mm thk			
	enear/1.5mm thk laminate on the top & all other exposed areas. Edges shall ve Teak wood moulding wuth Melamine polish all around. The rate shall be			
	lusive of providing a keyboard tray on sliding channels, foot rest, wire manager			
	d Pedestal drawer unit with castors comprising of 3 nos of drawers on side			
	be finished with approved 4.0mm thk veneer with Melamine polish, CPU trolley			
	standard make All internal surfaces shall be finished with in 1.0 mm thk			
	singto The side gradeness shall be inclusive. All internal surfaces to be finished in			
lan	ninate. The side credenza shall be inclusive. All internal surfaces to be finished in			

B4 SINGLE WINDOW COUNTERS	3	Nos		
Providing and erecting in position SWO of 5'-0" length and 2'-9" width as	per			
the instructions and drawings to be made out of 18 mm thk. IS: 303 MR Plywe	ood			
for work top and verticals. Top shall be finished in 1.5mm laminate as per				
design.All other exposed surfaces shall be finished with 1.5 mm thk approved	d			
laminate , All internal surfaces shall be finished with 1mm thick laminate.Edge	es			
shall be finished with Teek wood beeding with Mellamine polish. The rate sh	nall			
be inclusive of providing a keyboard tray on sliding channels.wire manager & a	a			
drawer unit on side with 3 nos of drawers on Telescopic channels with inte	ernal			
seperations in ply for keeping temporary cash. The rate shall be inclusive of C	CPU			
trolley of approved make, necessary fittings, fixtures, hardware such as				
channels, hinges, ball catches, automatic locking arrangement, wire manag	jers			
etc .Complete in all respect including side credenza and bevelled Glass seper	raters			
out of 12mm thk glass of (saint gobain/ Asahai India or equivalent make) in F	Front			
of SWO admeasuring approx 5 ' X 2' and to be placed in position with the D-				
brackets including bevelled edging of the glass, etching / frosted film etc com	plete.			
B5 MEETING /DINING TABLE (with Chairs)	1	NOS		
Providing and supplying 4'-0" square/circular dining tables made out of 112mr				
Glass(of saint gobain/ Asahai India or equivalent make) top with design etchin	ng			
pattern with bevelled edges. The table stand shall be of corrosive resistance				
Stainless steel (304) matte finished stand or Wooden Finish Stand of 4' dia.				
complete as per instructions and drawings.				
B6 RUNNING COUNTER (12'X 2.5')	1.00	RM		
Providing and erecting running counter (2'-3")wide to made out of 19mm thk.				
303 MR Plywood . The counter to have lockable heavy duty keyboard trays w	vith a			
pedestal drawer unit				
with 3 nos of equal sized drawers at regular intervals as per the plan in				
19mm thk. IS: 303 MR Plywood with necessary opening for electrical wiring a				
sockets. All exposed surfaces shall be finished with approved 1.0mm thk lami				
and all the internal areas shall be finished 1.0 mm laminate .Edges shall have				
wood beeding with Melamine polish finish, complete as per design & instructi				
The rate shall be inclusive of CPU trolleys, foot rest, wire manager, etc comple	ete.			
B7 CORNER TABLE (2'-0" X 2'-0" Rectangular)	1	NOS		
Providing and supplying in position corner table to				
be made out of 2" x 2" t.w. frame with 12mm thk.				
clear glass (of saint gobain/ Asahai India or equivalent make) top with bevelle	ed			
edges and etching with melamine polish etc. complete.				
B8 WRITING DESK	1	NOS		
Writing desk at entrance area in 18 mm MR and 1.5mm laminate finish surface	e 12			
mm clear glass (of saint gobain/ Asahai India or equivalent make) on top with	1 I			
shelves/partation in glass to keep slip books including acid etching / frosting o	of			
approved design and exposed edges in machine polished.and bank's printed				
broachers for public complete as per BANK's design and instructions. Size: 3'-(0″ x 1′			
6".			_	
SUM TOTAL OF SCHEDULES - FURNITURE WORKS	1	1	Rs.	1

		SUMMARY STATEMENT						
<u>No.</u>	Description	Qty.	<u>Unit</u>	<u>Rate</u>	Ame			
A	TOTAL OF INTERIOR FIXED ASSET WORKS			Rs.				
В	TOTAL OF FURNITURE WORKS			Rs.				
5	SUB TOTAL							